

Chemical Resistant SB[®] | SBS[®] | Powerpole[®]



The new Chemical Resistant (CR) line of connectors were developed for customers whose applications require robust connector solutions that offer durability against environmental factors that commonly degrade standard products. The new housing material offers improved resistance to hydrocarbons and solvents, as well as, an extended temperature range. The CR connectors are ideal for a variety of industries that include Automotive, Industrial, and Personal Mobility. In addition, these new housings offer all the benefits of the industry standard Powerpole[®] SB[®] and SBS[®] products including color and mechanical coding, hot plug capability, and genderless design. These products are fully intermateable and interchangeable with the standard lines of connectors and accept the same range of contacts.

Features

Same Great Design as Standard Connectors

- Use a trusted connector design in new applications
- Fully intermateable with standard product

Superior Chemical Resistance

Housing material is highly resistant to hydrocarbons and solvents commonly used in transportation applications

• Broader Operating Temperature Range Enables use in lower temperatures

- Durable Performance
 Resists damage from rough treatment
- Enhanced UV Resistance Prevents material degradation from prolonged sunlight exposure
- Marked for Easy Identification of Material Chemical resistant housings are marked with a "P" for PBT

laterials		Mechanical		Electrical
lousing Material	PC / PBT Blend	Mating Cycles*	10,000*	Operating Temperature** (°C) -40° to 105°
lamability	UL94 V-0			(°F) -40° to 221°
Veatherability	UL746C (F1)			
	certain contacts of certain co s. ** Contact customer service			nating cycle life ratings specific to certain connectors and

SB [®] 50 Housing Only		SB [®] 350 Housing Only			SBS [®] 75x Housing Only						
Bulk			Bulk	-	-	Part Number	Color	Pack Qty			
Part Number	Color	Pack Qty	Part Number	Color	Pack Qty	PSBS75xBLK-BK	Black	100			
P992-BK P992G1-BK P992G2-BK	Gray Red Black	500 500 500	Р906-ВК Р913-ВК	Gray Red	100 100	Powerpole [®] 75 Housing Only					
CD®4 00 1	lauai		SBS®50 Ho	ousing	Only	Part Number	Color	Pack Qty			
SB®120 I Bulk		0 ,	Bulk Part Number	Color	Pack Qty	P5916G7-BK P5916G4-BK	Red Black	1000 1000			
Part Number P6810G1-BK P6810G3-BK	Color Gray Red	Pack Qty 100 100	PSBS50GRA-BK PSBS50RED-BK PSBS50BLK-BK PSBS50BLU-BK	Gray Red Black Blue	500 500 500 500	P5916-BK P5916G5-BK	Blue White	1000 1000			
SB®175 I Bulk	Housi	ng Only	PSBS50GRN-BK PSBS50BRN-BK	Green Brown	500 500						
Part Number P940-BK	Gray	y 200				NOTE: See indiv regarding contac				al information	
P949-BK	Red	200				All Data Subject	To Change	Without Notice	15012	DS-CR REV 01	

HEADQUARTERS: Anderson Power Products®, 13 Pratts Junction Road, Sterling, MA 01564-2305 USA T:978-422-3600 F:978-422-3700 EUROPE: Anderson Power Products® Ltd., Unit 3, Europa Court, Europa Boulevard, Westbrook, Warrington, Cheshire, WA5 7TN United Kingdom T: +44 (0) 1925 428390 F: +44 (0) 1925 520203 ASIA / PACIFIC: IDEAL Anderson Asia Pacific Ltd., Unit 922-928 Topsail Plaza, 11 On Sum Street, Shatin N.T., Hong Kong T:+(852) 2636 0836 F:+(852) 2635 9036

ASIA / PACIFIC: IDEAL Anderson Asia Pacific Ltd., Unit 922-928 Topsail Plaza, 11 On Sum Street, Shatin N. I., Hong Kong 1:+(852) 2636 0836 F:+(852) 2635 9036 CHINA: IDEAL Anderson Technologies (Shenzhen) Ltd., Block A8 Tantou Western Industrial Park, Songgang Baoan District, Shenzhen, PR. China 518105 T: +(86) 755 2768 2118 F: +(86) 755 2768 2218 TAIWAN: IDEAL Anderson Asia Pacific Ltd., Taiwan Branch, 4F.-2, No.116, Dadun 20th St., Situn District, Taichung City 407, Taiwan (R.O.C.) T: +(886) 4 2310 6451 F: +(86) 4 2310 6460