



recommended pin design	
interface	description
pin 6	---
pin 1	+5V
pin 2	Data-
pin 3	Data+
pin 4	GND
pin 5	---

All dimensions are in mm; tolerances according to ISO 2768 m-H

### General Information

Magnetic connector  
 Number and type of contacts 6 rigid pins  
 Soldering THT  
 Color Black, similar RAL 9005

### Interface

Mating with MultiMag 6 cable assembly

### Material and Plating

#### Connector Parts

Contacts	Material Brass	Plating/Color Gold plated
Housing	PBT GF30	Black, similar RAL 9005
Magnets	NdFeB	Nickel plated



MultiMag 6 Receptacle  
(PCB Termination)

**M9K701-400L**

**Mechanical Data**

Magnetic disengagement force average ~ 8 N  
 Mating cycles without load min. 5.000  
 Expected Mating cycles with load:

Max. Voltage	Max. Current	Mating cycles
5.0 V DC	0.5 A	min. 5.000
12.6 V DC	1.0 A	min. 2.000
24.0 V DC	0.5 A	min. 800

**Environmental Data**

Temperature range -20 °C to +65 °C  
 Magnets start losing their magnetic properties above 65 °C

**Compliance**

RoHS compliant

**Packing**

Standard 100 pcs in blister  
 Weight ~ 1.1 g/pc

**Caution!**

**Magnets can impact the function of pace makers and implantable cardioverter-defibrillators (e.g. actuation of reed switch). Keep a minimum distance of 0.2 m (20 cm) between the magnetic connector and the implanted devices to prevent malfunction and danger to health.**

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
T. Scheuerlein	22.06.16	T. Scheuerlein	22.01.20	b00	20-0163	S. Kirchhofer	22.01.20