



# Perfect-It™ 1-Step Foam Finishing Pad

**33033 • 33034 • 33035 • 33036 • 33037 • 33042**

Technical Data

March 2019

3M Part Number	3M Part Descriptor
33033	Perfect-It™ 1-Step Foam Finishing Pad, 4 inch, Hookit™ single sided, inset backing
33034	Perfect-It™ 1-Step Foam Finishing Pad, 6 inch, Quick Connect
33035	Perfect-It™ 1-Step Foam Finishing Pad, 8 inch, Quick Connect
33036	Perfect-It™ 1-Step Foam Finishing Pad, 8 inch, Hookit™ single sided
33037	Perfect-It™ 1-Step Foam Finishing Pad, 8 inch, Hookit™ single sided, inset backing
33042	Perfect-It™ 1-Step Foam Finishing Pad, 6 inch, Hookit™ single sided

**Product Description** 3M™ Perfect-It™ 1-Step Foam Finishing Pad is a high-performance paint finishing pad designed to be used with Perfect-It™ 1-Step Finishing Material to remove Trizact™ 8000 abrasive scratches.

**Features**

- Removes 3M™ Trizact™ 8000 scratches, providing a 1-Step finish on most colors
- Provides the cut of a compound pad and the swirl-free finish of a polish pad

**Typical Physical Properties** NOTE: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Material	Foam
Color	Purple
Shape	Round

**Product Uses** 3M™ Perfect-It™ 1-Step Foam Finishing Pad is developed to be used with Perfect-It™ 1-Step Finishing Material to remove Trizact™ 8000 scratches during the paint finishing process of automotive clear coat surfaces, light industrial clear coat surfaces, and marine gelcoat and paint finishes.

**Directions for use**

1. Area to be finished must be clean. Flush or wipe away any sanding residue. Thoroughly wipe surface with a clean damp cloth.
2. Work a 2' x 2' area with the appropriate finishing material.
3. Use a buffer speed between 1200 and 2000 Max. RPM for best results.
4. Buff at a low angle, almost flat, for best results.

# 3M™ Perfect-It™ 1-Step Foam Finishing Pad

33033 • 33034 • 33035 • 33036 • 33037 • 33042

---

Directions for use continued 5. On contours and detail lines, reduce machine pressure to avoid damaging the surface.

---

Applications	Paint and gelcoat refinishing.
Storage and Handling	Product shall have a shelf life of 60 months from date of manufacture when stored in original unopened containers at Standard environmental conditions: 70F room temperature, 50% relative humidity; protect from UV exposure, prolong exposure to temperatures above 135F/57C.
Precautionary Information	Before using this product, please reference Product Label and/or Safety Data Sheet for Health and Safety Information. Note: Laws controlling the acceptable amounts of Volatile Organic Compounds (VOCs) vary by state, and in some cases by locality. For surface preparation and clean-up activities, consult federal, state and local regulations regarding use of products containing VOCs in your area.
Technical Information	The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.
Warranty, Limited Remedy and Disclaimer	Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

---

