



CIRCUIT: SPST

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERMINAL NO.S FOR REF ONLY.
 4. RATING: AC 250V 5A/80A, TV-5
 5. CONTACT RESISTANCE: 100m Ohms MAX. (AT DC 5V@1A)
 6. DIELECTRIC STRENGTH: AC 1000V
 7. OPERATING FORCE: 350±100gf
 8. TRAVEL: FULL STROKE: 3.5+0.5/-0mm
 9. 2002/95/EC (ROHS) COMPLIANT

C	16839	FIXED 9.8 DIM TD 19.8	1/9/07	TN
B	16838	FIXED CAP DESCRIPTION	1/8/07	TN
A	11228	RELEASED FOR PRODUCTION	2/07/01	CJB
REV.	ECN NO.	DESCRIPTION	DATE	CHKD

<p>THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED</p>		SCALE	DATE	DR	DWG	REV
<p>E-SWITCH®</p>		1.5:1	1/9/07	TN	XP02114	C
<p>TITLE</p> <p>P197DASB (TAG/BLK)</p>						