

Data sheet | Item number: 249-135

Test plug module; without locking device; modular; for 2-conductor terminal blocks; gray

www.wago.com/249-135



**Data
Notes**

Safety information

Middle pressure, 2.2 N per pole

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Electrical data

Ratings per IEC/EN

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)
Nominal voltage (III/3)	250 V

Ratings per IEC/EN 2

Ratings (note) 2	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)
------------------	--

General information

Test voltage	250 V
Test current	0.5 A

Physical data

Width	5 mm / 0.197 inches
Module width	5 mm / 0.197 inches

Material Data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material	Polyamide (PA66)
Fire load	0.098 MJ
Weight	1.1 g

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 8.0	EC002555
ETIM 7.0	EC002555
PU (SPU)	100 (25) pcs
Packaging type	box

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Country of origin	DE
GTIN	4045454620653
Customs tariff number	85366990990

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	5e27976c-2308-4987-a3e6-71e5dd95e7e3
SCIP notification number (Belgium)	75f0f8a5-731a-4c49-918e-50613bd76b62
SCIP notification number (Bulgaria)	1413fe7d-e7a6-4da3-9c93-658b81149295
SCIP notification number (Czech Republic)	e7692d23-2c0b-4bfa-a29d-33d219de35b7
SCIP notification number (Denmark)	e52a1c29-2320-4af7-82c2-1f125cb9780d
SCIP notification number (Finland)	4a6adb3f-620e-4b54-8c4a-186d9f152086
SCIP notification number (France)	f9e0193d-6591-42b2-93a3-dec34553ebf1
SCIP notification number (Germany)	a8082bb8-d64d-4ff3-9a36-89fb1dcc9589
SCIP notification number (Hungary)	dae059c8-fe0f-4b36-a5a2-ad089d9c35db
SCIP notification number (Italy)	b9bc0cbf-c5af-4913-828e-abd8619396cb
SCIP notification number (Netherlands)	fa662b17-ab01-41d4-93f1-0d41d4313519
SCIP notification number (Poland)	c9550a73-223c-4e9d-a635-d0d604a714c0
SCIP notification number (Romania)	26913252-c7b2-4d1c-aa8c-65a117ad545b
SCIP notification number (Sweden)	07ab7ecd-46c0-46b2-b916-96cf164fbaa9

Optional accessories**Testing and measuring**

Testing accessories	
Item no.: 210-136	www.wago.com/210-136
Test plug; 2 mm Ø; with 500 mm cable; red	

Downloads**Documentation****Bid Text**

249-135	2019 年2月19 日	xml	Download
---------	--------------	-----	----------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



X81 - Datei			3.2 kB	
-------------	--	--	--------	--

249-135	2017 年8月17 日	doc	Download
doc - Datei		24.6 kB	

Additional Information

pdf	Download
2.3 MB	

CAD/CAE-Data

CAD data

2D/3D Models 249-135	URL	Download
----------------------	-----	----------

CAE data

WSCAD Universe 249-135	URL	Download
------------------------	-----	----------

ZUKEN Portal 249-135	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-135	URL	Download
--	-----	----------

Test plug module; without locking device; modular; for 2-conductor terminal blocks;
gray

Installation Notes

Installation

Subject to changes. Please also observe the further product documentation!



Snapping individual modules together to assemble a multi-pole test plug module.

Testing



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 ... 40 mm!



Testing after the conductors have been terminated.

Subject to changes. Please also observe the further product documentation!