



- THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 - MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
 - METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 - PACKAGE MARKED M 24308/4-330F
 - THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION MARKED IN THIS AREA.

OBSOLETE	PHENOLIC, COLOR: BLACK	204527-2
	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TPES013G30 PER ASTM D5927 COLOR, BLACK	204527-1
	INSERT MATERIAL	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN 12-3-87	C.C. THOMAS
	0. PLC ± -	1-25-88	FC RALLEW
	1. PLC ± -		
	2. PLC ± -		
	3. PLC ± .005		
	4. PLC ± -		
	ANGLES ± -		
	FINISH SEE CALLOUTS		

STE TE Connectivity
 NAME: AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY D CONN, SIZE 2, SERIES 90 WITH FLOAT BUSHINGS
 SIZE: A1 CAGE CODE: 00779 DRAWING NO: 204527
 MATERIAL: SEE CALLOUTS WEIGHT: --- RESTRICTED TO: ---
 CUSTOMER DRAWING SCALE: 4:1 SHEET: 1 OF 1 REV: T