

JUG WARMERS

HotBelt™ Wrap-Around Refrigerant Jug Warmer (HB Series)

- ▶ Adjustable fit design with hook & loop strap fits common size cylinders: 30 lb, 50 lb, and 125 lb (13 kg, 23 kg, and 57 kg)
- ▶ Designed to heat the tank surface to 120°F (49°C)
- ▶ Moisture and chemical resistant – IP56 rated
- ▶ 6 ft (1.8 m) long power cord with choice of plug

Benefits:

- Preheats and keeps refrigerant jug cylinders warm when servicing HVACR systems in cold weather
- Ensures adequate pressure from refrigerant to A/C or refrigeration system during cold weather servicing Ideal for portable and outdoor use
- Easy-to-use – simple plug-and-play design
- Rugged – provides long service life and can be used in a wide variety of environments

Specifications:

Heater Width: 6 in (152 mm)

Length: 26 in (660 mm)

Thermostat: Thermostat is preset to 158°F (70°C) and the heater is designed to heat the surface of the tank to 120°F (49°C)

Exposure Temperature: -60°F to 450°F (-51°C to 232°C)

Voltage: 120, 230, or 240 VAC

Power Density: 1.4 W/in² (0.2 W/cm²)

Dielectric Strength: Over 2000 volts

Silicone Rubber Density: 46.0 oz/yd² (1560 g/m²) Closure

Method: Adjustable strap

Cylinder Diameter Range: Minimum 9 in (229 mm)

Power Cord: 6 ft (1.8 m) long with choice of power plug

Ingress Protection Rating: IP56

*Variations in ambient temperature and material contents within the cylinder may affect actual surface temperature of the cylinder.

Ordering Information:

| Part No. | Voltage VAC | Plug Type | Total Watts |
|----------|-------------|------------|-------------|
| HB1001 | 120 | NEMA 5-15P | 200 |
| HB2001 | 240 | NEMA 6-15P | 200 |
| HB2002 | 230 | CEE 7/7 | 200 |

NEW!

Plug and Play

**Moisture and
Chemical
Resistant**

Safe to use with common refrigerants:

- R-410A
- R-407C
- R-139A
- R-22
- R-404
- And more