

## Accessories - MSTBC-MT 0,2-0,5 BAND - 1879544

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Module socket contact, is inserted into the plug housing MSTBC after crimping the conductor, for conductors from 0.2 to 0.5 mm<sup>2</sup>

Supplied in tape form - please note the drawing.



### Key commercial data

Packing unit	1 1
Minimum order quantity	4000 1
Weight per Piece (excluding packing)	0.65 GRM
Custom tariff number	85366990
Country of origin	Czech Republic

### Technical data

#### Connection data

Core diameter including insulation	1.15 mm ... 2.31 mm
Stripping length of individual wires	3 mm

#### Material data

Contact material	CuFe
Contact surface material	Tin-plated

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701

## Accessories - MSTBC-MT 0,2-0,5 BAND - 1879544

### Classifications

#### eCl@ss

eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

#### ETIM

ETIM 3.0	EC000796
ETIM 4.0	EC000796
ETIM 5.0	EC000796

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

### Drawings

Dimensioned drawing

