



STRIPPING DIMENSIONS

Directive 2002/95/EC RoHS compliant

(b)

NOTES:

1. MATERIAL: COPPER ALLOY
2. PLATING:
 - ITEM 1: SEE TABLE
 - ITEM 2: GOLD FLASH over NICKEL
 - ITEM 3: NICKEL PLATED
3. CRIMPING: USE CRIMP TOOL 360X10409X
WITH TOOL INSERT 360X20029X
SELECTOR SETTINGS: 5 FOR AWG 12
4 FOR AWG 14

(b)

PLATING ITEM 1	PART-NO.
GOLD FLASH over NICKEL	131A11029X
min. 30µin HARD GOLD over min. 50µin NICKEL	131C11029X
min. 50µin HARD GOLD over min. 50µin NICKEL	131J11029X

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: SEE NOTES				tolerance ISO 2768-m		dim. in mm		scale: 5:1		material: SEE NOTES	
				date	name		title: HIGH POWER CONTACT MALE CRIMP VERSION 20A D-SUB COMBINATION				
				drawn	23.03.98 Barcinski						
				appd.	23.03.98 Mickenbecker						
				norm							
				d-old			dwg no:		DIN-A4		
4 x b	Ä3854	19.01.11	K.H.			13K11D2A		sh: 1			
a	Origin					part no:		SEE TABLE			
rev.	description	date	name								



title:		scale: 5:1	
material: SEE NOTES		material: SEE NOTES	
dwg no:		DIN-A4	
13K11D2A		sh: 1	
part no:		SEE TABLE	