

mec
switches

switches



Switch Engineering Catalog No. 6

mec Competences

Since its foundation in 1938, **mec** has been making state-of-the-art electromechanical components.

Today we are focusing on continuous innovation to maintain our position as leader in the segment of high end PCB mount push button switches. By always choosing the best possible solution, whether it is a design principle, a material or a manufacturing process we maintain and improve our sustainable high quality level. With this approach a wealth of know-how has been built up over the years for the benefit of new product development and custom solutions.

Despite the trend of outsourcing it has been the policy of **mec** to maintain a high degree of vertical integration that enables us to react promptly on specific customer requests. Only processes that are not considered core competences have been outsourced.

Research and Development

Equipped with the latest CAD solutions with 3D facilities and optical simulation software our experienced R&D engineers are designing, simulating and evaluating new products and machinery continuously. The combination of a strong R&D facility and the vertical integration enables us to provide custom designs from conception to completion.

Automation - Tooling - Moulding - Stamping - Graphics Marking - Custom Assembly

All switch modules are manufactured on fully automated production lines with complete in-line component tests. All production statistics are analysed and stored in computers. 98% of all parts used in the **mec** switches are produced in-house.

Ongoing investments ensure that latest technology is available for the tooling department. However, at **mec** we believe that the most important factors for maintaining a high tool standard are the outstanding skills and experience of our toolmakers.



Prompt reaction to customer requests has always been important to **mec.**

The plastic moulding department consists of numerous moulding machines. Rigorous process control ensures the highest possible precision and reproducible quality that is essential for making precision components.

All metal parts are manufactured in our metal stamping department. When making contact elements, a computer controlled test station provides a high level of repeatability and secures that any required corrections can be made instantly.

Graphics marking is also made in-house to secure constant quality and durability of both standard and customized graphics for the many keycaps and bezels available. The assembly department offers all kinds of value-added services such as customized final assembly made by experienced and quality conscious personnel.

Logistics and Production Planning

The production planning software is today fully integrated into the financial and administrative system.

The system provides the backbone that allows us to maintain precise deliveries and to offer excellent customer service.

Quality – Environment - RoHS

We strive to maintain the highest possible quality standard through our QA system. With 100% in-line inspection, tight tolerance

on all parts and use of only quality material we position ourselves to reach the highest achievable.

To be a part of a sustainable industrialized world environmental consciousness is crucial. At **mec** we have been substituting materials to more environmental friendly alternatives and are recycling as much as possible. Legal authorities are auditing our environmental management system regularly and confirming that our goal is being reached.

RoHS conversion has been completed for all switches. To manage the inventory in the complete supply chain a separate part number system has been established. All parts manufactured today are RoHS compatible.

Sales - Customer Service - Distribution

mec have a well established global distribution network that provides a presence in all parts of the world where electronic manufacturing takes place. Through close contact and continuous product training offered to our distributors we maintain a highly qualified and responsive global distribution network.

Please contact **mec** or one of our distributors if you require assistance or samples to complete your new design with **mec** switches. We welcome inquiries also for custom solutions.

mec Switches

Colourful and reliable to complete your next design successfully



Contents

Selection Guide

multimec® Pushbutton switches	04
multimec® Pushbuttons continued	05
unimec™ Pushbutton switches	06
multimec® Switches under foil	07
multimec® Switches - Variable heights	08
multimec® Solid colour codes	37

multimec® pushbutton switches

illumec™ 4A	09
3A + 1B/1C+2A/2B	10
3A + 1A/1H/1M/1ZA	11
Navimec™	12
illumec™ 4F	13
3F + 1N	14
3F + 1D/1E/1F	15
3F + 1K/1KB/1KC	16
3F + 1WA/1WD/1WP	17
3F + 1P/1Q/1R	18
3F + 1T/1U/1V	19
3F + 1X	20
3F + 1S+2S	21
Aquamec™	22
3F + 1GA/1GC	26
3C/3E switches	27
Varimec™ - Double variability - round	28
Varimec™ - Double variability- square	29
Right angle switches 3C/3E/3F	30
3F Right angle switches with keycaps	31
Legends	23

Technical information multimec®

Basic switch modules	32
Basic switches continued and tape & reel	33
Spacing	34
Technical specifications	35
LEDs	36

unimec™ pushbutton switches

16.324-16.326	38
16.310-16.315	39
16.300/16.700/16.800	40
Vario Support	41
Legends	42
unimec™ with multimec® keycaps	43

Technical information unimec™

Basic switch modules	44
Technical specifications + LEDs	45

Applications

Applications for inspiration	24
Applications for inspiration	25

General information

Competences	02
Usage guidelines	46
Custom products	47

multimec® PCB Mount Pushbutton Switches

mec specializes in the production of PCB mounted pushbutton switches. Our products are designed to be used in a wide variety of applications. Through the use of a modular approach to switch assembly the user is provided with a unique flexibility in his choice of options. multimec® switches are known for their crisp audible tactile feel although a "quiet" model is available for sensitive applications such as audio and conference equipment.


The multi-coloured keycaps, bezels and LEDs snap together to produce almost unlimited switch configurations. Customized keycaps and bezels can be manufactured for special applications.



	3A/4A Switches					Caps and Bezels	Page
	Pushbutton		Illuminated				
TH	SMD	TH	TH	SMD			
3AT	3AS	3AT	4AT	4AS			
X	X					1M 1ZA	11
		X X	X	X	X	1H 1C + 2A/2C	11/09 10/09
X	X	X X	X	X	X	1A 1B + 2A/2C 1B + 2B/2D + 2B LED	11/09 10/09 10/09
3C/3E Switches					Caps and Actuators	Page	
Pushbutton							
TH		SMD					
3CT	3ET	3CS	3ES				
X		X					27
	X			X		6 caps 6 actuators 3 bezels	27 28 29
Navimec™ Switches					Caps	Page	
Pushbutton		Illuminated					
TH		SMD	TH	SMD			
3AT	3FT	3AS	4FT	4FS			
X	X	X	X	X	1ZB 1ZC	12/13	

The size of the switches, caps, actuators and bezels listed may not correspond to the actual size.

multimec® PCB Mount Pushbutton Switches



		3F/4F Switches				Caps and Bezels		Page
		Pushbutton		Illuminated				
TH	SMD	TH		TH	SMD			
3FT	3FS	3FT		4FT	4FS			
X	X					1GA 1GC 1P 1ZC 1K + 2K	26 18 12 16	
		X	X	X		1K 1KB 1KC 1R 1Q	16/13 18/13	
X	X	X	X	X		1D 1E 1F 1N 1S 1T 1U 1V 1X AQN AQC AQB01 1WA 1WD 1WP	15/13 14/13 21/13 19/13 20/13 22/13 17/13	
Right Angle Switches						Caps and Actuators		Page
		Pushbutton		Illuminated				
		Through-hole						
3CTRAS	3ETRAS	3FRAS		3FRAS w/LED				
X								30
	X							30/27
		X						30/28
								30/29
			X			1GA 1GC 1P 1ZC 1K + 2K 1T 1U 1V 1S	31/26 31/18 31/12 31/16 31/19 31/21	
				X		1D 1E 1F 1Q 1R 1S 1N 1X	30/31/15 30/31/18 30/31/21 30/31/14 30/31/20	

The size of the switches, caps, actuators and bezels listed may not correspond to the actual size.

unimec™ PCB Mount Pushbutton Switches

This switch range is one of the smallest two pole switches available today. The contacts are capable of producing eight functions depending on the PCB layout. The unimec™ switch is available in momentary and alternate action models with standard silver contacts or optional gold contacts for low level switching. All unimec™ switches are available in low or high temperature models.



Switches Low. Temp.	Switches High Temp.	Caps and Bezels	Page	
 15.500		Silent silver 	 16.300 +  16.310	39
	 15.420	Silent gold 	 16.300 +  16.311 +  16.920	39
 15.501	 15.401	Momentary silver 	 16.300 +  16.312 +  16.921	39
 15.502	 15.402	Momentary gold 	 16.300 +  16.314 +  16.920 +  16.921	39
 15.551	 15.451	Alternate silver 	 16.300 +  16.315 + 2x  16.920/16.921	39
 15.552	 15.452	Alternate gold 	 16.270 +  16.300 +  16.324	38
			 16.270 +  16.300 +  16.325 +  16.327 +  16.922	38
			 16.270 +  16.300 +  16.326 + 2x  16.327/16.922	38
			 16.700	40
			 16.800	40
			 16.300	40
			 Vario Support 1x1 to 10x10	41
		Legends for	 16.300 +  16.700	42

The size of the switches, caps, actuators and bezels listed may not correspond to the actual size.

multimec® Switches Under Foil

The use of multimec® under a foil overlay offers an attractive alternative to the traditional membrane switch. With a mechanical life of 10 million cycles, multimec® will outperform membrane switches under the most extreme conditions. multimec® switches can be specified with LED illumination to provide back lighting of the overlay for front panel applications. While mec does not manufacture foil overlays, our local distributors can help you locate sources of supply.




	Switches	Caps and Actuators	Overall Height (mm)	Diameter (mm)	Page
	3CTL6 3CTH9		6.4	6.5	27
	3CSH9				
	3ETL9 3ETH9		08.0-15.0	6.5	27
	3ESH9				
	3FTL6 3FTH9	 1GA	12.5	11.0	26
	3FSH9	 1GC + 2S (optional)	17.5-22.5		
	3ETL 3ETH		10.4-22.5	5.2 7.8 11.6 Square 5.2 x 5.2 7.8 x 7.8 11.6 x 11.6	28
	3ESH				29
	3FTL6 3FTH9	 1D	14.9	9.6	15/13
	3FSH9	 1K	19.1	14.3x14.3	26/13
	3FTL6 w/LED	 1S	16-22.5	6.5	21/13
	4FTH9 w/LEDs	 1T	14.9	10.6x10.6	19/13
	4FSH9 w/LEDs	 1U	14.9	10.6	19/13

The size of the switches, caps, actuators and bezels listed may not correspond to the actual size.

multimec® Variable height switches

mec is probably the most flexible switch manufacturer worldwide when it comes to fulfilling customers' specific height requirements. This selection guide on variable height switches is giving a simple overview of the many height options the multimec® switch line can offer and how to overcome the problems with adapting building heights.


	Switches	Caps and Actuators	Overall Height (mm)	Diameter (mm)	Page
	 3CTL6 3CTH9	White – Black	6.4	6.5	27
	 3CSH9				
	 3ETL9 3ETH9		08.0 09.5 10.4 11.0 12.0 15.0	6.5	27
	 3FSH9	Blue – Grey – Yellow – Red – Black	12.5	11.0	
	 3FTL6 3FTH9	 1GA09 Black	17.5-22.5 in steps of 1 mm	15.0	26
	 3FSH9	 1GC09 Black + 2S (optional)			
	 3ETL 3ETH		10.4-22.5 <u>Double Variability</u> Above recess: 2.4-6.4 Below recess: 0-8.1	5.2 7.8 11.6	28
	 3ESH		Above recess: 2.4-6.4 Below recess: 0-8.1	Square 5.2x5.2 7.8x7.8 11.6x11.6	
	 3FTL6 3FTH9	 1S09 Black	16.0 19.0 22.5	6.5	21
	 3FSH9	 + 2S (optional)	21.0-32.5 in steps of 1 mm		
	 3FTL6 w/LED		16.0 19.0 22.5	6.5	21/13
	 4FTH9 w/LEDs				
	 4FSH9 w/LEDs		21.0-32.5 in steps of 1 mm		

The size of the switches, caps, actuators and bezels listed may not correspond to the actual size.


multimec® illumec™ 4A

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
high temp. switch: -40/+160°C
LED: -30/+85°C




Dimensions (through-hole)




Top View



Dimensions (SMD)




Top View





PCB layout and Circuit Diagram

1 LED




2 LEDs





PCB layout and Circuit Diagram

1 LED



2 LEDs



Technical specifications for 4A switch and LEDs see pages 35 and 36

How to order

4 A

+

Switch Mounting

SH9 surface mount
TH9 through-hole

LED

Illuminated Cap

01		1A 10,12,14,16,18
22		1B 10,12,14,16,18
42		10,12,14,16,18
61		
82		
2242	<input type="checkbox"/>	
8222	<input type="checkbox"/>	
8242	<input type="checkbox"/>	
	Cap Solid Colour	Illuminated Colour Lens

+ **2 C** or **2 D**
Bezel Solid Colour **Bezel** Solid Colour **Illuminated Lens**

1H Solid Colour + lens 1,2,4,6,8

1C Solid Colour + lens 1,2,4,6,8 + **2 C** or **2 D**
Bezel Solid Colour **Bezel** Solid Colour **Illuminated Lens**

Colour codes

LEDs	Illuminated Caps	Lenses
01 blue	10 frosted blue	1 transparent
22 green	11 transparent	2 green
42 yellow	12 frosted green	4 yellow
61 white	14 frosted yellow	6 frosted white
82 red	16 frosted white	8 red
2242 green/yellow	18 frosted red	
8222 red/green		
8242 red/yellow		

Solid Colours Caps and Bezels

For 1A, 1B and 2C only:	
00 blue	30 ultra blue
02 green	40 dusty blue
03 grey	42 aqua blue
04 yellow	32 mint green
06 white	33 tele grey
08 red	34 melon
09 black	38 noble red

Dimensions

Caps	See Page
1A - 1H	11
1B - 1C	10
2C - 2D	
Same as for 2A/B	10


Ordering example: 4ASH982 + 1A18 or 4ATH901 + 1B10 + 2C09

For updates of products and/or changes of specifications please see www.mec.dk



multimec® 3A + 1B/1C + 2A/2B

Technical Data



- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C





Dimensions (through-hole)




PCB layout





Dimensions w/LED in switch (1C/1H)




PCB layout (top view)





Dimensions w/LED PCB mounted (2B)




PCB layout (top view)



Dimensions (SMD)



PCB layout



How to order

3 | A



Switch



Mounting

T through-hole
S surface mount

+

1 | B



Cap

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

2 | A



Bezel

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

For 1B and 2A only:

30 ultra blue
40 dusty blue
42 aqua blue
32 mint green
33 tele grey
34 melon
38 noble red50 metal dark blue
53 metal light grey
57 metal dark grey
58 metal bordeaux

3 | A



Switch



Mounting

T through-hole



+

1 | C



Cap

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

+

2 | A



Bezel

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

3 | A



Switch



Mounting

T through-hole
S surface mount

+

1 | B



Cap

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

+

2 | B



Bezel

00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

Lens

1 transparent
2 green
4 yellow
6 frosted white
8 red

Keycaps and bezels shown on this page can also be used on illumec™ switch 4A - see page 9. Part nos. for bezels for 4A are 2C and 2D.

Ordering example: 3ATL640 + 1C094 + 2A04

For updates of products and/or changes of specifications please see www.mec.dk

multimec® 3A + 1A/1H/1M/1ZA

Technical Data

- through-hole or SMD
 - 50mA/24VDC
 - single pole/momentary
 - 10.000.000 operations life time
 - IP67 sealing
 - temperature range:
 - low temp: -40/+115°C
 - high temp: -40/+160°C



The image contains four sets of technical drawings. Each set includes a top view of the component and its mounting pad on a PCB, followed by a detailed cross-sectional view of the component's internal structure.

- Dimensions (through-hole) 1A:** Shows a component with a height of 16.2 mm, a lead width of 0.8 mm, and a lead spacing of 7.62 mm. The PCB layout shows a rectangular pad with a central via, dimensions 12.5 mm x 10.1 mm.
- Dimensions (w/LED) 1H:** Shows a component with a height of 16.2 mm, a lead width of 0.8 mm, and a lead spacing of 7.62 mm. The PCB layout shows a rectangular pad with a central via, dimensions 10.16 mm x 7.62 mm.
- Dimensions (SMD) 1ZA:** Shows a component with a height of 12.2 mm, a lead width of 0.8 mm, and a lead spacing of 7.62 mm. The PCB layout shows a rectangular pad with a central via, dimensions 18.65 mm x 10.1 mm.
- Dimensions (SMD) 1M:** Shows a component with a height of 12.2 mm, a lead width of 0.8 mm, and a lead spacing of 7.62 mm. The PCB layout shows a rectangular pad with a central via, dimensions 25.0 mm x 12.5 mm.

How to order

3 A	<input type="checkbox"/>	<input checked="" type="checkbox"/>	+ 1 A	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Switch	Mounting	L 6 low temp.	Cap	00 blue	30* ultra blue	50* metal dark blue
	T through-hole	H 9 high temp.		02 green	40* dusty blue	53* metal light grey
	S surface mount			03* grey	42* aqua blue	57* metal dark grey
			1 Z A	04 yellow	32 mint green	58* metal bordeaux
			Cap	06* white	33 tele grey	
				08 red	34 melon	
				09* black	38 noble red	*) Colours for 1ZA

3 A	<input type="checkbox"/>	<input checked="" type="checkbox"/>	+	1 M	<input type="checkbox"/>
Switch	Mounting T through-hole S surface mount	L 6 low temp. H 9 high temp.		Cap 	00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black

3 A	T			+	1 H		
Switch	Mounting T through-hole	L 6 low temp. H 9 high temp.	LED 00 blue 20 green 40 yellow 80 red	Cap 	00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	Lens 1 transparent 2 green 4 yellow 6 frosted white 8 red	


Keycaps shown on this page can also be used on
illumec™ switch 4A - see page 9

Ordering example: 3ATL680 + 1H098





multimec® Navimec™

Technical Data





- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C



Dimensions 1ZB (through-hole)




Dimensions 1ZC (SMD)




Recommended panel cut-out:

Ø35.0-35.5 Depending on application

PCB layout TH



PCB layout SMD



How to order

3 A Switch **Mounting**
T through-hole S surface mount

L 6 low temp.
 H 9 high temp.

Cap 1ZB


03 grey
 06 white
 09 black
 30 ultra blue
 40 dusty blue
 42 aqua blue
 50 metal dark blue
 53 metal light grey
 57 metal dark grey
 58 metal bordeaux

3 F Switch **Mounting**
T through-hole S surface mount

L 6 low temp.
 H 9 high temp.

Cap 1ZC


Dimensions Navimec™ Module



Dimensions (mm)

Circuit Diagram Navimec™ Module

(Front side View)



Navimec™ Module

Part No. 9508000
Part No. 950XXYY
Part No. 9509XXXXYY

Navimec™ Module excl. keycaps
Navimec™ Module incl. keycaps
Navimec™ Module incl. keycaps with legends

The module can be delivered with keycaps (4 x 1ZB and 1 x 1ZC) in solid colours or black keycaps with white legends.

For module incl. keycaps in solid colours (950XXYY) please indicate colour code for 1ZBXX and colour code for 1ZCYY.

For module incl. keycaps with legends (9509XXXXYY) please indicate legends for 1ZBXXX and legends for 1ZCYYY. All Caps are black with white legends. Please see legends available on page 23.

Examples: Module with 5 switches (4x3ATL6+1x3FTL6) mounted with 4x1ZB30 ultra blue and 1x1ZC42 aqua blue = 9503042.

Module with 5 switches (4x3ATL6+1x3FTL6) mounted with 4x1ZB09XD136 (legend arrow) and 1x1ZC09118 (legend OK) = 9509136118.

The plug on the Navimec™ module is JST SMT S10B-PH-SM3-TB or similar. We recommend using Cable socket: JST PHR-10 or similar Contact: JST SPH-002T-PO.5S or similar.

Ordering example: 4x3ATL6+1ZB53 and 1x3FTL6+1ZC58 or Navimec™ Module 9505358


multimec® illumec™ 4F

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
high temp. switch; -40/+160°C
LED: -30/+85°C




Dimensions (through-hole)




Top View



Dimensions (SMD)




Top View




PCB layout and Circuit Diagram

1 LED




2 LEDs





PCB layout and Circuit Diagram

1 LED



2 LEDs



Technical specifications for 4F switch and LEDs see pages 35 and 36

How to order

4 F

Switch **Mounting**
SH9 surface mount
TH9 through-hole

+

LED	Illuminated Cap
01	1D
22	1K,1KB,1KC
42	1N
61	1S
82	1T
2242	1U
8222	1V
8242	1WA,1WD,1WP
	1X



1D



1K,1KB,1KC

Colour code

Cap



Solid Colour



Illuminated Lens



1E Solid Colour + lens 1,2,4,6,8



1F Solid Colour + lens 1,2,4,6,8



1Q Solid Colour + lens 1,6



1R Solid Colour + lens 1,6

Colour codes

LEDs	Illuminated Caps
01 blue	10 frosted blue
22 green	11 transparent
42 yellow	12 frosted green
61 white	14 frosted yellow
82 red	16 frosted white
2242 green/yellow	18 frosted red
8222 red/green	
8242 red/yellow	

Lenses
1 transparent
2 green
4 yellow
6 frosted white
8 red

Solid Colours

1E,1F	1Q,1R
00 blue	00 blue
02 green	03 grey
03 grey	08 red
04 yellow	09 black
06 white	
08 red	
09 black	

Dimensions

Caps	See Page
1D,1E,1F	15
1K,1KB,1KC	16
1N	14
1Q,1R	18
1S	21
1T,1U,1V	19
1WA,1WD,1WP	17
1X	20

Ordering example: 4FSH98242 + 1D11 or 4FTH922 + 1T16

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1N

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)




PCB layout




Dimensions (w/LED)




PCB layout (top view)




Dimensions (SMD)



PCB layout



8 different position options



How to order

3 | F

Switch

Mounting

T through-hole
S surface mount

L 6 low temp.
H 9 high temp.

+

1 | N

Cap

00 blue
03 grey
04 yellow
08 red
09 black

3 | F

Switch

T

Mounting
T through-hole

L 6 low temp.
H 9 high temp.

LED
00 blue
20 green
40 yellow
60 white
80 red
2040 green/yellow
8020 red/green
8040 red/yellow

1 | N

Cap

10 frosted blue
12 frosted green
14 frosted yellow
16 frosted white
18 frosted red

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13

Ordering example: 3FTL6 + 1N09 or 3FTL680 + 1N18

For updates of products and/or changes of specifications please see www.mec.dk



multimec® 3F + 1D/1E/1F

Technical Data



- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C





Dimensions (through-hole)







Dimensions (w/LED)



Dimensions (SMD)



PCB layout



How to order

3 | F

Switch



Mounting
T through-hole
S surface mount



L 6 low temp.
H 9 high temp.



Cap
00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

00 ultra blue
40 dusty blue
42 aqua blue
32 mint green
33 tele grey
34 melon
38 noble red

50 metal dark blue
53 metal light grey
57 metal dark grey
58 metal bordeaux

3 | F


Switch



Mounting
T through-hole



L 6 low temp.
H 9 high temp.



LED
00 blue
20 green
40 yellow
60 white
80 red
2040 green/yellow
8020 red/green
8040 red/yellow



Cap 1D
00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black



Cap 1E
00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black



Cap 1F



1 transparent
2 green
4 yellow
6 frosted white
8 red
9 black

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13

Ordering example: 3FTL620 + 1E032

For updates of products and/or changes of specifications please see www.mec.dk

multimec® 3F + 1K/1KB/1KC

Technical Data

- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C



Dimensions 1K (through-hole)	Dimensions 1KB (w/LED)	Dimensions 1KC (w/LED)	Dimensions 1K (SMD)	Dimensions (Bezel) (Optional)
PCB layout 	PCB layout 	PCB layout 	PCB layout 	PCB layout

How to order

3 F	<input type="checkbox"/>	Switch	<input type="checkbox"/>	Mounting T through-hole S surface mount	<input type="checkbox"/>	L 6 low temp. H 9 high temp.	+	1 K 1 6	Cap	00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	+	2 K <input type="checkbox"/>	Bezel	03 grey 06 white 08 red 09 black
--------------	--------------------------	---------------	--------------------------	--	--------------------------	---	----------	---------------------------	------------	--	----------	---------------------------------------	--------------	---

3 F	<input type="checkbox"/>	Switch	<input type="checkbox"/>	T	<input type="checkbox"/>	Mounting T through-hole S surface mount	<input type="checkbox"/>	L 6 low temp. H 9 high temp.	<input type="checkbox"/>	LED 23 green 45 yellow 88 red	<input type="checkbox"/>	1 1 1 6	Cap frosted white	+	2 K <input type="checkbox"/>	Bezel	03 grey 06 white 08 red 09 black
--------------	--------------------------	---------------	--------------------------	----------	--------------------------	--	--------------------------	---	--------------------------	--	--------------------------	----------------------	--------------------------	----------	---------------------------------------	--------------	---

The 1K caps consist of a transparent lid and a diffuser lens.
It is possible to make your own customized legend by placing a foil between the lid and the lens.

Keycaps shown on this page can also be used on
illumecc™ switch 4F - see page 13

Ordering example: 3FTL688 + 1K1116

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1WA/1WD/1WP

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole) 1WA




PCB layout



Dimensions (w/LED) 1WD




PCB layout (top view)




Dimensions (SMD) 1WP



PCB layout



8 different position options



How to order

3 | F



Switch

Mounting

T through-hole
S surface mount



L 6 low temp.
H 9 high temp.

+



Cap

1WA



00 blue

03 grey

08 red

09 black

30 ultra blue

40 pigeon blue

42 aqua blue

53 metal light grey

57 metal dark grey

3 | F



Switch

Mounting

T through-hole



L 6 low temp.
H 9 high temp.



LED
23 green
45 yellow
88 red

+



Cap

1WA



16 frosted white

1WD

1WP

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13


Ordering example: 3FTL6 + 1WA09 or 3FTL680 + 1WP16

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1P/1Q/1R

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)




Dimensions (w/LED)




Dimensions (SMD)




PCB layout



PCB layout (top view)



PCB layout



How to order

3F

Switch

Mounting

T through-hole
S surface mount

L 6 low temp.
H 9 high temp.

+

1P

Cap



00 blue
02 green
03 grey
04 yellow
06 white
08 red
09 black

3F

Switch

T

Mounting

T through-hole

L 6 low temp.
H 9 high temp.

+

1Q



00 blue
03 grey
08 red
09 black

Lens
1 transparent
6 frosted white

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13


Ordering example: 3FTL680 + 1Q091

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1T/1U/1V

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)




Dimensions (w/LED)




Dimensions (SMD)




PCB layout



PCB layout (top view)



PCB layout



How to order

3 | F



Switch

Mounting
T through-hole
S surface mount



L 6 low temp.
H 9 high temp.

+




Cap
1T



00 blue
03 grey
08 red
09 black



1U



1V

3 | F



Switch

Mounting
T through-hole



L 6 low temp.
H 9 high temp.



LED
23 green
45 yellow
88 red

+



Cap
1T



16
frosted white



1U



1V

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13

Ordering example: 3FTL645 + 1V16

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1X

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)




Dimensions (w/LED)




Dimensions (SMD)




PCB layout



PCB layout (top view)



PCB layout



How to order

3 F	<input type="checkbox"/>	Switch	Mounting	L 6 low temp.	1 X	Cap	00 blue	30 ultra blue	50 metal dark blue
	<input type="checkbox"/>		T through-hole	H 9 high temp.			02 green	40 dusty blue	53 metal light grey
	<input type="checkbox"/>		S surface mount				03 grey	42 aqua blue	57 metal dark grey
	<input type="checkbox"/>						04 yellow	32 mint green	58 metal bordeaux
	<input type="checkbox"/>						06 white	33 tele grey	
	<input type="checkbox"/>						08 red	34 melon	
	<input type="checkbox"/>						09 black	38 noble red	

3 F	T	Switch	Mounting	L 6 low temp.	LED	1 X	Cap	11 transparent
	<input type="checkbox"/>		T through-hole		00 blue			16 frosted white
	<input type="checkbox"/>				20 green			
	<input type="checkbox"/>				40 yellow			
	<input type="checkbox"/>				60 white			
	<input type="checkbox"/>				80 red			
	<input type="checkbox"/>				2040 green/yellow			
	<input type="checkbox"/>				8020 red/green			
	<input type="checkbox"/>				8040 red/yellow			

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13

Ordering example: 3FTL6 + 1X09 or 3FTL680 + 1X11

For updates of products and/or changes of specifications please see www.mec.dk


multimec® 3F + 1S + 2S

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)



Dimensions (w/LED)



Dimensions (SMD)



How to order

3 | F

Switch



Mounting

T through-hole
S surface mount



L 6 low temp.
H 9 high temp.

+

1 | S | 0 | 9 | - | . | .

Cap black


Height
16.0
19.0
22.5



2 | S | 0 | 9 | - | . | 0

Extender black

Height
05.0 (Optional)
06.0 Adds 5-10mm to
07.0 total height
08.0
09.0
10.0



3 | F

Switch



Mounting

T through-hole



L 6 low temp.
H 9 high temp.

+

1 | S | 1 | 1 | - | . | .

Cap Transparent

Height
16.0
19.0
22.5



Customised Heights:

3F+1S is available in any height from 12.0 to 24 mm.

3F+1S+2S is available in any height from 17.0 to 34 mm.

Min. height for 1S11 is 16.0 and for 1S09 min height is 12.0 mm.

Min. order qty. for custom heights is 2.000 pcs.

For heights less than 12.0 mm, please refer to 3E switch range.

Keycaps shown on this page can also be used on

illumec™ switch 4F - see page 13

Ordering example: 3FTL640 + 1S11-19.0


multimec® Aquamec™

Specifications switches:

- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range: low temp: -40/+115°C
high temp: -40/+160°C

Specifications Sealing Boot:

- Operating temperature: -40/+85°C
- IP67 sealing
- sealing life time: 2.000.000 operations
- material: silicone



$$H = A + P + 13.2$$

This leaves nominal 0.3 mm clearance between the top of the cap and the inner side of the sealing boot to accomplish assembly tolerances. **A** can be chosen between 10 - 13 mm, we recommend 10 mm to reduce building height and optimize cap guidance.

A	P	CAP	H	BUSHING
10.0	1.0	AQCXX-24.2	24.2	AQN-0.5
10.0	2.0	AQCXX-25.2	25.2	AQN-0.5
10.0	3.0	AQCXX-26.2	26.2	AQN-2.5
10.0	4.0	AQCXX-27.2	27.2	AQN-2.5

Cap is available in black (09) or transparent (11).

The dimension H is the overall height of the switch+cap.

Bushing AQN-0.5 accepts panel thickness (P) 0.5-2.5 mm.

Bushing AQN-2.5 accepts panel thickness (P) 2.5-4.0 mm.

Panel cut out $\varnothing 12.0 \pm 0.2$.

How to order

3 | F +
Switch **Mounting**
T through-hole **L** 6 low temp.
S surface mount **H** 9 high temp.

AQN - <input type="checkbox"/> . <input type="checkbox"/>	+ AQC <input type="checkbox"/> <input type="checkbox"/> - <input type="checkbox"/> . <input type="checkbox"/> + AQB01 <input type="checkbox"/> <input type="checkbox"/>			
Bushing	Panel	Cap	Overall Height	Sealing boot, incl. sealing ring
	0.5 2.5	09 black 11 transparent	24.2 25.2 26.2 27.2	09 black 11 transparent

3 | F **T** + **AQN** - . + **AQC** - . + **AQB01**
Switch **Mounting**
T through-hole **L** 6 low temp.
H 9 high temp.

LED
00 blue
20 green
40 yellow
60 white
80 red
2040 green/yellow
8020 red/green
8040 red/yellow

AQN - <input type="checkbox"/> . <input type="checkbox"/>	+ AQC <input type="checkbox"/> <input type="checkbox"/> - <input type="checkbox"/> . <input type="checkbox"/> + AQB01 <input type="checkbox"/> <input type="checkbox"/>			
Bushing	Panel	Cap	Overall Height	Sealing boot, incl. sealing ring
	0.5 2.5	11 transparent	24.2 25.2 26.2 27.2	11 transparent

Keycaps shown on this page can also be used on
illumec™ switch 4F - see page 13

Ordering example: AQB0109 + AQC09-27.2 + AQN-2.5 + 3FTL6

multimec® Legends





All standard legends are white on black caps.

The size of the legends listed may not correspond to the actual size. Please ask your local distributor, if you do not find what you need on the list. New legends may have been added after this catalogue was printed.


Custom legends and other colour combinations are available, please contact your local distributor.

Note!



For 1A/1B the orientation shown above is standard.

Please consider the switch orientation you require before specifying legend orientation.



For the 1D and 1F caps the orientation shown above is standard.

Please consider the switch orientation you require before specifying legend orientation.

Standard Keycap Legends

Part no.



LEGEND	1A09XU	1A09XD	1B09XU	1B09XD	1D09	1F096	1ZB09XD	1ZC09
0	000	000	000	000	000	000		
1	001	001	001	001	001	001		
2	002	002	002	002	002	002		
3	003	003	003	003	003	003		
4	004	004	004	004	004	004		
5	005	005	005	005	005	005		
6	006	006	006	006	006	006		
7	007	007	007	007	007	007		
8	008	008	008	008	008	008		
9	009	009	009	009	009	009		
A	010	010	010	010				
B	011	011	011	011				
C	012	012	012	012				
D	013	013	013	013				
#	107	107	107	107	107	107		
*	019	019	019	019	019	019		
□	016	016	016	016				
→	033	033	033	033	033			
←	133	133	133	133	133			
↑	034	034	034	034	034			
↓	134	134	134	134	134			
↔	135	135	135	135	135	135		
+	054	054	054	054				
-	059	059	059	059				
•	056	056	056	056				
▲						136		
POWER	123	123	123	123	123	123		
START	031	031	031	031				
CLEAR	036	036	036	036				
LOAD	037	037	037	037				
RESET	038	038	038	038			038	
CANCEL	048	048	048	048				
ENTER							105	
OK							118	
SET							119	
MENU							120	
FUNC							121	
HOME							122	

* 1ZC16 for illumination

Applications with mec switches

<p>Studio Equipment</p>  <p>Navimec, 3A+1ZA</p>	<p>Security Access Control</p>  <p>Navimec, 3A+1B+2A, 3A+1A</p>	<p>Digital Microscope</p>  <p>3F+1D</p>
<p>Barcode Reader</p>  <p>3C in-moulded</p>	<p>Pump Control Unit</p>  <p>3E</p>	<p>Space Shuttle Internal Communication</p>  <p>Unimec 15501+16300+16310</p>
<p>Control for Video Camera in Police Cars</p>  <p>3A+1A, 1H</p>	<p>Conference Systems</p>  <p>3F+1ZA, 1ZC 3A+1H, 1M</p>	<p>Door Entry Control</p>  <p>3F+1T, 1U, 1V, 1F</p>

Applications with mec switches

<p>Police Speed Control</p>  <p>3F+1D, 1T, 1V</p>	<p>Control Panel for Boats</p>   <p>3F+1U</p>	<p>Scooter for Disabled People</p>   <p>3F+1D</p>
<p>Defibrillator</p>  <p>3C under foil</p>	<p>Tree Felling Equipment</p>   <p>3E</p>	<p>Flight Simulators</p>  <p>3F+1P</p> <p>3F+1P,1D</p>
<p>Military Handheld Computer</p>   <p>3C</p>	<p>Car Operation Panel for Disabled People</p>  <p>3F+1ZA, 1ZC</p> <p>Navimec, 3F+1ZC</p>	<p>Mixing Console</p>   <p>3F+1K,1E</p>


multimec® 3F + 1GA/1GC

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C




Dimensions (through-hole)




Dimensions (w/extender)




Dimensions (SMD)




PCB layout



PCB layout



PCB layout



How to order

3 | F



Switch



+

1 | G | A | 0 | 9

+

2 | S | 0 | 9 | - | | | . | 0

Extender black

Height



05.0
06.0
07.0
08.0
09.0
10.0

L | 6 low temp.
H | 9 high temp.



1 | G | C | 0 | 9

Cap black

(Optional)
Adds 5-10 mm
to total height.



Keycap	Variable Extender	H (height) mm	Example
1GA/1GC	2S09-05.0	12.5	H 1
1GA/1GC	2S09-06.0	17.5	H 2
	2S09-07.0	18.5	
	2S09-08.0	19.5	
	2S09-09.0	20.5	
	2S09-10.0	21.5	
		22.5	H 3

H = Overall height


Overall heights below 12.5 mm - Please see Multimec® versions 3C and 3E.

All 2S09 extenders are stackable giving the possibility to match most overall heights.

A = We recommend you to allocate enough space for travel of the foil and leave the area free from adhesive.

Switch travel = 1 mm.

H = We recommend you to calculate this dimension from the top of the PCB to the inner top of the panel.



Ordering example: 3FTL6 + 1GA09 or 3FTL6 + 2S09-07.0 + 1GC09

For updates of products and/or changes of specifications please see www.mec.dk

multimec® 3C/3E

Technical Data

- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C
high temp: -40/+160°C
actuator:
in PPS: -40/+160°C
in polycarbonate: -40/+85°C



Standard 3C		Variable heights 3E	
Dimensions (through-hole)	Dimensions (SMD)	Dimensions (through-hole)	Dimensions (SMD)
PCB layout	PCB layout	PCB layout	PCB layout

How to order

3 C	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Switch	Mounting	L 6 low temp. white	L 9 low temp. black	H 9 high temp.		
	T through-hole					
	S surface mount					

3 E	<input type="checkbox"/>	<input type="checkbox"/>	9	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Switch	Mounting	L low temp.	Black	-	Standard overall height	
	T through-hole	H high temp.	Actuator made of PPS		08.0	
	S surface mount				09.5	

Custom heights:

3E is available in any height from 08.0 to 15.0mm.
Min. order qty. for custom heights is 2.000 pcs.

3 E	T	L	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Switch	Mounting	L low temp.	20 blue	-	Standard overall height	
	T through-hole		23 grey		08.0	

Switch and 3E actuator can be delivered unassembled.

The actuators made of polycarbonate can also be used for high temperature switches,
however they must be mounted after soldering and the temp. range will be reduced to 85°C.

Ordering example: 3CTL6 and 3ETL9-09.5 or 3ETL23-08.0


varimec™ double variability

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range switch:
low temp: -40/+115°C
high temp: -40/+160 °C
- temperature range cap:
-40/+160 °C




Round ø5.2




Round ø7.8




Round ø11.6



PCB Layout (through-hole)




PCB Layout (SMD)



The Concept

H = Overall heights from 10.4-22.5
A = Variable height from 2.4 to 6.4
A cannot exceed **H** - 8.0
B = Fixed recess 1.6
D = Fixed switch 6.4
C = Variable from 0-8.1
C = **H-A-B-D**
 All measurements in mm

How to order



Switch

Shape and Size

Colour Codes

Overall Height H

Height above recess A

Tape*

3ETL

A 5.2 Round

60 blue

A 10.4

A 2.4

R

3ESH

E 7.8 Round

63 grey

B 11.0

B 3.0

3ETH

K 11.6 Round

64 yellow

C 12.0

C 3.5

68 red

D 12.5

D 4.0

69 black

E 13.0

E 4.5

F 14.0

F 5.0

G 15.0

G 5.6

H 16.0

H 6.4

J 19.0

K 22.5

Cap alone:

Instead of part no. for switch please use 3E- and then same as above

Examples Switch and Cap:

3ETLE64CC = Switch 3ETL, 7.8 Round Cap, Yellow, Overall Height 12.0, Height above recess 3.5, (Height under recess 0.5).

Example Cap Alone:

3E-E63FF = Cap, 7.8 Round, Grey, Overall Height with switch 14.0, Height above recess 5.0, (Height under recess 1.0).

Min. order is 2.000 pcs. per shape, size and heights for parts mentioned above.


For heights not mentioned in the list a start-up fee will apply.

*Only overall height up to 12.5mm can be supplied on tape.


varimec™ double variability

Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range switch:
low temp: -40/+115°C
high temp: -40/+160°C
- temperature range cap:
-40/+160°C




Square 5.2




Square 7.8




Square 11.6



PCB Layout (through-hole)




PCB Layout (SMD)



The Concept

H = Overall heights from 10.4 - 22.5
A = Variable height from 2.4 to 6.4
A cannot exceed **H** - 8.0
B = Fixed recess 1.6
D = Fixed switch 6.4
C = Variable from 0-8.1
C = **H-A-B-D**
 All measurements in mm

How to order



Switch

Shape and Size

Colour Codes

Overall Height

H

Height above recess

A

Tape*

3ETL

B 5.2 Square

60 blue

A 10.4

A 2.4

R

3ESH

F 7.8 Square

63 grey

B 11.0

B 3.0

3ETH

L 11.6 Square

64 yellow

C 12.0

C 3.5

68 red

D 12.5

D 4.0

69 black

E 13.0

E 4.5

70

F 14.0

F 5.0

71

G 15.0

G 5.6

72

H 16.0

H 6.4

73

J 19.0

J 9.0

74

K 22.5

Cap alone:

Instead of part no. for switch please use 3E- and then same as above

Examples Switch and Cap:

3ESHB60AA = Switch 3ESH, 5.2 Square Cap, Blue, Overall Height 10.4, Height above recess 2.4, (Height under recess 0).

Example Cap Alone:

3E-E63FF = Cap, 7.8 Square, Grey, Overall Height with switch 14.0, Height above recess 5.0, (Height under recess 1.0).

Min. order is 2.000 pcs. per shape, size and heights for parts mentioned above.

For heights not mentioned in the list a start-up fee will apply.

*Only overall height up to 12.5 mm can be supplied on tape.


multimec® Right Angle Switches

Technical Data


- through-hole only
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C




Dimensions 3CTRAS




PCB layout




Dimensions 3ETRAS




PCB layout




Dimensions 3FTRAS




PCB layout



**Dimensions 3FTRAS
w/LED**



**PCB layout
(top view)**



How to order

3 **E**
Switch
3C
3F

T
Mounting
T through-hole

L **6**
L low temp.

R **A** **S**
Right angle support

3FTL6RAS - for caps 1D-1K-1P-1S see page 31

3 **E**
Switch

T
Mounting
T through-hole

L
low temp.



Actuator made of PPS

9 black
20 blue
23 grey
24 yellow
28 red
29 black

Two digit colour code means
actuators made of polycarbonate



R **A** **S**

Actuator height
1.6
3.1
4.0
4.6
5.6
8.6

Switch and 3E actuator can be
delivered unassembled.

3 **F**
Switch

T
Mounting
T through-hole

L **6**
L low temp.



LED
00 blue
20 green
40 yellow
60 white
80 red
2040 green/yellow
8020 red/green
8040 red/yellow

R **A** **S**

Right angle support

3FTL6RAS w/LED can be used with the keycaps:
1D, 1E, 1F, 1K, 1N, 1Q, 1R, 1S, 1T, 1U, 1V, 1WA, 1WD,
1WP, 1X

Ask for drawings/dimensions for these keycaps with
3FTL6RAS w/LED


Ordering example: 3FTL620RAS + 1Q096

For updates of products and/or changes of specifications please see www.mec.dk



multimec® RAS + 1D/1K/1P/1S

Technical Data


- through-hole only
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
low temp: -40/+115°C




Dimensions 1D




**PCB layout
(top view)**




Dimensions 1K




**PCB layout
(top view)**





Dimensions 1P




**PCB layout
(top view)**



Dimensions 1S



**PCB layout
(top view)**



How to order

3 | F

T

Switch

Mounting
T through-hole

L | 6

L 6 low temp.

R | A | S

Right angle support

+

1 | D | |



- | | | |
|------------|-----------|---------------|
| Cap | 00 blue | 30 ultra blue |
| | 02 green | 40 dusty blue |
| | 03 grey | 42 aqua blue |
| | 04 yellow | 32 mint green |
| | 06 white | 33 tele grey |
| | 08 red | 34 melon |
| | 09 black | 38 noble red |

50 metal dark blue

53 metal light grey

57 metal dark grey

58 metal bordeaux

1 | P | |



- | | |
|------------|----------|
| Cap | 00 blue |
| | 03 grey |
| | 08 red |
| | 09 black |

1 | K | | 1 | 6



- | | |
|------------|-----------|
| Cap | 00 blue |
| | 02 green |
| | 03 grey |
| | 04 yellow |
| | 06 white |
| | 08 red |
| | 09 black |

2 | K | |



- | | |
|--------------|----------|
| Bezel | 03 grey |
| | 06 white |
| | 08 red |
| | 09 black |

1 | S | 0 | 9 | - | | . |



- | | | |
|------------------|----------|------------|
| Cap black | H | X * |
| | 16.0 | 8.5 |
| | 19.0 | 11.5 |
| | 22.5 | 15.0 |

Other keycaps such as 1GA, 1GC, 1N, 1T, 1U, 1V, 1WA, 1WD, 1WP and 1X can be used on 3FTL6RAS. It may require reducing the size of the PCB to the front side of the switch body to avoid the cap touching the PCB. Ask for drawings/dimensions for these keycaps with 3FTL6RAS.

Please also see 3FTL6RAS with LED on page 30.






*Any cap height X from 8.5 to 15.0 mm is available.







Please order 1S09-H, where H = X+7.5 mm

Min. order quantity for custom heights is 2.000 pcs.





Ordering example: 3FTL6RAS+1K0016 + 2K03

multimec® basic switch modules

Through-hole Versions					
3A	3C	3E	3F		
For 1A/1B/1M/1ZA/1ZB w/LED for 1C/1H		For 3E actuators/Varimec	For 1D/1K/1N/1P/1S/1T/1U/1V/1WA/1WD/1WG/1WP/1X/1ZC/1GA/1GC w/LED for 1D/1E/1F/1N/1Q/1R/1S/1X	w/LED for 1D/1E/1F/1N/1Q/1R/1S/1X	w/LED for 1K /1KB/1KC/1T/1U/1V/1WA/1WD/1WP
					
Standard Versions					
3ATL6 3ATH9	3ATL600/20/40/80 3CTL6/3CTL9 3CTH9	3CTL6/3CTL9 3CTH9	3ETLXX-H* 3ETHXX-H*	3FTL6 3FTH9	3FTL600/20/40/60/80/ 2040/8020/8040 3FTL623/45/88
* 3E available in 6 standard heights: 08.0, 09.5, 10.4, 11.0, 12.0, 15.0 mm. Other heights between 08.0 and 15.0 mm are available upon request.					
Specials: Gold contacts, quiet version and actuation force other than 3.0N					


Surface Mount Versions				illumec™ Through-hole Versions		illumec™ Surface Mount Versions	
3A	3C	3E	3F	4AT w/LEDs	4FT w/LEDs	4AS w/LEDs	4FS w/LEDs
For 1A/1B/1M/1ZA/1ZB		For 3E actuators/Varimec	For 1D/1K/1N/1P/1S/1T/1U/1V/1WA/1WD/1WP/1X/1ZC/1GA/1GC	For 1C/1H	For 1D/1E/1F/1K/1KB/1KC/1N/1Q/1R/1S/1T/1U/1V/1WA/1WD/1WP/1X	For 1C/1H	For 1D/1E/1F/1K/1KB/1KC/1N/1Q/1R/1S/1T/1U/1V/1WA/1WD/1WP/1X
							
Standard Versions				Standard Versions			
3ASH9/3ASH9R	3CSH9/3CSH9R	3ESH9/3ESH9R	3FSH9/3FSH9R	4ATH901/22/42/61/82/ 2242/8222/8242	4FTH901/22/42/61/82/ 2242/8222/8242	4ASH901/22/42/61/82/ 2242/8222/8242	4FSH901/22/42/61/82/ 2242/8222/8242

Co-planarity = ≤ 0.05

Right Angle Versions			
3C	3E	3F	3F w/LED
	For 3E actuators/Varimec	For 1D/1K/1N/1P/1S/1T/1U/1V/1W/1WA/1WD/1WP/1X/1ZC/1GA/1GC	For 1D/1E/1F/1N/1Q/1R/1S/1X
			
Standard Versions			
3CTRL6RAS	3ETXX-X.XRAS	3FTL6RAS	3FTL600/20/40/60/80/ 2040/8020/8040RAS


DIMENSIONS (mm) Unless otherwise specified, all tolerances ± 0.2

multimec® Cross Section





multimec® basic switches and tape & reel

Recommended PCB layout



Operating Force (typical example)



Tape and reel is available for the parts listed and has the following specifications:

Reel diameter	ø330mm
Tape width	24mm
Pitch	see list
Tape and reel material	antistatic or better
Quantity per reel	see list

3A/3C/3E/3F multimec® tape & reel


Part No.	Ordering Code	Pitch	Quantity per reel
3ASH9	3ASH9R	16	500
3CSH9	3CSH9R	16	500
3ESH9	3ESH9R	16	500
3ESH9-08.0	3ESH9R08.0	20	250
3ESH9-09.5	3ESH9R09.5	20	250
3ESH9-10.4	3ESH9R10.4	20	250
3ESH9-11.0	3ESH9R11.0	20	250
3ESH9-12.0	3ESH9R12.0	20	250
All varimec below R after the part no.		20	250
12.5		20	250
3FSH9	3FSH9R	20	250

4F illumec™ tape & reel


Part No.	Ordering Code	Pitch	Quantity per reel
4FSH901	4FSH901R	20	250
4FSH922	4FSH922R	20	250
4FSH942	4FSH942R	20	250
4FSH961	4FSH961R	20	250
4FSH982	4FSH982R	20	250
4FSH92242	4FSH92242R	20	250
4FSH98222	4FSH98222R	20	250
4FSH98242	4FSH98242R	20	250

Specifications are according to EIA 600481-3 and IEC 60286-3


Circuit Diagram



How to Assemble



Mounting Tool for Through-hole versions




Specifications are subject to change without notice.


multimec® spacing

Basic switch spacing

through-hole




surface-mount




Recommended switch/cap spacing


Switch spacing




Cap dimension




Panel cut-out



Panel Cut-out




1T




Spacing in mm

Spacing examples


multimec®




multimec®




multimec®




multimec®



multimec®



multimec®



Cap series

Recommended*
min. switch spacing AxBNominal cap dimension
W x HRecommended
min. panel cut-out

1A	12.7 x 10.16	12.6 x 10.1	13.0 x 10.5
1B/1C+2A/2B	15.24 x 15.24	15.1 x 15.1	15.5 x 15.5
1D/1E/1F	12.7 x 12.7	ø9.6	ø10.0
1K	15.24 x 15.24	14.3 x 14.3	14.7 x 14.7
1M	25.4 x 10.16	25.0 x 10.1	25.7 x 10.5
1N	12.7 x 12.7	ø9.8/□4.9	ø10.2/□5.1
1P/1Q/1R	15.24 x 10.16	6.5 x 12.5	7.0 x 13.0, R Max. 1.0
1S	12.7 x 10.16	ø6.5	ø7.0
1T	12.7 x 12.7	10.6 x 10.6	11.0 x 11.0
1U	12.7 x 12.7	ø10.6	ø11.0
1V (pointing outwards)	12.7 x 12.7	10.6 x 13.25	11.0 x 13.65
1X	12.7 x 12.7	9.4 x 7.4	9.8 x 7.9

*A dimension with surface mount version is min. 15.24. Depending on manufacturing technology it may be necessary either to reduce pad dimension, or to increase spacing.

In all applications the total assembly tolerance must be analysed by the user (board tolerance, front panel, assembly accuracy), to secure enough room for a free switch movement in the final product. The specifications on this page are to be considered as an aid only. MEC cannot be held responsible for the final assembly.

multimec® technical specifications

RoHS Compatible

	3A-3C-3E-3F Low Temperature Versions		3A-3C-3E-3F High Temperature Versions		illume™ 4A - 4F High Temperature Versions	
	Silver	Gold	Silver	Gold	Silver	Gold
Electrical Specifications						
Contact resistance	<30m Ω - typ. 10m Ω		<30m Ω - typ. 10m Ω		<30m Ω - typ. 10 m Ω	
Insulation resistance	>10M Ω		>10M Ω		>10M Ω	
Recommended load	0.5-50mA 24VDC	0.5μ-50mA 24VDC	0.5-50mA 24VDC	0.5μ-50mA 24VDC	0.5-50mA 24VDC	0.5μ-50mA 24VDC
Contact bounce	<2mS - typically 0.5mS		<2mS - typically 0.5mS		<2mS - typically 0.5mS	
Mechanical Specifications						
Standard actuation force (switch)	3.0N typ.		3.0N typ.		3.0N typ.	
Max. actuation force without cap	100N for 10 sec.		100N for 10 sec.		100N for 10 sec.	
Key travel (switch)	1 mm		1 mm		1 mm	
Life time (switch)	>10.000.000 cycles		>10.000.000 cycles		>10.000.000 cycles	
Temperature Range						
Working temperature	Min. -40°C Max. +115°C		Min. -40°C Max. +160°C		Min. -30°C Max. +85°C*	
Storage temperature	Min. -40°C Max. +115°C		Min. -40°C Max. +160°C		Min. -30°C Max. +85°C*	
Soldering IEC 68-2-20						
Wave	max. 260°C for max. 10 sec., please refer to usage guidelines.		Infrared, vapour phase, wave - max. 240°C for max. 40 sec. or max. 260°C for max. 30 sec.		Infrared, vapour phase, wave - max. 240°C for max. 40 sec. or max. 260°C for max. 30 sec.	
Soldering iron	max. 350°C for max. 3 sec.		Soldering iron - max. 350°C for max. 3 sec.		Soldering iron - max. 350°C for max. 3 sec.	
Flux tight.			Flux tight.		Flux tight.	
Environmental Endurance IEC 68-2-3						
Temperature	+40°C		+40°C		+40°C	
Humidity	93% RH		93% RH		93% RH	
Duration	56 Days		56 Days		56 Days	
Temperature Cycling IEC 68-2-14						
Temperature limit	Min. -40°C - Max. +125°C		Min. -40°C - Max. +125°C		Min. -40°C - Max. +125°C	
Number of cycles	10		10		10	
Exposure time at each temperature	30 min.		30 min.		30 min.	
Recovery time before measurements	16 hrs.		16 hrs.		16 hrs.	
Sealing IEC 529	IP-67		IP-67		IP-67	
Cleaning	Standard methods - see usage guidelines		Standard methods - see usage guidelines		Standard methods - see usage guidelines	
Vibration Test IEC 68-2-6						
Cycles					10	
Cycles time					2 hrs.	
Material Specifications - Switches						
Housing	PBT UL94VO		PPS UL94VO		PPS UL94VO	
Actuator	PBT UL94VO		PPS UL94VO		PPS UL94VO	
Sealing + spring	Silicone rubber		Silicone rubber		Silicone rubber	
Contact spring	Stainless steel + 3µAg	Stainless steel + 1µAu	Stainless steel + 3µAg	Stainless steel + 1µAu	Stainless steel + 3µAg	Stainless steel + 1µAu
Fixed contacts	SnCu + 2µNI + 3µAg	SnCu + 2µNI + 1µAu	SnCu + 2µNI + 3µAg	SnCu + 2µNI + 1µAu	SnCu + 2µNI + 3µAg	SnCu + 2µNI + 1µAu
Terminals	SnCu + 2µNI + 3µSn100	SnCu + 2µNI + 3µSn100	SnCu + 2µNI + 3µSn100	SnCu + 2µNI + 3µSn100	SnCu + 2µNI + 3µSn100	SnCu + 2µNI + 3µSn100
Material Specifications - Caps & Bezels						
Material	Parts		Temp limit	UL rating		
ABS	1A, 1B, 1C, 1D, 1E, 1F, 1H, 1K, 1M, 1N, 1P, 1Q, 1R, 1T, 1U, 1V, 1WA, 1WD, 1WP, 1X, 1ZA, 1ZB, 1ZC.		Max. 65°C	UL94HB		
Polycarbonate	All lenses, 3E coloured actuators		Max. 85°C	UL94V1		
LCP	Black actuator of 3E		Max. 160°C	UL94VO		
PPS	1S, 2S		Max. 160°C	UL94VO		
Polyamide	Actuator of Varimec™, 1GA/1GC		Max. 160°C	UL94VO		
Legends Adhesion	ISO Class: 1/ASTM Class: 4B DIN EN ISO 2409					

* LED max. working temperature

Specifications are subject to change without notice.

multimec® LEDs

For 3A switches

	3AXXX (for 1C/1H)				2BXXX			
Colour	B	G	Y	R	G	Y	R	
Color Codes	00	20	40	80	20	40	80	
Absolute Maximum Ratings (Ta=25°C)								
Power	mW	105	100	60	100	75	60	60
Current forward	mA	30	30	20	30	20	20	20
Forward peak current	mA	150	120	80	120	60**	60**	60**
Voltage reverse	V	5	5	5	5	3	3	3
Operating temperature	°C	-40 - +85	-55 - +100			-25 - +85		
Storage temperature	°C	-40 - +85	-55 - +100			-30 - +100		
Soldering temperature	°C	260/5 sec.	260 for max. 3 sec.			260 for max. 5 sec.		
Electrical-Optical Characteristics (Ta=25°C)								
Voltage forward	Typ. V	3.8	2.1*	2.1*	2.0*	2.1	2.1	2.0
	Max. V	4.5	2.8*	2.8*	2.8*	3.0	3.0	3.0
Current reverse (VR = 5V)	µA	10	100	100	100	10	10	10
Wave length	nm	466	565	585	630	563	585	650
Spread	Δnm	30	30	35	40	40	40	40
Spread angle	degree	40	90	90	90	45	45	45
Luminous Intensity	Min. mcd	4	0.7	1.7	1.1	9.0	5.6	5.6
	Typ. mcd	10	2.5	5.6	3.7	25	16	16
Orientation	The longer pin is the anode, the shorter is the cathode							

*/F = 20mA, **Pulse width 1ms Duty cycle 1:5

For 3F switches

	3FXXX (for 1E-1F-1N-1Q-1R-1S-1X)				3FXXX (for 1K-1T-1U-1V-1W-1WD)					
Colour	B	G	Y	R	G/Y	R/G	R/Y	G	Y	R
Color Codes	00	20	40	80	2040	8020	8040	23	45	88
Absolute Maximum Ratings (Ta=25°C)										
Power	mW	105	70	60	60	120	120	150	130	300
Current forward	mA	30	20	20	20	25	25	40	40	90
Forward peak current	mA	200	60**	60**	60**	150	150	500	500	1000
Voltage reverse	V	5	3	3	3	5	5	5	12	5
Operating temperature	°C	-25 - +85				-40 - +85				-55 - +100
Storage temperature	°C	-30 - +100				-40 - +85				-55 - +100
Soldering temperature	°C	260 for max. 5 sec.				260 for max. 2 sec.				300 for max. 3 sec.
Electrical-Optical Characteristics (Ta=25°C)										
Voltage Forward	Typ. V	2.1	2.1	2.1	2.0	2.1	2.1	2.1	2.1*	2.3***
	Max. V	2.8	3.0	3.0	3.0	2.8	2.8	2.8	2.5*	2.5***
Current reverse (VR = 5V)	µA	2	10	10	10	2	2	2	10	10
Wave length	nm	460	563	585	650	565/590	625/565	625/590	570	587
Spread	Δnm	40	40	40	40	35	35	35	25	45
Spread angle	degree	20	45	45	45	60	60	80	90	55
Luminous Intensity	Min. mcd	20	9.0	5.6	5.6	8	8	8	71****	71****
	Typ. mcd	25	25	16	16	25	25	25	112****	112****
Orientation	The longer pin is the anode, the shorter is the cathode. For bicolor LEDs the anode for the first colour (ex. 2080) is the longer pin.									

/F = 50mA, *Luminous Flux mlm

For 4A/4F switches

	illumec™ LEDs specifications				
Colour	B	G	Y	W	R
Color Codes	01	22	42	61	82
Absolute Maximum Ratings (Ta=25°C)					
Power	mW	60	65	65	65
Current forward	mA	20	25	25	25
Forward peak current	mA	150	150	100	100
Voltage reverse	V	5	12	12	5
Operating temperature	°C	-30 - +85			
Storage temperature	°C	-30 - +85			
Soldering temperature	°C	245 for max. 10 sec.			
Electrical-Optical Characteristics (Ta=25°C)					
Voltage forward	Typ. V	3.35	2.2	2	3.05
	Max. V	3.5	2.5	2.5	2.5
Current reverse (VR = 5V)	µA	0.01	0.02	0.01	0.01
Wave length	nm	470	570	588	n.a. 633
Spread	Δnm	n.a.	30	16	n.a. 16
Spread angle	degree	145	160	160	138 160
Luminous Intensity	Min. mcd	30	28	112	28 112
	Typ. mcd	35	70	150	35 150
Optical Intensity	Lm/w	4		2.5	

B= Blue, G= Green, Y= Yellow, R= Red, W= White, G/Y= Green/Yellow, R/G= Red/Green, R/Y= Red/Yellow

Specifications are subject to change without notice.

multimec® Solid Colours

No. Colour RAL Code	00 blue 5012		02 green 6018		03 grey 7004		04 yellow 1023		06 white 9010		08 red 3000		09 black 9004
---------------------------	--------------------	--	---------------------	--	--------------------	--	----------------------	--	---------------------	--	-------------------	--	---------------------

No. Colour RAL Code	30 ultra blue 5002		32 mint green 6029		33 tele grey 7046		34 melon 1028		38 noble red 3002		40 dusty blue 5014		42 aqua blue 5021	
---------------------------	--------------------------	--	--------------------------	--	-------------------------	--	---------------------	--	-------------------------	--	--------------------------	--	-------------------------	--

Metallic Colors












No. Colour RAL Code	50 dark blue No RAL Code		53 light grey No RAL Code		57 dark grey No RAL Code		58 bordeaux No RAL Code	
---------------------------	--------------------------------	--	---------------------------------	--	--------------------------------	--	-------------------------------	--

Cap		00	02	03	04	06	08	09	30	32	33	34	38	40	42	50	53	57	58
1A		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
1B		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
1C		X	X	X	X	X	X	X											
1D		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
1E		X	X	X	X	X	X	X											
1F		X	X	X	X	X	X	X											
1H		X	X	X	X	X	X	X											
1K		X	X	X	X	X	X	X											
1M		X	X	X	X	X	X	X											
1N		X		X	X		X	X											
1P		X	X	X	X	X	X	X											
1Q		X		X			X	X											
1R		X		X			X	X											
1S									X										
1T		X		X			X	X											
1U		X		X			X	X											
1V		X		X			X	X											
1WA/1WD/1WP		X		X			X	X	X						X	X		X	X
1X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
1ZA				X		X		X	X						X	X	X	X	X
1ZB					X		X		X	X					X	X	X	X	X
1ZC					X		X		X	X					X	X	X	X	X

The RAL Codes mentioned are the codes nearest to the solid colours in the multimec® range.

Technical Data

- Max. 250mA/120V/9W AC/6W DC
- 2 pole
- momentary or alternate
- 8 contact functions
- temperature range:
low temp: -40/+75°C
high temp: -40/+160°C
- through-hole version

**Dimensions****Dimensions (w/LED)****Dimensions (w/2 LEDs)****PCB layout****PCB layout (top view)****PCB layout (top view)****PCB layout (top view)****How to order**

1 5 [] []

+

1 6 2 7 0

+ 1 6 3 0 0 []

+

1 6 3 2 4 []

**Switch**

- 15501 mom. silver
15551 alt. silver
15502 mom. gold
15552 alt. gold
15500 silent silver
15401 mom. silver high temp.
15402 mom. gold high temp.
15420 silent gold high temp.
15451 alt. silver high temp.

Extender**Cap****00 blue**

- 30 ultra blue
01 brown
02 green
03 grey
04 yellow
05 golden
06 white
07 orange
08 red
09 black

Bezel

- 01 brown
03 grey
06 white
09 black



1 5 [] [] + 1 6 2 7 0 + 1 6 3 0 0 [] +

+ [] [] [] + 1 6 3 2 7 [] + 1 6 9 2 2 []

Switch

Extender

Cap

16325

Lens

- 02 green
04 yellow
08 red

LED

- 02 green
04 yellow
08 red

16326



Lens 16327

2 required

LED 16922

2 required

Ordering example: 15501 + 16270 + 1630008 + 1632509 + 1632708 + 1692208

unimec™

16310 - 16315

Technical Data

- Max. 250mA/120V/9W AC/6W DC
- 2 pole
- momentary or alternate
- 8 contact functions
- temperature range:
low temp: -40/+75°C
high temp: -40/+160°C
- through-hole version



Dimensions (through-hole)	Dimensions (w/LED)	Dimensions (w/LED)	Dimensions (w/4 LEDs)
PCB layout	PCB layout (top view)	PCB layout (top view)	PCB layout (top view)

How to order



1 | 5 | | |

+

1 | 6 | 3 | 0 | 0 | |



- Switch**
15501 mom. silver
15551 alt. silver
15502 mom. gold
15552 alt. gold
15500 silent silver
15401 mom. silver high temp.
15402 mom. gold high temp.
15420 silent gold high temp.
15451 alt. silver high temp.

1 | 6 | 3 | 1 | 0 | |



- Bezel**
00 blue
01 brown
02 green
03 grey
04 yellow
05 golden
06 white
07 orange
08 red
09 black

For 16300 and 16310 only

- 30** ultra blue
40 dusty blue
42 aqua blue
32 mint green
33 tele grey
34 melon
38 noble red
50 metal dark blue
53 metal light grey
57 metal dark grey
58 metal bordeaux



1 | 5 | | |

+

1 | 6 | 3 | 0 | 0 | |



- Switch**

 | | | | |

Bezel 16311



Bezel 16312



Bezel 16314



Bezel 16315

1 | 6 | 9 | 2 | 1 |

- LED 16921** **02** green
04 yellow
08 red

+ 1 | 6 | 9 | 2 | 0 |

- LED 16920** **02** green
04 yellow
08 red

LED 16920 **LED 16921**
1 required **1 required**






LED 16920 **LED 16921**
2 required **2 required**

Ordering example: 15501 + 1630003 + 1631408 + 1692008 + 1692108

For updates of products and/or changes of specifications please see www.mec.dk

Technical Data

- Max. 250mA/120V/9W AC/6W DC
- 2 pole
- momentary or alternate
- 8 contact functions
- temperature range:
low temp: -40/+75°C
high temp: -40/+160°C
- through-hole version

**Dimensions 16300****PCB layout****Dimensions 16700****PCB layout****Dimensions 16800**

Blanking Cap
can be used with
VARIO SUPPORT

How to order

1 5 [] []

+

1 6 3 0 0 []

**Switch**

15501 mom. silver

15551 alt. silver

15502 mom. gold

15552 alt. gold

15500 silent silver

15401 mom. silver high temp.

15402 mom. gold high temp.

15420 silent gold high temp.

15451 alt. silver high temp.

- | | | |
|------------|------------------|----------------------|
| Cap | 00 blue | 30 ultra blue |
| | 01 brown | 40 dusty blue |
| | 02 green | 42 aqua blue |
| | 03 grey | 32 mint green |
| | 04 yellow | 33 tele grey |
| | 05 golden | 34 melon |
| | 06 white | 38 noble red |
| | 07 orange | |
| | 08 red | |
| | 09 black | |

- | |
|----------------------------|
| 50 metal dark blue |
| 53 metal light grey |
| 57 metal dark grey |
| 58 metal bordeaux |



1 5 [] []

+

1 6 7 0 0 []

**Switch**

- | | | |
|------------|------------------|-----------------|
| Cap | 00 blue | 06 white |
| | 02 green | 08 red |
| | 03 grey | 09 black |
| | 04 yellow | |

1 6 8 0 0 []

**Blanking Cap**

- | | |
|------------------|------------------|
| 00 blue | 06 white |
| 01 brown | 07 orange |
| 02 green | 08 red |
| 03 grey | 09 black |
| 04 yellow | |
| 05 golden | |


- | |
|------------------------------|
| 11 transparent |
| 12 transparent green |
| 14 transparent yellow |
| 18 transparent red |

Ordering example: 15551 + 1670009

unimec™

Vario Support

For all types of UNIMEC™ switches with bezels - 16310 - 16315 and 16324 - 16326



unimec™ Legends




All standard legends are white on black caps.

The size of the legends listed may not correspond to the actual size. Please ask your local distributor, if you do not find what you need on the list. New legends may have been added after this catalogue was printed.


Custom legends and other colour combinations are available, please contact your local distributor.

Standard Keycap Legends


Part no.



Part no.

























Part no.



LEGEND	18_	18_	LEGEND	18_	18_	LEGEND	18_	18_
0	000	200	A	010	210	ON/OFF	017	217
1	001	201	B	011	211	STOP	018	218
2	002	202	C	012	212	START	031	231
3	003	203	D	013	213	CLEAR	036	236
4	004	204	E	014	214	LOAD	037	237
5	005	205	F	015	215	RESET	038	238
6	006	206	G	063	263	CR	043	243
7	007	207	H	064	264	MANUAL	044	244
8	008	208	I	065	265	END	047	247
9	009	209	J	066	266	CANCEL	048	248
10	020	220	K	067	267	CTRL	050	250
11	021	221	L	068	268	ESC	051	251
12	022	222	M	069	269	DSP	053	253
13	023	223	N	070	270	ENTER	105	305
14	024	224	P	072	272	SHIFT	106	306
15	025	225	S	075	275	ON	116	316
16	026	226	T	076	276	OFF	117	317
			U	077	277			
			V	078	278			
			W	079	279			
			#	107	307			
			*	019	219			
			□	016	216			
			→	033	233			
			←	133	333			
			↑	034	234			
			↓	134	334			
			↔	135	335			
			↑↓	115	315			
			↔↔	041	241			
			+	054	254			
			-	059	259			
			•	056	256			
			:	055	255			

unimec™ switches with multimec® keycaps

Selection guide

A 16250 extender is needed when mounting multimec® keycaps on unimec™ switches						
Cap	1D	1E	1F	1P	1Q	1R
Dimensions	 	 	 	 	 	 
LED		16923XX 00 blue 20 green 40 yellow 80 red				16923XX 00 blue 20 green 40 yellow 80 red
Cap	 					
Dimensions	 	 	 	 		
LED		16923XX 00 blue 20 green 40 yellow 80 red		16923XX 00 blue 20 green 40 yellow 80 red		16924XX 23 green 45 yellow 88 red



For specific dimensions, color codes, how to order and other information please refer to the pages with the keycaps on multimec® switches. For technical information on the unimec™ basic switches please see technical specifications or go to our website www.mec.dk where you will find a page for each option.

The multimec® keycaps 1N, 1T, 1U, 1V, 1WA, 1WD, 1WP and 1X can also be used on unimec™ switches. Please ask for technical drawings on dimensions.


unimec™ basic switch modules

Basic module applies to all versions

Low temp.



High temp.




Part no:

1 5

Temperature:
5: low temp.
4: high temp.

Switch function:
0: momentary
5: alternate


Terminal
1: silver
2: gold
0: quiet version, silver



PCB Mounting Hole Dimensions Basic Switch	Circuit diagram (topview)	PCB Mounting Hole Dimensions (w/Extender 16250)	Functional diagram


Wiring Diagram

Select the contact function you desire - and design your PC board accordingly




How to assemble


unimec™
15XXX + 16300 +
16310



unimec™
15XXX + 16270 +
16300 + 16324



Operating Force (Typical example)



RoHS Compatible

	RB			RA		
	Low Temperature Versions			High Temperature Versions		
	Silver	Gold		Silver	Gold	
Electrical Specifications						
Contact resistance	Max. 100 m Ω (initially)			Max. 100 m Ω (initially)		
Insulation resistance	>10 M Ω			>10 M Ω		
Recommended load	Min. 0.5 mA	Min. 0.5μ A		Min. 0.5 mA	Min. 0.5μ A	
	Max. 250 mA - 120 V - 9W AC - 6W DC			Max. 250 mA - 120 V - 9W AC - 6W DC		
Max. current in non switching state	0.5 A			0.5 A		
Contact bounce	Max. 10 ms			Max. 10 ms		
Dielectric strength between adjacent contacts	1000 V for 2 min.			1000 V for 2 min.		
Insulation resistance between adjacent contacts	5 X 10 ¹³ Ω			5 X 10 ¹³ Ω		
Capacitance between adjacent contacts	0.5 pF			0.5 pF		
Mechanical Specifications						
Standard actuation force (switch)	typ 2.5N			typ 2.5N		
Max. actuation force without cap	100N for 10 sec.			100N for 10 sec.		
Key travel (switch)	1.8 mm			1.8 mm		
Life time	Momentary 1.500.000 cycles			Momentary >10.000.000 cycles		
	Alternate 500.000 cycles			Alternate 5.000.000 cycles		
Temperature Range						
Working temperature	Min. -40°C Max. +75°C			Min. -40°C Max. +160°C		
Storage temperature	Min. -65°C Max. +85°C			Min. -65°C Max. +160°C		
Soldering IEC 68-2-20						
	Wave - max 260°C for max. 10 sec., please refer to usage guidelines			Soldering iron - max. 350°C for max. 3 sec. Flux tight.		
Environmental Endurance IEC 68-2-3						
Temperature	+40°C			+40°C		
Humidity	93% RH			93% RH		
Duration	56 Days			56 Days		
Sealing IEC 529	IP-54			IP-54		
Cleaning	Standard methods such as water and soap (not immersed)			Standard methods such as water and soap (not immersed)		
Material Specifications - Switches						
Housing and actuator	Glass fiber filled Polycarbonate UL94V1			LCP UL94V0		
Switch spring	Stainless steel			Stainless steel		
Key spring	Stainless steel			Stainless steel		
Latch pin	Stainless steel			Stainless steel		
Fixed contact	SnCu + 2μNi + 3μAg		SnCu + 2μNi + 3μAu		SnCu + 2μNi + 3μAg	SnCu + 2μNi + 3μAu
Moving contact	Stainless steel + 3μAg		Stainless steel + 3μAg+1μAu		Stainless steel +3μAg	Stainless steel + 3μAg+1μAu
Terminals	SnCu + 2μNi + 3μSn100			SnCu + 2μNi + 3μSn100		
Contact lubricant	Special protective lubricant Klüber Barrierta I EL Fluid			Special protective lubricant Klüber Barrierta I EL Fluid		
Material Specifications - All Caps & Bezels						
Temperature limit	ABS (standard) UL94HB			ABS (standard) UL94HB		
Tampon Printing	Max. +65°C			Max. +65°C		
	According to ISO Class: 1/ASTM Class.: 4B			According to ISO Class: 1/ASTM Class.: 4B		

unimec™ LEDs

Part Nos.	16920/16921			16922			16923			16924				
Colour (G= Green, Y= Yellow, R= Red)	G	Y	R	G	Y	R	G	Y	R	G	Y	R		
Color Codes	02	04	08	02	04	08	20	40	80	23	45	88		
Absolute Maximum Ratings (Ta=25°C)														
Power	mW	100	100	100	135	135	135	70	60	60	150	130	300	
Current forward	mA	30	30	30	30	30	20	20	20	40	40	90		
Forward peak current	mA	50	50	50	90	90	90	60**	60**	60**	500	500	1000	
Voltage reverse	V	5	5	5	5	5	3	3	3	12	12	5		
Operating temperature	°C	-25 - +100			-55 - +100			-25 - +85			-55 - +100			
Storage temperature	°C	-25 - +100			-55 - +100			-30 - +100			-55 - +100			
Soldering temperature	°C	+245 for max. 3 sec.			+300 for max. 3 sec.			+260 for max. 5 sec.			+300 for max. 3 sec.			
Electrical-Optical Characteristics (Ta=25°C)														
Voltage Forward	Typ. V	2.0	2.0	2.0	2.1	2.2	2.3	2.1	2.1	2.0	2.1*	2.3***	2.4***	
	Max. V	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	2.5*	2.5***	3.8***	
Current reverse	μA	100	100	100	100	100	100	10	10	10	10	10	10	
Wave length	nm	560	590	660	565	585	635	563	585	650	570	587	635	
Spread	Ønm	10	10	10	10	10	10	40	40	40	25	45	45	
Spread angle	degree	20	20	20	45	45	45	45	45	45	80	90	55	
Luminous Intensity		Min. mcd	1	1	0.8	1.5	2.5	2.5	9.0	5.6	5.6	71****	71****	100****
	Typ. mcd	2	3	1.6	2.5	3.0	5.0	25	16	16	112****	112****	160****	
Orientation	The longer pin is the anode, the shorter is the cathode.													

*F = 20mA, **Pulse width 1ms Duty cycle 1:5, ***F= 50mA, ****Luminous Flux mlm

Specifications are subject to change without notice.

mec Usage Guidelines

How to get the best results with **mec** switches

These guidelines are offered to users of **mec** switches as an aid to ensure successful and reliable switch operation.

Temperature

Both Unimec™ and Multimec® switches are produced in standard and high temperature versions. Please see the technical specifications for details on operating and storage temperatures and soldering guidelines to make sure you select the best switch for your application. When wave soldering is taking place, **mec** strongly recommend that the temperature profile is analyzed and compared with the temperature rating of the switch. In case of doubt always select the high temperature versions Unimec™ 154XX and Multimec® 3XXH. It is also important to monitor the accumulated heat build up from both the pre-heat zones and the solder zone.

Most standard accessories for both Unimec™ and Multimec® switches are made from ABS plastic with a maximum operating temperature of 65°C. It is strongly recommended that accessories are mounted after soldering of the switch. If this is not possible care must be taken not to overheat the accessories during the soldering process. Actuators for the 3EXX9, the 1S09 and Varimec™ caps are, however, made of high temperature materials and will meet the same temperature specifications as the high temperature switches.

For accessories made from other plastic materials please see Multimec and Unimec technical specifications.

LEDs have their own temperature specifications. When fitted in a high temperature switch the LED will determine the max. operating temperature, i.e. 3FTH923 has an upper temperature limit of 85°C – not 160°C! This also applies to the 4A and 4F switches.

Mounting and Dismounting

If switches are to be mounted in rows it is essential that the recommendations regarding spacing are followed. PC board thickness should be 1.2 to 1.6 mm and terminal hole diameter should be 0.9 mm.

All Unimec™ and Multimec® caps and bezels are easily snapped onto the switch modules and can be changed at a later time with the exception of the Unimec™ 16.700 cap. The same applies to the 3E caps/actuators. Once these caps are installed they are not designed to be removed. To do so may cause damage to the switch and the PC board if not done very carefully. If the 16.300 or 16.700 cap must be removed from a Unimec™ alternate action switch, make sure that the switch actuator is in the released, upper position before attempting to remove the cap. This will prevent possible damage to the internal latching pin.

Care must be taken when inserting the 3FT switch and LED assembly into the PC board. Do not press direct on the LED. This will force the LED down into the actuator and risks to cause the switch contacts to remain in the closed position. To correct the fault, the LED must be raised slightly and centered in the actuator to assure unrestricted movement of the actuator. A mounting tool is available for Multimec® switches.

Soldering and Cleaning Unimec™

Most assembly and field problems experienced by users of unsealed switches are caused by the contamination of the contacts during soldering and cleaning.

Contact contamination may be recognized by an increase in contact resistance and possible intermittent operation of the switch, especially in low power applications. Care must be taken not to submerge the switch in cleaning agents or spray the switch during cleaning. The switch must be protected at all times to prevent contamination by flux or cleaning liquids.

For Unimec™ alternate versions we recommend to leave the actuator in the released upper position during soldering. This makes the switch more resistant to overheating.

Soldering and Cleaning Multimec®

Multimec® switches are fully sealed to IP67 specifications to prevent solder flux and aqueous or solvent based cleaning solutions from entering the switch and contaminating the contacts. The switches can be placed on the PC board with other components and wave soldered. Multimec® offers a high level of sealing, however, with aqueous solvent solutions care must be taken to avoid the worst case situation with water jets, complete immersion into a liquid with a temperature below the board or surface tension reducing additives.

Recommended cleaning methods are demineralized water. Any surface tensions reducing agents, such as soap, must not be used as they risk causing a potential leakage of the switch.

Soldering - Through Hole Versions

Hand soldering: Max 350°C for max. 3 sec., this applies for both low temperature and high temperature versions.

Wave soldering: Heat built up in the switch during pre-heating and soldering must not exceed the maximum operating temperature of the switch. If, for some reason, a high pre-heating temperature is required, **mec** recommend the high temperature switches. In any case peak temperature must not exceed 260°C, and soldering time is max. 10 sec.

Soldering - Surface Mount Versions

For all methods – infrared, convection and vapour phase. The upper limit 260°C/30 sec. must be observed. The soldering temperature profile must have moderate temperature gradients.

RoHS Compliance

As of 1 July 2006 **mec** has completed the conversion to RoHS compliance. A separate part number system assures that there will not be any risk for mixing products in the supply chain. For more info please see our homepage www.mec.dk

General Temperature Limits:

Low Temperature	115°C
High Temperature	160°C
LEDs	85/100°C
Accessories	65/85/160°C

Packaging

Unimec™ and Multimec® switches are packed in rigid tubes of 50 pieces each.

A box contains 1.000 pcs.

The surface mount versions of Multimec® switches with a height up to 12.5 mm can also be delivered on tape/reel. Each reel contains 250/500 pcs.

Custom Products from Conception to Completion

mec are mastering all technologies for the design and manufacture of switches and accessories. The wide range of mec standard products is well known world wide, but also many custom solutions have been created. mec offer to be your partner from conception to completion. Our R/D engineers generate computer animated solutions, rapid prototypes and manage the whole industrialisation process.

We welcome any custom requirement.



- Navigation module
- Cap with concave surface
- Fluorescent legends
- Different actuation forces
- Reverse printed legend on translucent cap

- Quiet switches with and without tactile feeling
- Cap colours matched to customer's request
- Right angle switches with integrated illumination
- Customer specified ultra bright LED
- Ultra high temperature Cap

Please consult factory with your custom requirement.

SWITCHES

DISTRIBUTOR



MANUFACTURER

mec a/s

Industriparken 23
DK-2750 Ballerup
Denmark

Phone: (+45) 44 97 33 66
Fax: (+45) 44 68 15 14
E-mail: danmec@mec.dk
Web: www.mec.dk