


## **GENERAL SPECIFICATIONS:**

RATING: 15A / 125V AC CABLE TYPE / SIZE: TEMPERATURE RATING: 60° C CONDUCTOR COLORS: CABLE JACKET COLOR: BLACK OVERALL LENGTH (L): 2500 + 50 mm CABLE OUTER DIAMETER: 7.8 + 0.1 mm END 'A' TERMINATION: END 'B' TERMINATION: APPROVALS PLUG: BSMI APPROVALS CABLE: BSMI APPROVALS CONNECTOR: BSMI

VCTF 3x2.0mm<sup>2</sup> BLACK / WHITE / GREEN 5-15P, BSMI, YP-12 IEC 320 / C13, YC-12

## PACKING:

HANKING L = 230 + 10 mm MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.





## NOTES:

1. CORD. PLUG AND CONNECTOR MUST BE MARKED WITH  $\Delta PPROVAL SYMBOLS OR FILE NUMBER(S)$ 

AFFIXOVAL STMBOLS OKTILL NOMBLIK(S).			NO.	PART NO	REV.			DESCRIPTION	NOTES
$\mathbf{\mathfrak{S}}$			TABULATION BLOCK						
					.xx +/- 0.1 .xxx +/005		ANGULAR +/- 1*	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Nor Tel. 201-784-1000	
Contents of this document are subject to change without prior notice	Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applica- ble UL,CSA or EN Standards for proper installation instruction.	Globtek product are not authorized for use as mission critical components in life support, haz- ardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	INIT.BY: EM	DATE: 10/24/13	.xx +/	LIMETERS A xx +/- 0.3 xx +/013		DWG TITLE: TAIWAN DETACHABLE CORDSET, 2.5m, 5-15P TO IEC320/C13	
			DRAWN: NF	DATE: 10/24/13	FSCN G, CC		SIZE A	MODEL: N / A	REV. C1
			APRVD: HM	DATE: 10/24/13	SCAL	SCALE: NONE		PART NO: <b>3003322M5701(R)</b>	SHEET 1/2

DASH

## PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK,INC.

