

## **Technical Data Sheet**

## 8-Port RS-232 USB to Serial Adapter Data Control Box

**Model Number: USB-8COM** 







The USB-8COM USB Serial Adapter provides instant connectivity to RS-232 communication device for factory automation equipment, multi-drop data collection devices, barcode readers, time clocks, scales, data entry terminal and serial communication in harsh environment. The USB-8COM USB Serial Adapter Data Control Box is designed to make serial port expansion quick and simple.

## **Features**

- TAA Compliant.
- Rugged ABS plastic housing.
- Full RS-232 modem control signals and hardware.
- Software flow control: RTS/CTS, XON/XOFF.
- Baud rate up to 921.6K bps.
- 128 byte transmit FIFO & 384 byte receive FIFO.
- Non-standard baud rates supported
- Serial port protected with surge protection of 10KV.
- COM port number assigned can be changed to any COM port number required.
- Virtual COM port drivers provided for Windows 7, Vista, 2003, XP, 2000.
- Works with USB 1.1 & 2.0 host port.

## **Product Information**

- Model Number: USB-8COM
- Packing List:
  - o USB to Serial 8 Port RS-232 Adapter
  - o 3ft. USB-A male to USB-B male cable
  - Driver Disk
- Optional Accessories: N/A



| Specifications         |   |
|------------------------|---|
| Overview               |   |
| Interface              | USB to Serial   |
| Port Connections       | 8x DB-9 Male / 1USB Type-B Female   |
| USB Speed              | USB 1.0 / 1.1 compliant, USB 2.0 compatible   |
| Protocol               | RS-232  |
| Baud Rate              | up to 921.6K bps  |
| Available Power Modes  | USB Bus Powered, no external power adapter required   |
| Color                  | Silver  |
| Compliance             | TAA   |
| Physical Features      |   |
| Construction           | Rugged ABS Plastic  |
| Cable Length           | 3ft.  |
| Dimensions             | 5.43(L)x5.10(W)x1.56in(H)   |
| Weight                 | .531 lbs  |
| OS Support             | XP, 2000, 2003, CE, Vista, Windows 7, 8, Windows 10, Linux and Mac OS 10.X  |
| Current Certifications | CE, FCC, RoHS   |
| Signals                |   |
| RS-232 Data Signals    | TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND, RI  |
| Serial COM Parameters  |   |
| Parity                 | None, Even, Odd, Space, Mark  |
| Flow Control           | RTS/CTS, XON/XOFF   |
| FIFO                   | 128 byte transmit FIFO / 384 receive FIFO   |
| Environment            |   |
| Operating Temperature  | 0 to 55°C (32 to 131 °F)  |
| Operating Humidity     | 5 to 95% RH   |
| General Applications   |   |
| Applications           | Remote Access, Retail & Industrial Data Center, Modem, POS, Printer, BarCode Scanners, Time Clocks – Industrial serial RS-232 protocol applications |
| Product URL            |   |
| USB-8COM               | https://www.coolgear.com/product/8-port-rs-232-usb-to-serial-adapter-data-control-box   |
| product page           |   |

product page