



Section A-A



Section B-B



Section C-C

NOTES:

1. MATERIAL: PHOSPHOR BRONZE, t=0.12mm
2. APPLICABLE WIRE RANGE: SEE CONTACT INFORMATION
3. INSULATION O.D.: SEE CONTACT INFORMATION
4. USE WITH HOUSING: 10145492.
5. PRODUCT SPEC: GS-12-1444.
6. PACKAGING SPEC: GS-14-2616.
7. ORDERING CODE: 10145493-X X LF

- LEAD FREE
- CRIMP HEIGHT
0: STANDARD
1: LOW CRIMP HEIGHT
- FINISH:
1: TIN-PLATED OVER NICKEL
2: GOLD FLASH OVER NICKEL

CONTACT INFORMATION:

Part No.	Wire Range	Insulation O.D.	DIM.(mm)			
			A	B	C	D
10145493-X0LF	AWG#28~30	∅0.40~∅0.60mm	1.10	1.05	1.00	0.90
10145493-X1LF	AWG#32	∅0.30~∅0.40mm	1.00	0.85	0.90	0.70

mat'l. code		surface	tolerance	projection	product family
		ISO 1302 ✓	ISO 406 ISO 1101		MINITEK
ltr	ecn no	dr	date	tolerances unless otherwise specified	title
A		TONY	2017-09-13	angles linear	0.8MM CRIMP CONTACT
				0°±3'	mm
				.0±.30	scale 1:1
				.00±.20	
				.000±.10	
		dr	TONY LENG	2017-09-13	Amphenol FCI
		engr	TONY LENG	2017-09-13	dwg no
		chr	ZK HU	2017-09-13	sheet 1 of 1
		appd	TIM YAO	2017-09-13	size
					A3
sheet	revision	A			type
index	sheet	1			Product Customer Drawing