TECHNICAL DATA SHEET	Rosenberger
CRIMP INSERT	11W15A-5XX



Simplified view without mounting steel sheet and screw.

All dimensions are in mm; tolerances according to ISO 2768 m-H

Order-No.	*Cable type*	*a*	*b*	*c*	*d*	Weight (g/pce)
11W15A-502	RG 316 /U, RG 174 A/U, RG 188 A/U, RG 179 B/U, RG 187 A/U	3.30	1.20	1.5	3.0	64.8
11W15A-504	RG 180 B/U, 2YCY 0.4/2.5, RG 195 A/U, TZC 75024	4.30	1.10	1.5	4.5	64.2
11W15A-506	RG 141 A/U, RG 58 C/U, 2YCCY 0.4/2.5, 2Y(ms) CY 0.4/2.5	5.35	1.10	1.5	4.5	63.8
11W15A-508	RG 223 /U, RG 400 /U, RG 142 B/U	5.50	1.10	1.5	4.5	63.5

Tooling

Crimping tool 11W150-000

Packing

Standard 1 pce in bag

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date
J. Krautenbacher	19/10	Krautenbacher J.	19.07.12

Rev.	Engineering change number	Name	Date
c00	12-0002	J_Krautenb.	19.07.12

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel.: +49 8684 18-0
Fax: +49 8684 18-499
email: info@rosenberger.de