

## Differential current monitoring - RCM-A-SCT-210 - 2806100

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Differential current converter for type A differential current monitor.

### Product Features

- Residual current detection characteristics type A (50/60 Hz)
- Detects pulsating DC and AC residual currents
- Adjustable residual response current of 30 mA to 3 A
- Adjustable pre-alarm threshold and delay time
- Actual residual current can be read via LED display
- Remote signaling for main and pre-alarm
- Residual current monitoring devices act as a form of fire prevention

### Key commercial data

Packing unit	1 pc
Custom tariff number	85043180
Country of origin	Germany

### Technical data

#### Dimensions

Height	299 mm
Width	33 mm
Depth	284 mm
Diameter converter	210.00 mm
Outside diameter of cables max.	140.00 mm

#### Ambient conditions

Degree of protection	IP20 (terminal blocks)
	IP45 (housing)
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

# Differential current monitoring - RCM-A-SCT-210 - 2806100

## Technical data

### General

Housing material	Polycarbonate
Mounting type	Screw mounting

### Common characteristics

Rated current $I_n$	400 A
Rated response differential current $I_{dyn}$	3 A
Differential current acquisition characteristic	Type A (50 / 60 Hz)
Response differential current $I_{\Delta n}$	0.03 A ... 3 A
Thermal permanent differential current $I_{cth}$	$1.5 \times I_n$
Thermal rated short-time differential current $I_{th}$	$10 \times I_n$ (for 1 s)
Rated surge voltage resistance $U_{imp}$	8 kV
Surge voltage category	IV
Rated voltage $U_n$	690 V
Pollution degree	2
Max. overcurrent as regards the non-resolution	$6 \times I_n$
Rated differential short-circuit current $I_{\Delta c}$	10 kA
Rated surge differential current $I_{dyn}$	$25 \times I_n$

### Connections

Connection method	Screw terminal blocks
Number of connections	2
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Cable/line name	Converter supply line
Maximum cable length	10 m
Cross section	0.5 mm <sup>2</sup>
Cable type	LiY

### Standards and Regulations

Standards/specifications	DIN EN 62020
	VDE 0663
	DIN EN 60044-1
	VDE 0414

## Differential current monitoring - RCM-A-SCT-210 - 2806100

### Classifications

#### eCl@ss

eCl@ss 4.0	27210902
eCl@ss 4.1	27210902
eCl@ss 5.0	27210902
eCl@ss 5.1	27210902
eCl@ss 6.0	27210902
eCl@ss 7.0	27210902
eCl@ss 8.0	27210902

#### ETIM

ETIM 2.0	EC001505
ETIM 3.0	EC001505
ETIM 4.0	EC002048
ETIM 5.0	EC002048

#### UNSPSC

UNSPSC 6.01	30211501
UNSPSC 7.0901	39121019
UNSPSC 11	39121006
UNSPSC 12.01	39121006
UNSPSC 13.2	39121006

### Approvals

#### Approvals

---

##### Approvals

VDE Zeichengenehmigung

---

##### Ex Approvals

---

Approvals submitted

---

#### Approval details

## Differential current monitoring - RCM-A-SCT-210 - 2806100

### Approvals

