



PCB Layout(Top View)

N = Number of poles Δ
 Dim A = $N \times 6.35 + 1.0$
 Dim B = $(N - 1) \times 6.35$

Poles	Tol.	Dim A & B
2-5p		± 0.20
6-10p		± 0.25
11-16p		± 0.35
17-24p		± 0.40
25-30p		± 0.50

SIGN	DATE	DESCRIPTION	APPROVER
Δ	10/20'08	Add APPROVAL: : CQC	Kind
Δ	12/05'12	Change the screw plating specification	Jacky
Δ	12/05'12	Change the dimensional tolerance	Jacky
Δ	12/12'13	Add the view	Jacky
Δ	12/12'13	Change the withatand voltage and current	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL: cULus CQC
 RATED VOLTAGE & CURRENT: 250 V, 10 A / 250 V, 9 A $\Delta 5$
 WITHSTAND VOLTAGE: AC 2000 V/Min
 INSULATION RESISTANCE: 1000 M Ω OR MORE AT DC 500 V
 OPERATING TEMPERATURE RANG: -40 $^{\circ}$ C ~ +115 $^{\circ}$ C
 SCREW TORQUE VALUE: 5.3 Lb-In.
 WIRE RANGE: 22 - 18 AWG
 1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK
 2) TERMINAL: BRASS, 0.8t, Tin PLATED
 3) TERMINAL SCREWS: STEEL, M3
 APPROVAL: Δ
 PART NO.:
 Critical dimension: ∇

YK 222 xx 0 x x 00G

NO. OF POLES
 02: 2 POLES
 03: 3 POLES
 04: 4 POLES

30: 30 POLES

G: RoHS compliant (lead<4%) In copper Alloy
 MARK
 0: "@" MARK
 1: "ANY" MARK
 TERMINAL & SCREW PLATED
 0: TERMINAL & SCREW: G/F
 Δ 1: TERMINAL: G/F, SCREW: Zinc
 2: TERMINAL: Sn, SCREW: G/F
 Δ 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE	YK-222 Series			DWG NO.	8YK001-222		
PART NO.	YK222xx0xx00G			CUST NO.			
APPROVED	CHECKED	DESIGNED	DRAWN	Tolerance			
		Jacky 2013.12.12	Jacky 2013.12.12		UNIT: mm	X.	± 0.50
					SCALE: NONE	X.X	± 0.30
				SHEET: 01/01	REV.: G	X.XX	± 0.10
						X $^{\circ}$	$\pm 1^{\circ}$