



- NOTES:
1. MOUNTING HARDWARE SHIPPED UNASSEMBLED.
 2. RATED 15 AMP, 24 VOLT DC AT 105° C (CURRENT CARRY ONLY) WHEN USING 14 AWG STRANDED CONDUCTOR CABLE.
 3. IP68 RATED WHEN MATED TO S15KS SERIES PLUGS.
 4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					UNLESS OTHERWISE SPECIFIED			FINISH	
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL	
					- TWO PLACE DECIMALS ±0.02 [0.5]			SPEC No.	
					- THREE PLACE DECIMALS ±0.005 [0.13]			SCALE	
					FIRST USED ON			1.5:1	
					DATE DRAWN	BY	CHKD	APVD	Switchcraft®
					5-10-19	SRC	SRC	TJK	
					NAME			SHEET 1 OF 1	
					15 AMP JACK ASSEMBLY. RoHS			PART No.	
					DO NOT SCALE DRAWING			ST15S	
REVISIONS								REV	
								A	