



**Terminal Assignment**

Connector Pins	RS232/UART/USB**	RS422	RS485	Wireless	Wire Color
Pin 1	+Vin	+Vin	+Vin	+Vin	Brown
Pin 2	GND	GND	GND	GND	White
Pin 3	TX	TX+	D+	–	Blue
Pin 4	–	TX-	D-	–	Black
Pin 5	RX	RX+	D+	–	Gray
Pin 6	–	RX-	D-	–	Pink




Device:  
M 8 – 6-contact (female)

Cable:  
M 8 – 6-pin (male)



**Dimensional Drawing**



**Specifications**

Protection	IP 67
Material	Connector: brass / nickel Cable molded head: TPU Cable carrier: TPU or nylon Conductor insulation: PVC
Operational Temperature range <sup>†</sup>	-40°C to +85°C (-40°F to +185°F)
Connection	Cable gland Connector M8, 6-contact (male)

**Communication Cable Part Number <sup>‡</sup>**

<b>XXX</b>	<b>XX</b>	<b>-</b>	<b>X</b>	<b>-</b>	<b>X</b>	<b>-</b>	<b>CS</b>
		<b>Length</b>		<b>Interface</b>			
		1 meter		<u>G</u> <u>UART / RS232 / RS422 / RS485</u>			
		2 meter		<u>U</u> <u>USB</u>			
		3 meter		<u>W</u> <u>Wireless</u> <sup>§</sup>			
		4 meter (non-stock)					
		5 meter (non-stock)					
		6 meter (non-stock)					
		<u>10</u> meter (Only PSG)					
		<u>15</u> meter (non-stock)					
		<u>30</u> meter (non-stock)					
<b>Type</b>							
<u>PSG 6M</u>		<u>Straight</u>					
<u>PSW 6M</u>		<u>Right Angle</u>					

<sup>†</sup> Cable is a third party product with temperature tolerance from -40°C to +105°C (-40°F to +221°F).

<sup>‡</sup> Available options for this model are underlined.

<sup>§</sup> Wireless Module on device side has to be powered.

**Warranty:** This product has 18 months limited warranty. For more information, please visit: [www.CTiSensors.com/warranty](http://www.CTiSensors.com/warranty)

**CTI SENSOR, INC.**

30301 Emerald Valley Parkway, Unit B  
 Solon, OH 44139  
 Phone: (440) 264 - 2370  
 Email: [sales@CTiSensors.com](mailto:sales@CTiSensors.com)

All contents of this document are subject to change without any notice.

\*\* USB interface uses UART interface and a UART to USB driver.