

Relay connectors - ST-REL4-SW230/21-21 - 2825513

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Relay connector, equipped with Siemens KAMMRELAIS ®, contacts (Ag): medium loads, 2 PDT, input voltage 230 V AC, with light indicator, can be plugged onto basic termination blocks

The illustration shows version ST-REL 4-SG 48/21-21



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 077792 |
| Weight per Piece (excluding packing) | 67.94 GRM |
| Custom tariff number | 85364900 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 27 mm |
| Height | 33 mm |
| Depth | 66.5 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Coil side

| | |
|---|--------------------------|
| Nominal input voltage U_N | 230 V AC |
| Input voltage range in reference to U_N | 0.8 ... 1.06 |
| Typical input current at U_N | 7 mA |
| Typical response time | 4 ms ... 15 ms (with AC) |

Relay connectors - ST-REL4-SW230/21-21 - 2825513

Technical data

Coil side

| | |
|----------------------------|--------------------------|
| Typical release time range | 4 ms ... 15 ms (with AC) |
| Operating voltage display | Yes |

Contact side

| | |
|---------------------------------------|-----------------------|
| Contact type | Single contact, 2-PDT |
| Contact material | Ag, gold-flashed |
| Maximum switching voltage | 250 V AC/DC |
| Maximum inrush current | 5 A |
| Limiting continuous current | 5 A |
| Interrupting rating (ohmic load) max. | 120 W (at 24 V DC) |
| | 60 W (at 48 V DC) |
| | 50 W (at 60 V DC) |
| | 50 W (at 110 V DC) |
| | 70 W (at 220 V DC) |
| | 500 VA (for 250 V AC) |

General

| | |
|--|--|
| Test voltage relay winding/relay contact | 1 kV AC (50 Hz, 1 min.) |
| Test voltage PDT/PDT | 1 kV AC (50 Hz, 1 min.) |
| Operating mode | 100% operating factor |
| Mechanical service life | Approx. 10^7 cycles (approx. 10^6 with AC relay) |
| Standards/regulations | DIN VDE 0110b, Gr. C for 250 V DC |
| | DIN VDE 0160 (in relevant parts) |
| | DIN VDE 0110b, Gr. C for 250 V DC |
| | DIN VDE 0160 (in relevant parts) |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |
| eCl@ss 8.0 | 27371001 |

Relay connectors - ST-REL4-SW230/21-21 - 2825513

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000196 |
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC000196 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11 | 39121515 |
| UNSPSC 12.01 | 39121515 |
| UNSPSC 13.2 | 39121515 |

Approvals

Approvals


Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Relay connectors - ST-REL4-SW230/21-21 - 2825513

Circuit diagram

