



The Bluetooth® Intelligent Serial Module is specifically designed for applications where robust short range connectivity is required. This particular module provides a reliable Bluetooth connection that exceeds all requirements in terms of performance. The excellent range of up to 300 meters with very low power consumption of less than 36 mA makes this module a true class leader.

#### Key Features

- Best-in-class range provides open field connectivity in excess of 300 meters
- Integrated high-performance ceramic antenna
- Adaptive frequency hopping to cope with interference from other wireless products
- Optimised receive sensitivity to provide long range initial connections that largely eliminate connection hysteresis
- A full industrial operating temperature range of -40°C to +85°C
- Data transfer rate up to 300 kbps
- Fully approved product
- Class 1 version 2.0 Bluetooth
- Receive sensitivity better than -84 dBm
- Support for 128 bit encryption
- Non-discoverable modes
- 40 way Hirose connector
- 2 X 8 bit ADCs
- 9 X GPIO
- Low power modes
- Lead free
- 2 year warranty
- Supports Wi-Fi co-existence
- Embedded Bluetooth stack
- Integrated antenna with up to 300m range
- External antenna version available

As well as incorporating a fully approved embedded Bluetooth protocol stack, the module includes a comprehensive AT style interface that dramatically reduces the development time of applications from months to days.

#### global solutions: local support

USA: +1.800.492.2320  
Europe: +44.1628.858.940  
Asia: +852.2923.0610

wirelessinfo@lairdtech.com  
www.lairdtech.com/wireless

FEATURE	IMPLEMENTATION
Bluetooth®	Class 1
Frequency	2.402 – 2.480 GHz
Max Transmit Power	+6 dBm (internal antenna - TRBLU23-00200) +4 dBm (at u.fl connector - TRBLU-23-00300)
Min Transmit Power	-27 dBm
Low Power Sniff	2.5 mA typical
Receive Sensitivity	Better than -84dB
Range	300m (free space)
Serial Interface	3.3 V UART
GPIO	9 x digital GPIO
Serial Parameters	Default: 9600,n,8,1 From 1200 bps to 921.6 kbps DTR, DRS, RTS, CTS, DCD, RI DCE or DTE mode
Current Consumption	Idle mode = 13mA Connected as master = 20mA
Physical Size	25.0 x 35.0 x 7.6 mm, 8 g
Antenna	Internal – Multilayer Ceramic External – Connection via U.FL connector
Bluetooth Qualified	Bluetooth 2.0
Lead Free	RoHS Compliant
Temperature Range	-40°C to +85°C
Interface Levels	3.3 V
Audio	Supported
Multipoint	Supported
Field Upgrades	Over UART
ADC	2 x 8bit
Protocols	UART, AT command set, Multipoint
Data Transfer Rate	Up to 300 kbps

## Ordering Information

TRBLU23-00200	Bluetooth Serial Module with integrated antenna
TRBLU23-00300	Bluetooth Serial Module with U.FL connector for external antenna

The details contained within the document are subject to change. Download the product specification from [www.lairdtech.com/wireless](http://www.lairdtech.com/wireless) for the most current specification.