## 3 METERS LENGTH



Connector A 132116 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 142206 SMB Plug Right Angle Brass Gold + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|   |   | Connector A  | A  | Cable  |   |   | Connector B  |  |  |
|---|---|--|--|--|---|---|--|--|--|
|   | Part #:<br>Description:<br>Type:  | 132116<br>SMA Clamp JK R<br>SMA  | G58 LMR195 50O   | Part #:<br>Description:<br>Dielectric:   | RG-58<br>RG-58 - PE 0.196<br>PE                                   | Part #:<br>Description:<br>Type:  | 142206<br>SMB R/A PLUG RG<br>SMB   | 58 LMR195 50O  |  |
|   | Gender:<br>Gottact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Finish:<br>Max. Freq.:<br>Booting: | Jack<br>Straight<br>Solder<br>Standard<br>50 Ohm<br>Cable<br>Brass<br>Gold<br>None<br>Beryllium Copper<br>Gold<br>12.4 GHz<br>SMA Jack Straigh |  | Shielding:<br>Diameter:<br>Impedance:<br>Sheathing:<br>Testing:<br>Length:                             | Braid<br>0.196<br>50 Ohm<br>None<br>Continuity Hi-Pot<br>3 Meters | Gender:<br>Body Type:<br>Contact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Tinish:<br>Max. Freq.:<br>Booting: | Plug<br>Right Angle<br>Solder<br>Standard<br>50 Ohm<br>Cable<br>Brass<br>Gold<br>None<br>Beryllium Copper<br>Gold<br>4 GHz<br>SMB Plug Right Ang | gle  |  |
| Amphenol<br>CUSTOM CABLE<br>CONTROLLED DOCUMENT DO NOT CORV |   |  | THIS DRAWING MAY CONTAIN<br>PROPRIETARY INFORMATION A<br>FOR ANY PURPOSE DETRIMEN'<br>INC. IT MAY NOT BE REPRODU<br>IN ANY FORM WITHOUT THE W<br>CUSTOM CABLE INC. ACCEPTA<br>ESTABLISHES AND AGREEMEN | AND MUST NOT BE U<br>TAL TO CUSTOM CAI<br>CED OR TRANSCRIBI<br>/RITTEN CONSENT O<br>.NCE OF THIS DRAWI | BLE<br>ED<br>F<br>NG Part No:                                     | SMA-ST-JK/SMB-RA-PL RG58 3M   |  | UNLESS SPECIFIED<br>TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2%<br>ASSEMBLY:<br>CENTER LABEL IF LENGTH<br>IS LESS THAN 12 INCHES |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-2Z03U0008003M

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/SMB-RA-PL RG58 3M

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank