

PRODUCT VIDEO



QUICK START



USER GUIDE



REFERENCE SK-VIBRATION-AX-3D-10G

DESCRIPTION

This wireless IOT vibration starterkit includes everything you need to setup quickly your vibration monitoring application :

- Wireless Receiver/Gateway with LAN Output (Ref: BeanGateway® Indoor)
- Wireless Vibration sensor with standard base, measurement range $\pm 10g$ (ref: BeanDevice® 2.4GHZ AX-3D $\pm 10g$)
- Free software to collect and display in real-time data measurement from the vibration sensor (Ref: BeanScope® 2.4GHZ version)
- AC/DC Power Adapter (US or EUR or UK plugs) for charging the battery or to be used constantly

MAIN FEATURES

- Wireless vibration sensor (measurement range $\pm 10g$)
- Global License-free band 2.4GHz, with maximum radio range 650 meters
- Time-synchronized data acquisition ($\pm 2.5ms$ of accuracy)
- Low Noise vibration sensor ($100 \mu g/\sqrt{Hz}$)
- Waterproof IP67 aluminum casing (Nema 6)
- Rechargeable Lithium-Polymer battery 2200 mAh providing a battery life up to 15 months
- **Embedded data logger** : up to 1 million data points (with events dating)
- Excellent radio link with a maximum range of 650 meters

Beanair products are Made in Germany and are certified CE/FCC/Giteki

WEBLINKS TO PRODUCTS

- [Wireless vibration sensor](#)
- [Wireless Receiver/Gateway](#)
- [Eco-friendly Monitoring Software with Real-Time FFT](#)

HOW IT WORKS ?



CONTACT US

Headquarter:

BeanAir GmbH
Wolfener Straße 32 - 34
12681 Berlin

Email:

info@beanair.com

Phone number:

+49 30 98366680

