104130-1 - ACTIVE

AMP-LATCH

TE Internal #: 104130-1 Ribbon Cable Connectors, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Right Angle, Through Hole - Solder, 2 Row, Receptacle, Low Profile

View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors



Connector System: Board-to-Board

Number of Positions: 10

Centerline (Pitch): 2.54 mm [.1 in]

PCB Mount Retention: Without

PCB Mount Orientation: Right Angle

Features

TE

Product Type Features

Ribbon Cable Connector Header Type	Pin Header	
Connector Product Type	Connector Assembly	
Connector System	Board-to-Board	
Connector & Housing Type	Receptacle	
Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Number of Positions	10	
PCB Mount Orientation	Right Angle	
Number of Rows	2	
Electrical Characteristics		
Insulation Resistance	5000 MΩ	
Body Features		
Daisy Chain	With	
Primary Product Color	Black	

C For support call+1 800 522 6752

Ribbon Cable Connectors, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Right Angle, Through Hole - Solder, 2 Row, Receptacle, Low Profile



Connector Profile	Low	
Contact Features		
Mating Square Post Dimension	.64 mm[.025 in]	
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]	
Contact Type	Pin	
	30 µin	
Contact Mating Area Plating Material	Gold, Gold Flash, Gold Flash over Palladium Nickel	
Contact Shape & Form	Square	
Contact Underplating Material	Nickel	
PCB Contact Termination Area Plating Material	Tin-Lead	
Contact Base Material	Copper Alloy	
Contact Current Rating (Max)	1 A	
ermination Features		
Square Termination Post & Tail Dimension	.64 mm[.025 in]	
Termination Post & Tail Length	3.43 mm[.135 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	

Mechanical Attachment

Mating Alignment	With	
PCB Mount Alignment	Without	
Panel Mount Feature	Without	
PCB Mount Retention	Without	
Mating Alignment Type	Center, Dual Polarizing Bar	
Mating Retention	With	
Mating Retention Type	Ejection Latch	
Connector Mounting Type	Board Mount	
Housing Features		
Housing Material	Thermoplastic	
Centerline (Pitch)	2.54 mm[.1 in]	
Dimensions		
Dimensions Shrouded End Dimension	3.81 mm[.15 in]	
	3.81 mm[.15 in] 10.16 mm[.8 in]	

C For support call+1 800 522 6752

08/08/2023 12:58AM | Page 2

Ribbon Cable Connectors, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Right Angle, Through Hole - Solder, 2 Row, Receptacle, Low Profile



Connector Height	9.77 mm[.38 in]	
Row-to-Row Spacing	2.54 mm[.1 in]	
Usage Conditions		
Housing Temperature Rating	Standard	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]	
Operation/Application		
Solder Process Feature	Solder Dipped	
Circuit Application	Signal	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Packaging Features		
Packaging Quantity	120	
Packaging Method	Tray	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

Not Compliant

EU ELV Directive 2000/53/EC	Compliant with Exemptions	
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (13% in Component Part) Aticle Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.	
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.	
Solder Process Capability	Not lead free process capable	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous

Ribbon Cable Connectors, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Right Angle, Through Hole - Solder, 2 Row, Receptacle, Low Profile



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



TTE			ETE
TE Part #1-640388-5	TE Part #6368011-3	TE Part #2-406549-1	TE Part #103908-9
15P MTA156 HDR ASSY RN STR F/L	STK MJ,2X1,SHLD,I135,G/Y/G/Y L	IMJ,1X1,PNL GRD,LED(G/Y), SN	10 MTE HDR SRST LATCH W/HLDWN



Documents

Product Drawings 010 LOPRO HDR RA 30DP LATCH

Ribbon Cable Connectors, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Right Angle, Through Hole - Solder, 2 Row, Receptacle, Low Profile



English **CAD** Files 3D PDF 3D **Customer View Model** ENG_CVM_CVM_104130-1_H.2d_dxf.zip English **Customer View Model** ENG_CVM_CVM_104130-1_H.3d_igs.zip English **Customer View Model** ENG_CVM_CVM_104130-1_H.3d_stp.zip English By downloading the CAD file I accept and agree to the Terms and Conditions of use **Product Specifications Product Specification** English **Product Environmental Compliance** MD_104130-1_06222016843_dmtec

English

MD_104130-1_06222016843_dmtec

English

Agency Approvals Agency Approval Document

English