

DEVICE TYPE NO.	POLARITY	P _D @ T _C =25°C	MAXIMUM RATINGS				ELECTRICAL CHARACTERISTICS				CASE
		WATTS	I _C AMPS	BV _{CEO}	BV _{CE}	BV _{EB0}	h _{FE} MIN.	I _C AMPS	V _{CE}	f MHZ *KHZ	
BUX17	NPN	150	10.0	250	150	6	20	4.00	3	2.5	T03
BUX17A	NPN	150	10.0	350	250	6	20	4.00	3	2.5	T03
BUX17B	NPN	150	10.0	400	300	6	15	4.00	3	2.5	T03
BUX17C	NPN	150	10.0	450	350	6	15	4.00	3	2.5	T03
BUX18	NPN	120	8.00	300	200	6	7	6.00	3	2	T03
BUX18A	NPN	120	8.00	450	275	6	7	5.00	3	2	T03
BUX18B	NPN	120	8.00	600	325	6	10	4.00	3	2	T03
BUX18C	NPN	120	8.00	750	375	6	10	4.00	3	2	T03
BUX20	NPN	350	50.0	160	125	7	20	25.0	2	8	T03 MOD
BUX21	NPN	350	40.0	250	200	7	20	12.0	2	8	T03 MOD
BUX31	NPN	150	8.00	800	400	8	8	4.00	3	15	T03
BUX31A	NPN	150	8.00	900	450	8	8	4.00	3	15	T03
BUX32	NPN	150	8.00	800	400	8	8	6.00	3	15	T03
BUX32A	NPN	150	8.00	900	450	8	8	6.00	3	15	T03
BUX37	NPN	52.0	15.0	400	400	7	20	15.0	5	2	T03
BUX39	NPN	120	30.0	90	120	7	8	20.0	4	8	T03
BUX40A	NPN	120	20.0	160	125	7	8	15.0	4	8	T03
BUX41	NPN	120	15.0	250	200	7	8	8.00	4	8	T03
BUX41N	NPN	120	18.0	220	160	7	8	12.0	4	8	T03
BUX42	NPN	120	12.0	300	250	7	8	6.00	4	8	T03
BUX43	NPN	120	10.0	400	325	7	8	5.00	4	8	T03
BUX44	NPN	120	8.00	450	400	7	8	4.00	4	8	T03
BUX45	NPN	120	5.00	500	500	7	8	2.00	4	8	T03
BUX47	NPN	107	8.50	850	400	7	5	6.00	1.5	4	T03
BUX48	NPN	175	15.0	850	400	7	5	15.0	5	4	T03
BUX69A	NPN	100	10.0	1000	400	8	15	2.50	10	4	T03
BUX69B	NPN	100	10.0	800	325	8	15	2.50	10	4	T03
BUX69C	NPN	100	10.0	500	200	8	15	2.50	10	4	T03
MJ410	NPN	125	5.00	200	200	5	30	1.00	5	2.5	T03
MJ411	NPN	125	5.00	300	300	5	30	1.00	5	2.5	T03
MJ413	NPN	125	10.0	400	325	5	15	1.00	5	2.5	T03
MJ423	NPN	125	10.0	400	325	5	10	2.50	5	2.5	T03
MJ431	NPN	125	10.0	400	325	5	10	3.50	5	2.5	T03
MJ802	NPN	200	30.0	100	90	4	25	7.50	2	2	T03
MJ900	PNP	90.0	8.00	60	60	5	1000	3.00	3	4	T03
MJ901	PNP	90.0	8.00	80	80	5	1000	3.00	3	4	T03
MJ1000	NPN	90.0	8.00	60	60	5	1000	3.00	3	4	T03
MJ1001	NPN	90.0	8.00	80	80	5	1000	3.00	3	4	T03
MJ2500	PNP	150	10.0	60	60	5	1000	5.00	3	4	T03
MJ2501	PNP	150	10.0	80	80	5	1000	5.00	3	4	T03
MJ2955	PNP	115	15.0	100	60	7	20	4.00	4	2.5	T03
MJ3000	NPN	150	10.0	60	60	5	1000	5.00	3	4	T03
MJ3001	NPN	150	10.0	80	80	5	1000	5.00	3	4	T03
MJ3040	NPN	175	10.0	400	100	8	100	2.50	5	2	T03
MJ3041	NPN	175	10.0	400	300	8	250	2.50	5	2	T03
MJ3042	NPN	175	10.0	500	350	8	250	2.50	5	2	T03
MJ4030	PNP	150	16.0	60	60	5	1000	10.0	3	4	T03
MJ4031	PNP	150	16.0	80	80	5	1000	10.0	3	4	T03
MJ4032	PNP	150	16.0	100	100	5	1000	10.0	3	4	T03
MJ4033	NPN	150	16.0	60	60	5	1000	10.0	3	4	T03
MJ4034	NPN	150	16.0	80	80	5	1000	10.0	3	4	T03
MJ4035	NPN	150	16.0	100	100	5	1000	10.0	3	4	T03
MJ4502	PNP	200	30.0	100	90	4	25	7.50	2	2	T03
MJ8500	NPN	125	2.50	1200	700	8	7.5	0.50	5	2	T03
MJ8501	NPN	125	2.50	1400	800	8	7.5	0.50	5	2	T03
MJ8502	NPN	150	5.00	1200	700	8	7.5	1.00	5	2	T03
MJ8503	NPN	150	5.00	1400	800	8	7.5	1.00	5	2	T03
MJ8504	NPN	175	10.0	1200	700	8	7.5	1.50	5	2	T03
MJ8505	NPN	175	10.0	1400	800	8	7.5	1.50	5	2	T03
MJ10000	NPN	175	20.0	450	350	8	40	10.0	5	10	T03
MJ10001	NPN	175	20.0	500	400	8	40	10.0	5	10	T03
MJ10002	NPN	150	10.0	450	500	8	30	5.00	5	10	T03
MJ10003	NPN	150	10.0	350	400	8	30	5.00	5	10	T03
MJ10004	NPN	175	20.0	450	350	8	40	10.0	5	10	T03