



TECHNICAL

LISTED: UL & CSA
 RATED SUPPLY VOLTAGE: 120/240VAC
 RATED CURRENT: UP TO 30 AMPS
 RESET TYPE: AUTOMATIC OR MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 5mA +/- 1mA
 OVERLOAD CURRENT: 180 AMPS, 0.45PF
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 ENCLOSURE: NEMA 4X/6P

MATERIAL NUMBER	PART NUMBER	LENGTH "L"	LENGTH "A"	POWER-UP	RATED VOLTAGE
1301530261	30051-0A	2 FT 9.4 IN	1 FT	AUTO	120VAC
1301530262	30051-0M	2 FT 9.4 IN	1 FT	MANUAL	120VAC
1301530181	30053-0A	2 FT 9.4 IN	1 FT	AUTO	240VAC
1301530182	30053-0M	2 FT 9.4 IN	1 FT	MANUAL	240VAC

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FP = 0	DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATION TO ECTR/NX		
	INCH	NTS			
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 670716		
	4 PLACES	±	MM	INCH	DRWN: PPURSUTANDEL 2021/05/26
	3 PLACES	±	± 0.005		CHK'D: DNGUYEN62 2021/08/05
	2 PLACES	±	0.13	± 0.01	APPR: HKNEELAND 2021/08/06
	1 PLACE	±	0.25	± 0.02	INITIAL REVISION:
	0 PLACES	±			DRWN: HRUIZ01 2013/02/11
	ANGULAR TOL	±	0.5 °		APPR: JFMURPHY 2014/08/02
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES
		C-SIZE		130153	

molex

GFCI 30A, 120/240VAC INLINE FLYING LEADS

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
SD-130153-035	PSD	001	B1

MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
SEE TABLE	GNEERAL MARKET	1 OF 1