



21.5" Slim Line Touch Monitor

Effortless Multi-Touch Experience

Projected Capacitive touch technology provides a smooth, effortless multi-touch experience—identical to many of your favorite mobile touch devices.

Greater Durability

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

Sophisticated Bezel-Free Design

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

Display Details

TPK Model #	K21A-0311
LCD Size /Type	21.5" TFT - Active Matrix
Active Area	476.1 H x 267.8 V mm
Backlight	WLED
Aspect Ratio	16:9
Native Resolution	1920 x 1080
Display Colors	16.7 M (6 bits + A-FRC)
Pixel Pitch	0.248 H x 0.248 V mm
Brightness (typ)	225 cd/m ²
Contrast Ratio	1000:1
Hor. Viewing Angle	178°
Vert. Viewing Angle	178°
Response Time	14 ms

Touch Details

Touch Technology	Projected Capacitive
Multi-Touch Input	10 points
Input Method	Finger, Thin Glove
Touch Interface	USB-Type B
Multi-Touch OS Support	Windows 7/8/10 & Linux - Native HID
Single-Touch OS Support	All Windows, Linux & Mac OSX

Dimensions and Weight

Display (WxHxD)	517.4 x 313.3 x 46.0 mm
Display Weight	5.6 Kg
Shipping Weight	7.8 Kg

Product Details

Power Supply	12V DC, 4.16A
Power Consumption	Operating: 27 W Sleep: 2 W Off: 1 W
Video Input	Analog VGA, DVI-D
Audio Input	None
Mounting Options	VESA Mount, Included Side Mounting Brackets
VESA Pattern	100 x 100 mm
Operating Conditions	0°C to +40°C, Noncondensing 80%
Storage Conditions	-20°C to +60°C, Noncondensing 90%
Agency Approvals	TUV, CE, UL, CUL, FCC-B, RoHS
Warranty	3 year

The information presented in this specification sheet is intended as general information about TPK America, LLC products and is subject to change. Product specifications and warranties will be governed by TPK America, LLC standard terms and conditions of sale. Products are subject to availability. 100417R1