




UNIT:mm



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 10M Ohm(min)
 4. dielectric test: DC 300V



NO.	TIE	Q'TY	NAME	SPECIFICATION
⑥	1	1	BLACK L=80mm	
⑤	1/10		CLEAR SIZE: 280*330*0.05mm PRINT BLACK*MADE IN CHINA*+10PCS*及印生产周期,有透气孔.	
④	1	1	CLEAR SIZE: 130*230*0.05mm PRINT BLACK*MADE IN CHINA*+1PC*及印生产周期,有透气孔.	
③	12g		BLACK PVC-40P (MOULD NO:MM-116)	
②	1	1	USB2.0 UL2725 [28AWG(7/0.12TC+AL)*1P+28AWG(7/0.12TC)*2C]+AEB(48B TC) JACKET:BLACK OD:3.5mm L=3000±10mm	
①	2	2	MICRO USB 5P B/M SOLDER TYPE SHELL:NICKEL PIN:G/F INSULATOR COLOR:BLACK	

CNC Tech, LLC
 Industrial Cable and Connector Technology

DRAWN	ZHONGHS	DRAWING NO	
CHECKED		CUSTOMER	
APPROVAL		ITEM NO.	102-1082-BL-00300
DECIDED		DATE	2012-02-16
VERSIONS/EDITION	A/0	PROJECTION	