### S20KAC-P03MJG0-300S

series\_k, type\_s2



#### **General information**

| Part number       | S20KAC-P03MJG0-300S |            |
|-------------------|---------------------|------------|
| Termination       | solder              |            |
| Size              | 0                   | C IIII C A |
| Locking principle | push                | C ARRES E  |
| Coding            | a_key               |            |
| Cable Diameter    | cable_mini_30       |            |
| Cable outlet      | bend_relief         |            |





| • | ≈32 mm |   | •          |
|---|--------|---|------------|
|   | [XXX]  |   | 1 mu<br>ti |
|   | TAAAT  |   | jā,        |
| - | =25 mm | - |            |

# Contact insert description

| Number of contacts   | 3      |
|----------------------|--------|
| Contact type         | pins   |
| Contact diameter     | 09mm   |
| Insulator material   | peek   |
| Wire cross section   | 22_awg |
| Termination          | solder |
| Termination diameter | 085mm  |

reverse\_gender\_on\_request

#### **Technical information**

| Max. creepage and air clearance distance | 08_mm    | 08_mm         |
|--|----------|---------------|
| Nominal current single contact           | 075_a    | iec_60512_5_2 |
| Nominal current insert                   | 7,5 A    | vde_0298_4    |
| Test voltage                             | 12_kv_ac | sae_13441     |
| safety_text                              |          |               |

## Mechanical and environmental data

| Degree of protection* | ip68     |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles         | 5000     |

mated

#### Material and surface treatments

| Housing | m_chrome      |
|---------|---------------|
| Contact | cu_alloy_gold |

safety\_text\_2 ul\_text illustrative\_text