



- NOTES:**
- MATERIALS:**
 HOOD, GLAND, COMPR.-RING: ABS UL94 V-0 METALLIZED
 FRONTSEALING: SILICONE VMQ BLUE
 CABLE SEALING: NBR BLACK
 JACK-SCREW: STAINLESS STEEL
 O-RING: NBR BLACK
 CABLE STRAIN RELIEF: STEEL, NI-PLATED
 SCREWS: STEEL, NI-PLATED
 SHIELDING BRACKET: CU-ALLOY, NI-PLATED
 - TEMPERATURE RANGE: -30°C TO +80°C
 - RECOMMENDED TORQUE FOR SCREW:
 35Ncm (3.1 in.LB)
 MAX. TORQUE: 68Ncm (6 in.LB)
 - SINGLE PACKED

* COMPLETELY TIGHTENED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale:	1,5:1 (1:1)	
					dim. in mm	material:	SEE NOTES	
				date	name	title:		
				drawn	07.02.2014	Heinrich	WATER RESISTANT D-SUB HOOD	
				appd.	07.02.2014	Huether	SHIELDED 37 POS.	
			norm			JACKSCREW 4-40UNC STAINLESS STEEL		
			d-old	15K1A1154		dwg no:		
1 x b	Ä 5092	12.03.14	Heinrich				DIN-A3	
a	Origin						15K1A1441	sh: 1
rev.	description	date	name			part no:	15-004790	