

## EMIPAK 1B PressFit Power Module 600 V Double PFC MOSFET, 25 A



EMIPAK 1B  
(package example)



RoHS  
COMPLIANT

### FEATURES

- E series Power MOSFET
- MOAT and SiC diode technology
- Exposed Al<sub>2</sub>O<sub>3</sub> substrate with low thermal resistance
- Low input capacitance
- Low switching and conduction losses
- Ultra low gate charge Q<sub>g</sub>
- Low internal inductances
- Qualified using AQG324 guideline as reference
- PressFit pins locking technology  
PATENT(S): [www.vishay.com/patents](http://www.vishay.com/patents)
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

### DESCRIPTION

The EMIPAK 1B package is easy to use thanks to the PressFit pins. The exposed substrate provides improved thermal performance.

The optimized layout also helps to minimize stray parameters, allowing for better EMI performance.

PRIMARY CHARACTERISTICS	
<b>Q1 - Q4 MOSFET</b>	
V <sub>DSS</sub>	600 V
R <sub>DS(on)</sub> typical at I <sub>C</sub> = 25 A	59 mΩ
I <sub>D</sub> at T <sub>SINK</sub> = 37 °C	25 A
<b>Da1 - Da2 DIODE</b>	
V <sub>RRM</sub>	1200 V
V <sub>FM</sub> typical at 20 A	1.29 V
I <sub>F</sub> at T <sub>SINK</sub> = 83 °C	20 A
<b>D1 - D4 SILICON CARBIDE CLAMP DIODE</b>	
V <sub>RRM</sub>	600 V
V <sub>FM</sub> typical at 10 A	1.72 V
I <sub>F</sub> at T <sub>SINK</sub> = 62 °C	10 A
Package	EMIPAK 1B
Circuit configuration	Double interleaved bridgless PFC (4 x channels) with individual return diodes
Type	Modules - MOSFET

ABSOLUTE MAXIMUM RATINGS (T <sub>J</sub> = 25 °C unless otherwise noted)				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Operating junction temperature	T <sub>J</sub>		150	°C
Storage temperature range	T <sub>Stg</sub>		-40 to +150	
RMS isolation voltage	V <sub>ISOL</sub>	T <sub>J</sub> = 25 °C, all terminals shorted, f = 50 Hz, t = 1 s	3500	V
<b>Q1 - Q4 MOSFET</b>				
Drain to source voltage	V <sub>DSS</sub>		600	V
Gate to source voltage	V <sub>GS</sub>		± 20	
Pulsed drain current	I <sub>DM</sub>	V <sub>GS</sub> = 10 V	85	A
Continuous drain current	I <sub>D</sub>	T <sub>SINK</sub> = 25 °C	26	A
		T <sub>SINK</sub> = 80 °C	20	
Power dissipation	P <sub>D</sub>	T <sub>SINK</sub> = 25 °C	104	W
		T <sub>SINK</sub> = 80 °C	58	
Single pulse avalanche energy	E <sub>AS</sub>	L = 10 mH, I <sub>AS</sub> = 19 A, T <sub>J</sub> = 25 °C	1800	mJ
Pulsed source current (body diode)	I <sub>SM</sub>		85	A

PATENT(S): [www.vishay.com/patents](http://www.vishay.com/patents)

This Vishay product is protected by one or more United States and international patents.



<b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise noted)				
<b>DA1 - DA2 DIODE</b>				
Cathode to anode voltage	$V_{RRM}$		1200	V
Single pulse forward current	$I_{FSM}$		230	A
Diode continuous forward current	$I_F$	$T_{SINK} = 25\text{ }^\circ\text{C}$	29	A
		$T_{SINK} = 80\text{ }^\circ\text{C}$	21	
Power dissipation	$P_D$	$T_{SINK} = 25\text{ }^\circ\text{C}$	70	W
		$T_{SINK} = 80\text{ }^\circ\text{C}$	39	
<b>D1 - D4 SILICON CARBIDE CLAMP DIODE</b>				
Cathode to anode voltage	$V_{RRM}$		600	V
Single pulse forward current	$I_{FSM}$	10 ms sine or 6 ms rectangular pulse, $T_J = 25\text{ }^\circ\text{C}$	80	A
Diode continuous forward current	$I_F$	$T_{SINK} = 25\text{ }^\circ\text{C}$	12	A
		$T_{SINK} = 80\text{ }^\circ\text{C}$	9	
Power dissipation	$P_D$	$T_{SINK} = 25\text{ }^\circ\text{C}$	38	W
		$T_{SINK} = 80\text{ }^\circ\text{C}$	21	

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise noted)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
<b>Q1 - Q4 MOSFET</b>						
Drain to source breakdown voltage	$BV_{DSS}$	$V_{GS} = 0\text{ V}, I_D = 500\text{ }\mu\text{A}$	600	-	-	m $\Omega$
Drain to source on resistance	$R_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 25\text{ A}$	-	59	71	
		$V_{GS} = 10\text{ V}, I_D = 25\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	140	-	
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	1.8	2.6	4.4	V
Temperature coefficient of threshold voltage	$\Delta V_{GS(th)}/\Delta T_J$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$ (25 $^\circ\text{C}$ to 125 $^\circ\text{C}$ )	-	-9.7	-	mV/ $^\circ\text{C}$
Forward transconductance	$g_{fs}$	$V_{DS} = 20\text{ V}, I_D = 25\text{ A}$	-	29	-	S
Transfer characteristics	$V_{GS}$	$V_{DS} = 20\text{ V}, I_D = 25\text{ A}$	-	5.1	-	V
Zero gate voltage drain current	$I_{DSS}$	$V_{GS} = 0\text{ V}, V_{DS} = 600\text{ V}$	-	0.3	5	$\mu\text{A}$
		$V_{GS} = 0\text{ V}, V_{DS} = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	19	-	
Gate to source leakage current	$I_{GSS}$	$V_{GS} = \pm 20\text{ V}, V_{DS} = 0\text{ V}$	-	-	$\pm 150$	nA
<b>Q1 - Q4 BODY DIODE</b>						
Source-to-drain voltage drop	$V_{SD}$	$I_{SD} = 25\text{ A}, V_{GS} = 0\text{ V}$	-	0.9	1.32	V
<b>Da1 - Da2 DIODE</b>						
Forward voltage drop	$V_{FM}$	$I_F = 20\text{ A}$	-	1.29	1.90	V
		$I_F = 20\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.26	-	
Breakdown voltage	$V_{BR}$	$I_R = 500\text{ }\mu\text{A}$	1200	-	-	V
Reverse leakage current	$I_{RM}$	$V_R = 1200\text{ V}$	-	1.0	100	$\mu\text{A}$
		$V_R = 1200\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	900	-	
<b>D1 - D4 SILICON CARBIDE CLAMP DIODE</b>						
Forward voltage drop	$V_{FM}$	$I_F = 10\text{ A}$	-	1.72	1.98	V
		$I_F = 10\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	2.21	-	
Breakdown voltage	$V_{BR}$	$I_R = 500\text{ }\mu\text{A}$	600	-	-	V
Reverse leakage current	$I_{RM}$	$V_R = 600\text{ V}$	-	0.2	100	$\mu\text{A}$
		$V_R = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	1.4	-	



<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise noted)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
<b>Q1 - Q4 MOSFET WITH D1 - D4 CLAMP DIODE</b>						
Total gate charge (turn-on)	$Q_g$	$I_D = 24\text{ A}$ $V_{DS} = 480\text{ V}$ $V_{GS} = 10\text{ V}$	-	147	-	nC
Gate to source charge (turn-on)	$Q_{gs}$		-	36	-	
Gate to drain charge (turn-on)	$Q_{gd}$		-	60	-	
Turn-on delay time	$t_{d(on)}$	$I_D = 25\text{ A}$ $V_{DD} = 300\text{ V}$ $V_{GS} = 10\text{ V}$ $R_g = 4.7\text{ }\Omega$ , $L = 500\text{ }\mu\text{H}$	-	82	-	ns
Rise time	$t_r$		-	23	-	
Turn-off delay time	$t_{d(off)}$		-	109	-	
Fall time	$t_f$		-	9	-	
Turn-on delay time	$t_{d(on)}$	$I_D = 25\text{ A}$ $V_{DD} = 300\text{ V}$ $V_{GS} = 10\text{ V}$ $R_g = 4.7\text{ }\Omega$ , $L = 500\text{ }\mu\text{H}$ , $T_J = 125\text{ }^\circ\text{C}$	-	83	-	ns
Rise time	$t_r$		-	26	-	
Turn-off delay time	$t_{d(off)}$		-	111	-	
Fall time	$t_f$		-	22	-	
Input capacitance	$C_{iss}$	$V_{GS} = 0\text{ V}$ $V_{DS} = 100\text{ V}$ $f = 1\text{ MHz}$	-	4810	-	pF
Output capacitance	$C_{oss}$		-	230	-	
Reverse transfer capacitance	$C_{rss}$		-	5	-	
Reverse bias safe operating area	RBSOA	$T_J = 150\text{ }^\circ\text{C}$ , $I_D = 50\text{ A}$ , $V_{DD} = 400\text{ V}$ , $V_P = 600\text{ V}$ , $R_g = 4.7\text{ }\Omega$ , $V_{GS} = +10 / 0\text{ V}$				
<b>Q1 - Q4 BODY DIODE</b>						
Diode reverse recovery time	$t_{rr}$	$V_R = 30\text{ V}$ , $T_J = 25\text{ }^\circ\text{C}$ $I_S = 30\text{ A}$ $di/dt = 100\text{ A}/\mu\text{s}$	-	500	-	ns
Diode reverse recovery current	$I_{rr}$		-	41	-	A
Diode reverse recovery charge	$Q_{rr}$		-	10.5	-	$\mu\text{C}$
<b>D1 - D4 SILICON CARBIDE CLAMP DIODE</b>						
Total capacitive charge	$Q_C$	$V_R = 600\text{ V}$ $I_F = 10\text{ A}$ $di/dt = 500\text{ A}/\mu\text{s}$	-	30	-	nC

<b>INTERNAL NTC - THERMISTOR SPECIFICATIONS</b>				
PARAMETER	SYMBOL	TEST CONDITIONS	VALUE	UNITS
Resistance	$R_{25}$	$T_C = 25\text{ }^\circ\text{C}$	5000	$\Omega$
	$R_{100}$	$T_C = 100\text{ }^\circ\text{C}$	$493 \pm 5\%$	
B-value	$B_{25/50}$	$R_2 = R_{25} \exp. [B_{25/50}(1/T_2 - 1/(298.15\text{K}))]$	$3375 \pm 5\%$	K
Maximum operating temperature			220	$^\circ\text{C}$
Dissipation constant			2	$\text{mW}/^\circ\text{C}$
Thermal time constant			8	s

<b>THERMAL AND MECHANICAL SPECIFICATIONS</b>					
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS
Q1 - Q4 MOSFET - Junction to sink thermal resistance (per switch) <sup>(1)</sup>	$R_{thJS}$	-	1.00	-	$^\circ\text{C}/\text{W}$
Da1 - Da2 DIODE - Junction to sink thermal resistance (per diode) <sup>(1)</sup>		-	1.48	-	
D1 - D4 SILICON CARBIDE DIODE - Junction to sink thermal resistance (per diode) <sup>(1)</sup>		-	2.76	-	
Case to sink thermal resistance (per module) <sup>(1)</sup>		-	0.1	-	
Mounting torque (M4)		2	-	3	Nm
Weight		-	28	-	g

**Note**

<sup>(1)</sup> Mounting surface flat, smooth, and greased,  $\lambda_{grease} = 0.67\text{ W}/\text{mK}$




Fig. 1 - Maximum Continuous Drain Current vs. Sink Temperature




Fig. 4 - Typical Drain-to-Source On-Resistance vs. Temperature




Fig. 2 - Typical Drain to Source Current Output Characteristics at  $T_J = 25\text{ }^\circ\text{C}$




Fig. 5 - Typical Transfer Characteristics




Fig. 3 - Typical Drain to Source Current Output Characteristics at  $T_J = 125\text{ }^\circ\text{C}$




Fig. 6 - Typical Gate Threshold Voltage Characteristics




Fig. 7 - Typical Drain-State Resistance vs. Gate-to-Source Voltage




Fig. 10 - Typical Turn-off Switching Time vs.  $I_D$   
 $V_{DD} = 300\text{ V}$ ,  $R_g = 4.7\ \Omega$ ,  $V_{GS} = \pm 10\text{ V}$ ,  $L = 500\ \mu\text{H}$




Fig. 8 - Typical Body Diode Source-to-Drain Current Characteristics




Fig. 11 - Typical Turn-on Switching Time vs.  $I_D$   
 $V_{DD} = 300\text{ V}$ ,  $R_g = 4.7\ \Omega$ ,  $V_{GS} = \pm 10\text{ V}$ ,  $L = 500\ \mu\text{H}$




Fig. 9 - Typical Zero Gate Voltage Drain Current




Fig. 12 - Power Dissipation Curve




Fig. 13 - Safe Operating Area




Fig. 16 - Maximum Da1-Da2 Diode Continuous Forward Current vs. Sink Temperature




Fig. 14 - Reverse BIAS SOA




Fig. 17 - Typical Da1-Da2 Diode Reverse Leakage Current




Fig. 15 - Typical Da1-Da2 Diode Forward Characteristics




Fig. 18 - Typical D1-D4 Clamp Diode Forward Characteristics




Fig. 19 - Maximum D1-D4 Clamp Diode Continuous Forward Current vs. Sink Temperature




Fig. 20 - Typical D1-D4 Clamp Diode Reverse Leakage Current




Fig. 21 - Maximum Thermal Impedance  $Z_{thJS}$  Characteristics - (Q1-Q4 MOSFET)




Fig. 22 - Maximum Thermal Impedance  $Z_{thJS}$  Characteristics - (Da1-Da2 Diode)




Fig. 23 - Maximum Thermal Impedance  $Z_{thJS}$  Characteristics - (D1-D4 Clamp Diode)

**ORDERING INFORMATION TABLE**

Device code	<b>VS-</b>	<b>EN</b>	<b>Z</b>	<b>025</b>	<b>C</b>	<b>60</b>	<b>N</b>
	①	②	③	④	⑤	⑥	⑦


- 1** - Vishay Semiconductors product
- 2** - Package indicator (EN = EMIPAK 1B)
- 3** - Circuit configuration (Z = Double interleaved bridgless PFC (4 x channels) with individual return diodes)
- 4** - Current rating (025 = 25 A)
- 5** - Switch die technology (C = PowerMOS)
- 6** - Voltage rating (60 = 600 V)
- 7** - Diode die technology





CIRCUIT CONFIGURATION		
CIRCUIT	CIRCUIT CONFIGURATION CODE	CIRCUIT DRAWING
Double interleaved bridgless PFC (4 x channels) with individual return diodes	Z	

**PACKAGE**




LINKS TO RELATED DOCUMENTS	
Dimensions	<a href="http://www.vishay.com/doc?95558">www.vishay.com/doc?95558</a>
Application Note	<a href="http://www.vishay.com/doc?95580">www.vishay.com/doc?95580</a>



## EMIPAK-1B PressFit

**DIMENSIONS** in millimeters





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.