



PCB LAYOUT  
(Top View)

**RoHS compliant**  
Unit:mm

Scale	Free								
TOLERANCE									
.XX	±0.20								
.XXX	±0.13								
.XXXX	±0.05								
DIM	TOL								
Angle	+0°30'	Id.	Drawn	Modification	Date	Name	Date	Name	
			①		04.08.2016	Winnie			

- Specification:
- Electrical Char  
Insulation Resistance: 500MΩ min. 500V DC for 1 minute  
Contact Resistance: 30mΩ max.  
Rating Current: 1.5A max.  
Rating Voltage: 150V AC  
Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
  - Physical Char  
Housing: PBT Glass filled (UL 94V-0) Color: Black  
Soldering Temperature: 235°C for 5 sec.  
Spring Wire: 0.45mm Dia Phosphor Bronze  
6u" Gold plating over Nickel  
Temperature Range: -40°C to +85°C  
Durability: 750 mating cycles min.
  - Packing: Tray

Customer-No.	ASSMANN WSW-No.		Drawing-No.	Replace	SHEET
	A-2004-2-4-LPS-N-R		ASS 7323 CO	rev00	
	Date		Name		
	04.08.2016		Winnie		
	Date		Name		
	04.08.2016		Winnie		



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H