

IMPACT

TE Internal #: 2007716-1

High Speed Backplane Connectors, 120 Position, Mating Alignment, Keyed Mating Alignment Type, 12 Row, 10 Column,

PCB Mount Receptacle, IMPACT

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors











Connector System: Board-to-Board

Number of Positions: 120

Row-to-Row Spacing: 1.35 mm [.053 in]

Mating Alignment: With

Mating Alignment Type: Keyed

Features

Product Type Features

Connector System Board-to-Board PCB Connector Assembly Type PCB Mount Receptacle Shroud Style Unshrouded Connector & Contact Terminates To Printed Circuit Board Configuration Features Number of Ground Positions 40 Number of Pairs 40 Stackable No Number of Signal Positions 80 Number of Positions 120 Number of Rows 12 Number of Columns 10 PCB Mount Orientation Right Angle	Signal Arrangement	Differential
Shroud Style Unshrouded Connector & Contact Terminates To Printed Circuit Board Configuration Features Number of Ground Positions 40 Number of Pairs 40 Stackable No Number of Signal Positions 80 Number of Positions 120 Number of Rows 12 Number of Columns 10	Connector System	Board-to-Board
Connector & Contact Terminates To Printed Circuit Board Configuration Features Number of Ground Positions 40 Number of Pairs 40 Stackable No Number of Signal Positions 80 Number of Positions 120 Number of Rows 12 Number of Columns 10	PCB Connector Assembly Type	PCB Mount Receptacle
Configuration FeaturesNumber of Ground Positions40Number of Pairs40StackableNoNumber of Signal Positions80Number of Positions120Number of Rows12Number of Columns10	Shroud Style	Unshrouded
Number of Ground Positions40Number of Pairs40StackableNoNumber of Signal Positions80Number of Positions120Number of Rows12Number of Columns10	Connector & Contact Terminates To	Printed Circuit Board
Number of Pairs40StackableNoNumber of Signal Positions80Number of Positions120Number of Rows12Number of Columns10	Configuration Features	
StackableNoNumber of Signal Positions80Number of Positions120Number of Rows12Number of Columns10	Number of Ground Positions	40
Number of Signal Positions80Number of Positions120Number of Rows12Number of Columns10	Number of Pairs	40
Number of Positions120Number of Rows12Number of Columns10	Stackable	No
Number of Rows12Number of Columns10	Number of Signal Positions	80
Number of Columns 10	Number of Positions	120
	Number of Rows	12
PCB Mount Orientation Right Angle	Number of Columns	10
	PCB Mount Orientation	Right Angle



Guide Location	Right
Electrical Characteristics	
Impedance	100 Ω
Operating Voltage	30 VAC
Signal Characteristics	
Number of Differential Pairs per Column	4
Data Rate	20 – 25 Gb/s
Body Features	
Primary Product Color	Black
Contact Features	
PCB Contact Termination Area Plating Material Thickness	1.27 μm[50 μin]
Contact Layout	Inline
Contact Type	Socket
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]
Contact Mating Area Plating Material	Gold
Contact Shape & Form	Dual Beam
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	.75 A
Termination Features	
Termination Post & Tail Length	1.2 mm[.047 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mount Alignment Type	Locating Posts
Guide Hardware	With
Mating Retention	Without
PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail & Screw
Mating Alignment	With
Mating Alignment Type	Keyed



Connector Mounting Type	Board Mount
Housing Features	
Number of Shrouded Sides	0
Housing Material	LCP - GF (Liquid Crystal Polymer)
Centerline (Pitch)	1.9 mm[.075 in]
Dimensions	
Connector Length	26.6 mm[1.047 in]
Connector Height	17.3 mm[.681 in]
Connector Width	28.2 mm[1.11 in]
PCB Thickness (Recommended)	1 mm
PCB Hole Diameter	.39 mm[.015 in]
Row-to-Row Spacing	1.35 mm[.053 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Approved Standards	CSA Certified, UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tube, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | IMPACT



Customers Also Bought

















Documents

Product Drawings

IMP100S,R,RA4P10C,RG,39

English

CAD Files

Customer View Model

ENG_CVM_CVM_2007716-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2007716-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2007716-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773458-1_IMPACT_BACKPLANE_CONNECTOR_SYSTEM_CATALOG

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_2007716-1_011420151253_dmtec

English

MD_2007716-1_011420151253_dmtec

English

Agency Approvals

Agency Approval Document

English