BGA Heat Sink - High Performance Ultra Low Profile





ATS Part#: **ATS-60002-C1-R0**

Description: 58.20 x 61.00 x 5.50 mm BGA Heat Sink - High Performance Ultra Low Profile

Heat Sink Type: Ultra Low profile
Heat Sink Attachment: Thermal Tape
Equivalent Part Number: ATS-60002-C2-R0

*Image above is for illustration purpose only.


Features & Benefits

- bluelCE™ heat sinks feature an ultra low profile for tough-to-cool applications
- Designed for high performance in low air velocities
- Ideal for telecommunications applications where space is limited
- · Comes preassembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4 °C/W	3.1 °C/W	2.5 °C/W	2.2 °C/W	1.8 °C/W	1.7 °C/W	1.5 °C/W
	Ducted Flow	2.3	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail



Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
58.20 mm	61.00 mm	5.50 mm	66.3 mm	T412	GOLD-ANODIZED

Notes:

- Dimension A and B refer to component size.
- Dimension C is the heat sink height from the bottom of the base to the top of the fin field.
- ATS-60002-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675).
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.
- Contact ATS to learn about custom options available.

