

USB 3.0 PFT A plug - A HIFFF jack 1,5m



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 45 545 1932 |
| Specification | USB 3.0 PFT A plug - A HIFFF jack 1,5m |
| HARTING eCatalogue | https://b2b.harting.com/09455451932 |

Version

| | |
|-----------------|---|
| Cable length | 1.5 m |
| Number of cores | 8 |
| Core structure | 4x AWG 26/7 2x AWG 28/7 2x AWG 22/7 |
| Shielding | Shielded |

Technical characteristics

| | |
|--|---|
| Rated current | 1.5 A |
| Rated voltage | 30 V DC |
| Data rate | 5 Gbit/s |
| Insulation resistance | $>10^8 \Omega$ |
| Contact resistance | $\leq 30 \text{ m}\Omega$ |
| Limiting temperature | -40 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP65 IP67 |
| Cable diameter | 6.2 mm |
| Test voltage $U_{r.m.s.}$ | 0.5 kV (contact-contact) 0.5 kV (contact-ground) |
| Impedance | 90 $\Omega \pm 15 \%$ |

Material properties

| | |
|------------------|-------|
| Material (cable) | PVC |
| Colour (cable) | Black |



Pushing Performance
Since 1945

Material properties

| | |
|-----------------------------|---------------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |

Specifications and approvals

| | |
|----------------|--------------------------------|
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|--------------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 110.7 g |
| Country of origin | China |
| European customs tariff number | 85444290 |
| GTIN | 5713140263352 |
| eCl@ss | 27060390 Ready-made data cable (unspecified) |