



## Netshelter RX 42U Enclosure 800mm x 1000mm

NSYSFRSEDC208100

V

Presentation

NEMA 12 rated assembled enclosure for OT, IT and networking applications. Form factor to easily roll through doorways. Configurable to work as a ventilated enclosure with the addition of Climasys ventilation components. Includes: Front and rear solid doors with handle and insert key, side panels, 19" uprights, bottom plinth, grounding and gland plate at the bottom panel. Ventilation system not included. Can be shipped pre-integrated with UPS, PDU, monitoring components and internal equipment up to

Usually Ships within 4 Weeks

350 lbs

400 kg static

**Physical** 

Lead time

Height 2100 mm Width 800 mm Depth 1000 mm Number of rack unit 42U **Product weight** 196 kg Mounting mode Rack-mounted **Mounting preference** No preference Maximum mounting depth 852 mm Max CTO ship weight 221 kg

## **Packing Units**

Permanent permissible load

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	228.0 cm
Package 1 Width	94.0 cm
Package 1 Length	116.0 cm
Package 1 Weight	256.0 kg

## Offer Sustainability

EU RoHS Directive Not applicable, out of EU RoHS legal scope

## Recommended replacement(s)