

M12-PCB-THR-2PC-5P-KCOD-M-STR- Front 1pc



Specification	M12-PCB-THR-2PC-5P-KCOD-M-STR- Front 1pc
HARTING eCatalogue	https://b2b.harting.com/21033091531

21 03 309 1531

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Identification	Power PushPull
Element	PCB adapter
Specification	Straight incl. housing for front mounting

Part number

Version

Termination method	Reflow soldering termination (THR)
Gender	Male
Shielding	Shielded
Number of contacts	5
Number of power contacts	4
Number of special contacts	1
Specification of special contacts	PE contact
Coding	K-coding
Locking type	Screw locking PushPull

Technical characteristics

Rated current	12 A
Rated voltage	630 V



Technical characteristics

Rated impulse voltage	6 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 ⁸ Ω
Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Limiting temperature	-40 +125 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Isolation group	I (600 ≤ CTI)

Material properties

·	
Material (insert)	Polyamide (PA)
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material (seal)	NBR
Colour (seal)	Grey
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26



Specifications and approvals

Canadiana	IEC 61076-2-111
Specifications	IEC 61076-2-010

Commercial data

Packaging size	1
Net weight	31 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140228399
eCl@ss	27460201 PCB connector (board connector)