

CT09E-04T273-5

 Rev. 0-2022
 RoHS3 & REACH
 Electromagnetic Sound Transducers



Operating Characteristics

ELECTRICAL

Rated Voltage	3 Vo-p
Operating Voltage	2 to 4 Vo-p
Coil Resistance	20 ± 3 Ω
Max Current at V Rated	70 mA

ACOUSTIC

Min SPL at V Rated	86 dB
Test Conditions	10 cm
f_o	2730 Hz



Physical Characteristics

MATERIAL


Housing	Plastic
Diaphragm	Iron
Through-hole Pin	Tin Plated Copper

TEMPERATURE RANGES

Operating	-30 to +70 °C
Storage	-40 to +85 °C

Weight 1 g

Unless otherwise specified, tolerance: ±0.5mm



All Measurements are mm unless noted otherwise.

Revision	Description	By	Date
0-2022	Original Specification	CT	2022-01-07

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

©2022 Challenge Electronics, Inc. Pub. 20220107111835