

**Full bridge  
Series & SiC parallel diodes  
MOSFET Power Module**

**$V_{DSS} = 500V$**   
 **$R_{DSon} = 75m\Omega$  typ @  $T_j = 25^\circ C$**   
 **$I_D = 46A$  @  $T_c = 25^\circ C$**

**Application**



- Motor control
- Switched Mode Power Supplies
- Uninterruptible Power Supplies

**Features**

- **Power MOS 7<sup>®</sup> MOSFETs**
  - Low  $R_{DSon}$
  - Low input and Miller capacitance
  - Low gate charge
  - Avalanche energy rated
- **Parallel SiC Schottky Diode**
  - Zero reverse recovery
  - Zero forward recovery
  - Temperature Independent switching behavior
  - Positive temperature coefficient on VF
- Kelvin source for easy drive
- Very low stray inductance
- Lead frames for power connections
- Internal thermistor for temperature monitoring
- High level of integration

**Benefits**

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS Compliant



**All ratings @  $T_j = 25^\circ C$  unless otherwise specified**

**Absolute maximum ratings**

Symbol	Parameter	Max ratings	Unit
$V_{DSS}$	Drain - Source Breakdown Voltage	500	V
$I_D$	Continuous Drain Current	$T_c = 25^\circ C$	46
		$T_c = 80^\circ C$	34
$I_{DM}$	Pulsed Drain current	184	A
$V_{GS}$	Gate - Source Voltage	$\pm 30$	V
$R_{DSon}$	Drain - Source ON Resistance	90	$m\Omega$
$P_D$	Maximum Power Dissipation	$T_c = 25^\circ C$	357
$I_{AR}$	Avalanche current (repetitive and non repetitive)	46	A
$E_{AR}$	Repetitive Avalanche Energy	50	mJ
$E_{AS}$	Single Pulse Avalanche Energy	2500	

**CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on [www.microsemi.com](http://www.microsemi.com)

**Electrical Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 500V			100	μA
		T <sub>j</sub> = 25°C				
		V <sub>GS</sub> = 0V, V <sub>DS</sub> = 400V			500	
		T <sub>j</sub> = 125°C				
R <sub>DS(on)</sub>	Drain – Source on Resistance	V <sub>GS</sub> = 10V, I <sub>D</sub> = 23A		75	90	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 2.5mA	3		5	V
I <sub>GSS</sub>	Gate – Source Leakage Current	V <sub>GS</sub> = ±30 V, V <sub>DS</sub> = 0V			±100	nA

**Dynamic Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> = 0V		5590		pF
C <sub>oss</sub>	Output Capacitance	V <sub>DS</sub> = 25V		1180		
C <sub>rss</sub>	Reverse Transfer Capacitance	f = 1MHz		85		
Q <sub>g</sub>	Total gate Charge	V <sub>GS</sub> = 10V		123		nC
Q <sub>gs</sub>	Gate – Source Charge	V <sub>Bus</sub> = 250V		33		
Q <sub>gd</sub>	Gate – Drain Charge	I <sub>D</sub> = 46A		65		
T <sub>d(on)</sub>	Turn-on Delay Time	<b>Inductive switching @ 125°C</b> V <sub>GS</sub> = 15V V <sub>Bus</sub> = 333V I <sub>D</sub> = 46A R <sub>G</sub> = 5Ω		18		ns
T <sub>r</sub>	Rise Time			35		
T <sub>d(off)</sub>	Turn-off Delay Time			87		
T <sub>f</sub>	Fall Time			77		
E <sub>on</sub>	Turn-on Switching Energy	<b>Inductive switching @ 25°C</b> V <sub>GS</sub> = 15V, V <sub>Bus</sub> = 333V I <sub>D</sub> = 46A, R <sub>G</sub> = 5Ω		453		μJ
E <sub>off</sub>	Turn-off Switching Energy			726		
E <sub>on</sub>	Turn-on Switching Energy	<b>Inductive switching @ 125°C</b> V <sub>GS</sub> = 15V, V <sub>Bus</sub> = 333V I <sub>D</sub> = 46A, R <sub>G</sub> = 5Ω		745		μJ
E <sub>off</sub>	Turn-off Switching Energy			846		
R <sub>thJC</sub>	Junction to Case Thermal Resistance				0.35	°C/W

**Series diode ratings and characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V <sub>RRM</sub>	Peak Repetitive Reverse Voltage				600	V
I <sub>RM</sub>	Reverse Leakage Current	V <sub>R</sub> = 600V			50	μA
I <sub>F</sub>	DC Forward current	T <sub>c</sub> = 80°C		50		A
V <sub>F</sub>	Diode Forward Voltage	I <sub>F</sub> = 50A		1.6	2	V
		V <sub>GE</sub> = 0V	T <sub>j</sub> = 25°C			
			T <sub>j</sub> = 150°C	1.5		
t <sub>rr</sub>	Reverse Recovery Time	I <sub>F</sub> = 50A	T <sub>j</sub> = 25°C	100		ns
			T <sub>j</sub> = 150°C	150		
Q <sub>rr</sub>	Reverse Recovery Charge	V <sub>R</sub> = 300V	T <sub>j</sub> = 25°C	2.6		μC
			di/dt = 1800A/μs	T <sub>j</sub> = 150°C	5.4	
E <sub>rr</sub>	Reverse Recovery Energy		T <sub>j</sub> = 25°C	0.60		mJ
			T <sub>j</sub> = 150°C	1.2		
R <sub>thJC</sub>	Junction to Case Thermal Resistance				1.42	°C/W

**Parallel diode ratings and characteristics**

<i>Symbol</i>	<i>Characteristic</i>	<i>Test Conditions</i>		<i>Min</i>	<i>Typ</i>	<i>Max</i>	<i>Unit</i>
V <sub>RRM</sub>	Peak Repetitive Reverse Voltage					600	V
I <sub>RM</sub>	Reverse Leakage Current	V <sub>R</sub> =600V	T <sub>j</sub> = 25°C		100	400	μA
			T <sub>j</sub> = 175°C		200	2000	
I <sub>F</sub>	DC Forward Current		T <sub>c</sub> = 125°C		20		A
V <sub>F</sub>	Diode Forward Voltage	I <sub>F</sub> = 20A	T <sub>j</sub> = 25°C		1.6	1.8	V
			T <sub>j</sub> = 175°C		2.0	2.4	
Q <sub>C</sub>	Total Capacitive Charge	I <sub>F</sub> = 20A, V <sub>R</sub> = 600V di/dt = 800A/μs			56		nC
Q	Total Capacitance	f = 1MHz, V <sub>R</sub> = 200V			130		pF
		f = 1MHz, V <sub>R</sub> = 400V			100		
R <sub>thJC</sub>	Junction to Case Thermal Resistance					1.5	°C/W

**Thermal and package characteristics**

<i>Symbol</i>	<i>Characteristic</i>	<i>Min</i>	<i>Max</i>	<i>Unit</i>		
V <sub>ISOL</sub>	RMS Isolation Voltage, any terminal to case t = 1 min, 50/60Hz	4000		V		
T <sub>J</sub>	Operating junction temperature range	-40	150	°C		
T <sub>JOP</sub>	Recommended junction temperature under switching conditions	-40	T <sub>Jmax</sub> -25			
T <sub>STG</sub>	Storage Temperature Range	-40	125			
T <sub>C</sub>	Operating Case Temperature	-40	100			
Torque	Mounting torque	To Heatsink	M5	2.5	4.7	N.m
Wt	Package Weight				160	g


**Temperature sensor NTC** (see application note APT0406 on www.microsemi.com).

<i>Symbol</i>	<i>Characteristic</i>	<i>Min</i>	<i>Typ</i>	<i>Max</i>	<i>Unit</i>
R <sub>25</sub>	Resistance @ 25°C		50		kΩ
ΔR <sub>25</sub> /R <sub>25</sub>			5		%
B <sub>25/85</sub>	T <sub>25</sub> = 298.15 K		3952		K
ΔB/B		T <sub>C</sub> =100°C	4		%

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$

T: Thermistor temperature  
 R<sub>T</sub>: Thermistor value at T


**SP4 Package outline** (dimensions in mm)















ALL DIMENSIONS MARKED "\*" ARE TOLERANCED AS  $\pm 0.1$





See application note APT0501 - Mounting Instructions for SP4 Power Modules on [www.microsemi.com](http://www.microsemi.com)

**Typical MOSFET Performance Curve**







**Typical SiC Diode Performance Curve**
**Maximum Effective Transient Thermal Impedance, Junction to Case vs Pulse Duration**

**Forward Characteristics**

**Reverse Characteristics**

**Capacitance vs. Reverse Voltage**


DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.