

## Marker strip - SK 2,8 WH:REEL - 0805205

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Marker strip, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK X, THERMOMARK S1.1, THERMOMARK ROLL X1, Mounting type: Adhesive, Lettering field: Continuous x 2.8 mm

### Product Features

- The markers supplied in card format can be easily labeled using standard laser printers
- The markers that are supplied in roll format can be labeled quickly and cost-effectively using THERMOMARK printers
- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove
- Ideal for labeling COMBICON connectors
- Labeling service: Phoenix Contact can custom-label SK markers according to your requirements
- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 1216.6 g |
| Custom tariff number                 | 39199000 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                    |          |
|--------------------|----------|
| Length (b)         | 90 m     |
| Width (a)          | 2.8 mm   |
| Inner diameter (f) | 76.00 mm |

#### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Ambient temperature (operation) | -40 °C ... 150 °C  |
| Ambient temperature (assembly)  | > 15 °C  |
| Recommended storage conditions  | 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing. |

#### General

|                       |           |
|-----------------------|-----------|
| Color                 | white     |
| Base element material | Polyester |

# Marker strip - SK 2,8 WH:REEL - 0805205

## Technical data

### General

|   |                                     |
|---|-------------------------------------|
| Components  | free from silicone and halogen      |
| Flammability rating according to UL 94                              | V2                                  |
| Material  | Polyester                           |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)         |
| Number of individual labels   | 480000                              |
| Number of individual labels per row                                 | 10                                  |
| Number of marker strips   | 14                                  |
| Adhesive  | Acrylic                             |
| Printability  | Thermal transfer                    |
| Device  | 5146477 THERMOMARK ROLL             |
|   | 5146231 THERMOMARK X1.2             |
| Ink ribbon  | 5145384 THERMOMARK-RIBBON 110       |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result  | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration   | 96 h                                |
| Wipe resistance test result   | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration   | 96 h                                |
| Salt spray testing result   | Test passed                         |
| Alternating condensation climate with SO2 test specification        | DIN 50018:2013-05                   |
| Climate level   | AHT 1.0 S                           |
| Cycles  | 2                                   |
| Condensation test result  | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result  | Test passed                         |
| Foil strength   | 53 µm                               |
| Adhesive strength   | 20 µm                               |
| Marking mounting type   | Adhesive                            |

### Standards and Regulations

|  |                             |
|--|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V2                          |

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190208 |
|------------|----------|

## Marker strip - SK 2,8 WH:REEL - 0805205

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |