

**Data sheet | Item number: 221-941**

Jumper; for conductor entry; 2-way; insulated; dark gray

[www.wago.com/221-941](http://www.wago.com/221-941)



Color:

**Data**

**Electrical data**

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated current	41 A

## Physical data

Jumper assignment	1-2
-------------------	-----

## Material Data

Note (material data)	Information on material specifications can be found here
Color	dark gray
Insulation material	Polyamide (PA66)
Weight of insulation material	0.45 g
Weight	2.9 g

## Environmental requirements

Continuous operating temperature	-60 ... +105 °C
----------------------------------	-----------------

## Commercial data

ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	5 pcs
Packaging type	bag
Country of origin	CN
GTIN	4055144067873
Customs tariff number	85366990990

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Documentation

### Bid Text

Subject to changes. Please also observe the further product documentation!



221-941 X81 - Datei	xml 3.0 kB	Download
------------------------	---------------	----------

221-941 doc - Datei	docx 28.1 kB	Download
------------------------	-----------------	----------

**Additional Information**

	pdf 2.3 MB	Download
--	---------------	----------

**CAD/CAE-Data**

**CAD data**

2D/3D Models 221-941	URL	Download
----------------------	-----	----------

**Environmental Product Compliance**

**Compliance Search**

Environmental Product Compliance 221-941 Jumper; for conductor entry; 2-way; insulated; dark gray	URL	Download
--	-----	----------

**Installation Notes**

**Commoning**



Extending the N and PE (ground) distribution via jumper

**Commoning**

Subject to changes. Please also observe the further product documentation!




Insert the jumper without a locking function into open clamping units.

### Commoning



Without a locking function:  
The jumper without a locking function is plugged into the splicing connectors.

### Commoning



Remove the locking mechanism for intentional jumper removal.



Remove the jumper from open clamping units.

Subject to changes. Please also observe the further product documentation!