

Technical Data Sheet

USB 2-Port Serial RS-232 Industrial Adapter w/ FTDI Chipset

Model Number: GM-FTDI2X-M

Rev 03.210420



2-port USB to Serial 9 Pin RS-232 Industrial adapter with Surface or Din Rail mounting Configuration. Surface Visible Power and Activity LED's for easy diagnostic review. Utilizes FT2232H FTDI Chip set Automatically configures the additional COM ports Plug and Play allows easy installation Perfect for connecting serial modems, bar code scanners, CNC routers, and others Rugged metal industrial design

Features

- Utilizes FT2232H FTDI Chip set
- Automatically configures the additional COM ports
- Plug and Play allows easy installation
- Perfect for connecting serial modems, bar code scanners, CNC routers, and others
- Wall-mountable, with included DIN Rail clips

Product Information

- Model Number: GM-FTDI2X-M
- Packing List:
 -

Specifications
OVERVIEW

Product Type	USB Serial Adapter
Electrical Protections	N/A
Mountable	Surface Mount
Material	
Compliance	N/A
LED indicators	Power, TX/RX
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	Odd, Even, Mark, Space, None
Stop Bits	1, 2
Flow Control	
FIFO	

Specifications Cont.**ENVIRONMENTAL**

Operating Temperature	0C ~ 40C
Operating Humidity	5% to 95% RH
Storage Temperature	-20c ~ 50C

PHYSICAL

Length	inches
Width	2.255906 inches
Height	0.99212598 inches
Item Weight	lbs
Ship Weight	0.9500 lbs

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7
-----------------------------	---

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

GM-FTDI2X-M Product Page	https://www.gearmo.com/shop/gearmo-usb-2-port-serial-rs232-featuring-ftdi-chipset-with-led-indicators/
--------------------------	---