



NOTES 1 ONE EXAMPLE OF THE ROTATION OF REF. NO. ①, ② AND ③ IS SHOWN.
 ② THE RECOMMENDED CLAMP TORQUE REF. NO. ⑨: 3 TO 4 N · m.
 LOCITITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑨ FROM LOOSENING.
 ③ AGRISS FLATS HEXAGON HEAD OF REF. NO. ⑩: 1.27
 THE RECOMMENDED CLAMP TORQUE REF. NO. ⑩: 0.3 TO 0.4 N · m
 LOCITITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑩ FROM LOOSENING.
 4 THIS PRODUCT TO BE USED WITH CABLECLAMP, JR13WC-*(72)
 * DESIGNATE DIAMETER OF APPLICABLE CABLE.
 LOCITITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT FROM LOOSENING.
 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,
 DEPENDING ON THE CABLE STRUCTURE.
 PLEASE CONFIRM BEFORE THE USE.

7	STEEL	NICKEL PLATING	13	STEEL	JISB1177 HEXAGON SOCKET SET SCREW M2.6X0.45X2
6	BRASS	NICKEL PLATING	12	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)
5	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)	11	PHOSPHOR BRONZE	NICKEL PLATING
4	BRASS	SILVER PLATING 2 μm min.	10	BRASS	NICKEL PLATING
3	BRASS	SILVER PLATING 2 μm min.	9	BRASS	NICKEL PLATING
2	POLYBUTYLENE TEREPHTHALATE	(BLACK) UL94V-0	8	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	NICKEL PLATING			

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					
APPROVED : HY. KOBAYASHI		18.02.22		DRAWING NO. EDC-113405-31-00		
CHECKED : HY. KOBAYASHI		18.02.22		PART NO. HR22-12WTLR-20P(31)		
DESIGNED : HY. KISHI		18.02.21		CODE NO. CL122-0054-5-31		
DRAWN : MK. INOUE		18.02.06		NO. 1		