


# LINOS F-Theta-Ronar Lens


f = 420mm, 1064nm



Part number	4401-350-000-21		
Design wavelength	$\lambda$	(nm)	1064
Effective focal length	EFL	(mm)	420.5
Back focal length	BFL	(mm)	497.1
Working distance	WD	(mm)	494.2
Flange focal length	FFL	(mm)	548.8
Beam diameter 1/e <sup>2</sup> truncated	$\varnothing_{\text{beam}}$	(mm)	15.0
Recommended mirror distance m1	m1	(mm)	30.0
Recommended mirror distance m2	m2	(mm)	16.0
Recommended mirror distance m2 <sub>mechanical</sub>	m2 <sub>m</sub>	(mm)	8.3
Scan angle	$\pm\theta_{x,y}$	(°)	19.8
Scan area (edge length of scan field)	2x * 2y	(mm <sup>2</sup> )	291 x 291
Spot diameter	$\varnothing_{\text{spot}}$	( $\mu\text{m}$ )	55
Total transmission @ 1064nm	T	(%)	> 96
LIDT coating @ 1064nm, 9ns, 100Hz		(J/cm <sup>2</sup> )	10
Focused back reflex positions from first surface		(mm)	2.3; 42.1; 61.0; 137.2; 137.5
Weight		(g)	1050
Protective glass	PG		4401-288-005-01

Optical parameters calculated for a 1-mirror system  
 Subject to technical change

**Mechanical drawing**



Dimensions without tolerances are nominal values and illustration not to scale

**Notes**



For technical explanations, see our homepage.

In a 1-mirror system, the entrance pupil (EP) is the position of the scan mirror. In a 2-mirror system, it is the point where the scan mirrors should be placed around symmetrically to reach specified performance.