

**NOTES:**

**MATERIAL:**  
 HOUSING : HIGH IMPACT NYLON 66, HALOGEN AND PHOSPHOR FREE  
 UL94V-0, BLACK, UL FILE # E48285

**RIVETS: BRASS, NICKLE PLATED.**


**SPRING: 302 STAINLESS STEEL, NICKLE PLATED.**

**WIRE: 24AWG, UL1007, CSA, TR64**

**TEMPERATURE RANGE: -40°C TO +140°C**

**RESISTANT TO SOLVENTS, COMMON OILS AND REFRIGERANTS**

**MOUNTING INSTRUCTION:**  
 USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT. ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735	
decimal ±.5 (.020)	Scale	Drawn By B.S.
Fractional ± .8 (.030)	Title FOUR "AAA" CELL HOLDER	
Angular ± 3°	Date 10/18/03	Drawing Number BH4AAAW