



			1	
	TE082603-2		DRAWN	
			CJ	5/4/2018
	I EU82	2003-2	CHECKED	5/4/2018
			C.H.	
	Description:	nical Transducer	APPROVED	5/4/2018
	Electro-Mechai		C.E.	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


## Top View




## Side View (1)



## **Bottom View**



## Side View (2)



	Items	Specifications	Conditions					
	Min. Sound Pressure Level	90	dBA (@ 10cm)					
	Resonant Frequency	2,670	Hz					
	Rated Voltage	3.6	V	REVISION HISTORY				
	Voltage Range	2.5 ~ 4.5	V	REV	DESCRIPTION	DATE	APPROVED	
	Coil Resistance	16 ± 2.4	Ω		Released from Engineering	10/21/2013	J.S.	
,	Max. Rated Current	90	mA	1	Updated voltage range, temperatures, and template	5/4/2018	C.E.	
A	Storage Temperature	-40 ~ +85	°C		NOTES			
	Operating Temperature	-40 ~ +85	°C		All dimensions are in mm unless otherwise noted			
	Connection Method	SMD			2) All tolerances are ± 0.2 mm unless otherwise noted			
	Mount Type	Surface Mount			3) All parts meet RoHS			
	Housing Material	LCP			4) Subject to change or redrawn without notice			
	Weight	0.4	g					