



General ordering data

| | |
|------------------|---|
| Order No. | 9510310000 |
| Part designation | Klippon POK 10 Ex |
| Version | EXI enclosure, 120 mm, 405 mm, 400 mm, glass fibre-reinforced polyester |
| EAN | 4008190498801 |
| Qty. | 1 pc(s). |

Dimensions

| | |
|--------------------------|--------|
| Fixing dimension, height | 355 mm |
| Fixing dimension, width | 380 mm |
| Height | 120 mm |
| Length | 405 mm |
| Width | 400 mm |

General details

| | |
|---------------------------------|------------------------------|
| Cover fixing | 4 stainless steel M6 screws |
| Enclosure fixing | Holes 6 mm |
| Sealing material | Polyurethane and chloroprene |
| Colour | grey |
| Class of protection to EN 60529 | IP 66 |
| Weight | 5,580 g |
| Ambient temperature, min. | -40 °C |
| Ambient temperature, max. | 90 °C |

Screwed cable glands top/bottom

| | |
|-------------------|--------------|
| M 12 | 62 |
| M 16 | 54 |
| M 20 | 33 |
| M 25 | 18 |
| M 32 | 14 |
| M 40 | 6 |
| M 50 | 4 |
| Side of enclosure | Top / Bottom |

Screwed cable glands, left/right

| | |
|-----------------|--------------|
| M12 | 60 |
| M16 | 39 |
| M20 | 30 |
| M25 | 18 |
| M32 | 7 |
| M40 | 5 |
| M50 | 4 |
| On housing side | left / right |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| ETIM 2.0 | EC000520 |
| ETIM 3.0 | EC000049 |
| eClass 4.1 | 27-14-12-06 |
| eClass 5.0 | 27-18-05-02 |
| eClass 5.1 | 27-18-05-02 |

Similar products

| Order No. | Part designation | Version |
|------------|------------------|--|
| 1565440000 | Klippon POK 10 | Housings, 120 mm, 405 mm, 400 mm, glass fibre-reinforced polyester |