

Economy Power

TE Internal #: 1744037-2 Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header

Connector & Housing Type: Plug

Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 5.08 mm [.2 in]

Features



Product Type Features

Header Type	Partially Shrouded			
Rectangular Power Connector Type	Header			
Connector & Housing Type	Plug			
Connector System	Wire-to-Board			
Sealable	No			
Connector & Contact Terminates To	Printed Circuit Board			
Configuration Features				
Number of Positions	2			
PCB Mount Orientation	Vertical			
Number of Power Positions	2			
Number of Rows	1			
Electrical Characteristics				
Operating Voltage	250 VDC			

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power



PCB Contact Termination Area Plating Material Thickness	.8 μm, 1 μm[31.49 μin][39.37 μin]	
Contact Layout	Inline	
Contact Mating Area Plating Material	Tin	
Contact Base Material	Copper Alloy	
Contact Current Rating (Max)	8 A	
Contact Retention Within Housing	Without	
Contact Type	Pin	
PCB Contact Termination Area Plating Material	Tin	
Contact Mating Area Plating Material Thickness	2.03 μm[80 μin]	
Fermination Features		
Termination Post & Tail Length	3.7 mm[.146 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	
Mechanical Attachment		
Strain Relief	Without	
Mating Retention	With	
Mating Alignment	With	
PCB Mount Alignment	Without	
Panel Mount Feature	Without	
PCB Mount Retention	Without	
Mating Retention Type	Latch	
Connector Mounting Type	Board Mount	
Housing Features		
Centerline (Pitch)	5.08 mm[.2 in]	
Housing Color	Natural	
Housing Material	Nylon 66	
Dimensions		
Connector Height	10.9 mm[.429 in]	
PCB Thickness (Recommended)	.06 mm[1.6 in]	
Product Width	8.2 mm[.323 in]	
Product Length	7.68 mm[.302 in]	
Jsage Conditions		
Operating Temperature Range	-25 – 105 °C[-13 – 221 °F]	

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power



Operation/Application

Circuit Application	Power	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Glow Wire Rating	Standard Part - Not Glow Wire	
Packaging Features		
Packaging Quantity	1000	
Packaging Method	Bag	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233)	

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Wave solder capable to 240°C

Does not contain REACH SVHC

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power





TE Part # 1744036-2 02P ECONOMY POWER .200 CL HSG



TE Part # 1-2316953-4 04P EP.200 CL HDR ASSY VRT, NO PIN 1,3




TE Part # 2108744-1 POWER 2P HDR ASSY L/PRO NAT





Also in the Series | Economy Power






Insertion & Extraction Tools(1)





Connector Contacts(1)	Insertion & Extraction Tools(1)	PCB Headers & Receptacles(162)	PCB Latches, Locks & Retainers(2)
Power Contacts(8)	Rectangular Connector Housings(1)	Rectangular Power Connectors(302)	Wire-to-Board Connector Assemblies & Housings(142)



Customers Also Bought

& For support call+1 800 522 6752

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power







Documents

Product Drawings 02P EC PWR.200 CL HDR ASSY VRT

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1744037-2_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1744037-2_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1744037-2_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1-1773885-9 Economy Power Connectors

English

Product Specifications Application Specification

English

Application Specification

Japanese

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 2 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0, Economy Power



Product Environmental Compliance

MD_1744037-2_07262017155_dmtec

English

MD_1744037-2_07262017155_dmtec

English

Agency Approvals

UL Report

English