


Contact assignment:

- 1) brown
- 2) white
- 3) blue
- 4) black
- 5) green-yellow

Contact assignment:

- 1) white
- 2) brown
- 3) green
- 4) yellow
- 5) grey
- 6) pink
- 7) blue
- 8) red



Technical specification:

Rated voltage:	4pos	5pos	8pos
IEC 61076-2-101	250 V	60 V	30 V
Current rating:	4/5pos	8pos	
IEC 61076-2-101	4 A at 40°C	2 A at 40°C	
Insulation resistance:	≥100 MΩ		
IEC 60512			
Pollution degree:	3/2		
IEC 60664-1			
Degree of protection:	IP 67, in mated condition		
IEC 60529			
Temperature range:	-30°C ... +80°C		
Mating cycles:	≥100		
IEC 60512-9a			

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PBT GF, UL 94
Sealing:	FPM
Counter nut:	CuZn, nickel plated
Socket housing:	CuZn, nickel plated
Grouting:	Polyurethane-resin, UL 94

Installation specification:

recommended torque:	1-1,2 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 17: 36-000230

Part no:	Description:	Pos	Length L:	Wire:
43-01091	SAL - 12 - FKP4 - 0,5 - 9	4	0,5m	AWG 24 PVC, UL
43-xxxxx	SAL - 12 - FKP4 - ... - 9	4	x	
43-01093	SAL - 12 - FKP5 - 0,5 - 9	5	0,5m	
43-xxxxx	SAL - 12 - FKP5 - ... - 9	5	x	
43-01101	SAL - 12 - FKP8 - 0,5 - 9	8	0,5m	
43-xxxxx	SAL - 12 - FKP8 - ... - 9	8	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: c 11.02.13 MG Ä4631 Data sheet revised, technical specification changed, materials corrected	dim. in mm	title: Female socket M12x1 with wire, frontmounting, reposition, PG9		
	tolerance of wire: L ≤ 0,5m: L + 20mm L > 0,5m: L + 4%	drawn 01.03.07 Fromm	dwg no: 43K1A337		
	general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm	appd. 01.03.07 Mankopf			
	CONEC ®	part no: see table			
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH					