

PAGE 1 of 6

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, appliances, light fixtures, electrical cables and similar products.



**DIELECTRIC STRENGTH TESTER (HIPOT)
MODEL AVC-25DV**

NEW DESIGN

INPUT	120 V 60 Hz 3 A
OUTPUT	Adjustable 0-2500 V ac @ 95 mA (0-2750 V ac @ open circuit)
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	DPM 0-2500 V ac @ 95 mA (0-2750 V ac @ open circuit Accuracy: $\pm 2\%$ of full scale.
TRIP CURRENT	Fixed @ 95 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, High-Voltage-on, Fault and Line-Fault)
CONTROLS	One on/off switch, one fuse, one reset push-button, one high voltage adjust-knob and safety device for faulty power-outlet.
LEADS	One input Line-Cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable High-Voltage probe. Each 2 meters (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H) Inches
WEIGHT	9.5 kg (21 Lb)

PAGE 2 of 6

This Dielectric Strength Tester, is Ideal for testing: control panels, small transformers, electrical motors, appliances, light fixtures, short electrical cables and similar products.



**DIELECTRIC STRENGTH TESTER (HIPOT)
MODEL AV-25DV-10**

INPUT	120 V 60 Hz 3 A
OUTPUT	Adjustable 0-2500 V ac @ 10 mA (0-2750 V ac @ open-circuit).
TRANSFORMER	Rate 500 VA Short Duty Cycle.
VOLTMETER	DPM 0-2500 V ac @ 10 mA (0-2750 V ac @ open-circuit) Accuracy: $\pm 2\%$ of full scale.
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, High-Voltage-on, Fault and Line Fault)
CONTROLS	One on/off switch, one fuse, one reset push-button, one high voltage adjust-knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead c/w a clip and one high voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H inches)
WEIGHT	9.5 kg (21 lb)

PAGE 3 of 6

This Dielectric Strength Tester is ideal for testing: Control panels, small transformers, small electrical motors, appliances, light fixtures, short electrical cables and similar products.




**DIELECTRIC STRENGTH TESTER (HIPOT)
MODEL AV-25DV-5**

INPUT	120 V 60 Hz 3 A
OUTPUT	Adjustable 0-2500 V ac @ 5 mA (0-2750 V ac @ open circuit)
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	DPM 0-2500 V ac @ 5 mA (0-2750 V ac @ open circuit). Accuracy: $\pm 2\%$ of full scale.
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line fault)
CONTROLS	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H inches)
WEIGHT	9.5 kg (21 lb)

PAGE 4 of 6

This Dielectric Strength Tester is ideal for testing: Control panels, transformers, electrical motors, appliances, light fixtures, electrical cables and similar products.



**DIELECTRIC STRENGTH TESTER (HIPOT)
MODEL AVC-25DVA**


INPUT	120 V 60 Hz 3A
OUTPUT	Adjustable 0-2500 V ac @ 95 mA (0-2750 V ac @ open circuit)
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	DPM 0-2500 V ac @ 95 mA (0-2750 V ac @ open circuit). Accuracy $\pm 2\%$ of full scale.
AMMETER	DPM 0-100 mA Accuracy $\pm 2\%$ of full scale.
TRIP CURRENT	Fixed @ 95 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROLS	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power outlet.
LEADS	One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H inches)
WEIGHT	9.5 kg (21 lb)

PAGE 5 of 6
 This Dielectric Strength Tester, is Ideal for testing: Control panels with electronic circuits, appliances, light fixtures with electronic ballasts, electrical cables and similar Products.



**DIELECTRIC STRENGTH TESTER (HIPOT)
 MODEL DV-25DV-10**

INPUT	120 V 60 Hz 3 A
OUTPUT	Adjustable 0-2500 V dc @ 10 mA (0-3000 V dc @ open circuit).
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	DPM 0-2500 V dc @ 10 mA 0-3000 V dc @ open circuit. Accuracy $\pm 2\%$ of full scale.
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault).
CONTROLS	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power outlet.
LEADS	One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H inches)
WEIGHT	9.5 kg (21 lb)

<p>PAGE 6 of 6</p> <p>This Dielectric Strength tester, is Ideal for testing: Control panels with electronic-circuit, light-fixtures with electronic ballasts, electrical-cables and similar products.</p>	 <p style="text-align: center;">DIELECTRIC STRENGTH TESTER (HIPOT) MODEL DV-25DV-5</p>
<p>INPUT</p>	<p>120 V 60 Hz 3 A</p>
<p>OUTPUT</p>	<p>Adjustable 0-2500 V dc @ 5 mA (0-3000 V dc @ open circuit).</p>
<p>TRANSFORMER</p>	<p>Rated 500 VA Short Duty Cycle</p>
<p>VOLTMETER</p>	<p>DPM 0-2500 V dc @ 5 mA (0-3000 V dc @ open circuit. Accuracy: $\pm 2\%$ of full scale.</p>
<p>TRIP CURRENT</p>	<p>Fixed @ 5 mA $\pm 5\%$</p>
<p>INDICATORS</p>	<p>4 Lights (Power-on, high-voltage-on, fault and line fault).</p>
<p>CONTROLS</p>	<p>One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power-outlet.</p>
<p>LEADS</p>	<p>One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.</p>
<p>SIZE</p>	<p>30W x 25D x 18H cm (12W x 10D x 7H inches)</p>
<p>WEIGHT</p>	<p>9.5 kg (21 lb)</p>