



CRADLE MUST HAVE
SLOT IN BOTTOM

NOTES:

1. MATERIALS:

FRAME & HARDWARE - STEEL, ZINC PLATED
 PIVOT PIN - STAINLESS STEEL
 ACTUATOR & LIFTER: - NYLON GLASS - FILLED NATURAL
 INSULATORS - XXXP PHENOLIC AND PPO
 SWITCH MOUNTING SCREWS - STEEL, NICKEL PLATED
 CONTACT SPRINGS - SPRING TEMPER, NICKEL SILVER WITH GOLD CONTACTS
 ACTUATOR SPRING - TINNED MUSIC WIRE
 HOUSING - ABS, BLACK

2. THIS PRODUCT IS RoHS COMPLIANT

| PART NO. | CRADLE COLOR |
|----------|--------------|
| 14412GX | BLACK |
| 14512GX | BEIGE |
| 14612GX | WHITE |

CUSTOMER DRAWING

| | | | | | | | | | | | | | | | | | | | | | | | |
|------------|--|--|--|--|---|--|--|--|--|--|--|-------|--|--------------|--|--------|--|-------------------------|--|----|--|-----|--|
| | | | | | ★ STAR SYMBOL DENOTES CRITICAL DIMENSION | | | | | THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | | | | | | | | |
| | | | | | UNLESS OTHERWISE SPECIFIED | | | | | SIZE | | WIDTH | | MULT | | LBS/M | | TEMPER | | | | | |
| | | | | | 1. ALL DIMENSIONS IN INCHES -TWO PLACE DECIMALS ±0.01 -THREE PLACE DECIMALS ±0.005 -ANGLES ±1° -ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R. | | | | | FINISH | | | | MATERIAL | | | | | | | | | |
| | | | | | 2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002 | | | | | SPEC No. | | | | SPEC No. | | | | | | | | | |
| | | | | | 3. REMOVE ALL BURRS | | | | | FIRST USED ON | | SCALE | | Switchcraft® | | | | | | | | | |
| | | | | | DO NOT SCALE DRAWING | | | | | NONE | | | | | | | | | | | | | |
| A | | | | | 26238 | | | | | DATE DRAWN | | BY | | CHKD | | APVD | | SHEET | | OF | | REV | |
| ECO NUMBER | | | | | DATE | | | | | 01-Feb-07 | | TJK | | TJK | | 2-1-07 | | 2-1-07 | | | | | |
| REVISIONS | | | | | | | | | | NAME | | | | PART No. | | | | 14412GX 14512GX 14612GX | | A | | | |

A